

SAFETY DATA SHEET

according to Regulation (EU) 2015/830

Page 1/8

Tyre and Trim

Revision 3

Revision date 2017-08-21

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name	Tyre and Trim
Product code	QAFS821

1.2. Relevant identified uses of the substance or mixture and uses advised against

Product Use	[SU21] Consumer uses: Private households (= general public = consumers); ----- [SU22] Professional uses: Public domain (administration, education, entertainment, services, craftsmen);
Description	No data is available on this product.

1.3. Details of the supplier of the safety data sheet

Company	SUPAGARD LIMITED
Address	19-27 Gavinton Street Muirend Glasgow G44 3EF
Web	www.supagard.co.uk
Telephone	0141 633 5933
Fax	01416377219
Email	James.Smyth@supagard.com
Email address of the competent person	James.Smyth@supagard.com

1.4. Emergency telephone number


Emergency telephone number	01416335933 8.30am to 5.00pm
----------------------------	---------------------------------

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

2.1.2. Classification - EC 1272/2008	Flam. Liq. 3: H226; Asp. Tox. 1: H304; STOT SE 3: H336;
--------------------------------------	---

2.2. Label elements

Hazard pictograms	
Signal Word	Danger
Hazard Statement	Flam. Liq. 3: H226 - Flammable liquid and vapour. Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways. STOT SE 3: H336 - May cause drowsiness or dizziness.

Tyre and Trim

Revision 3

Revision date 2017-08-21

2.2. Label elements

Precautionary Statement: Prevention	P102 - Keep out of reach of children. P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Precautionary Statement: Response	P301+P310 - IF SWALLOWED: IF SWALLOWED: Immediately call a POISON CENTER/doctor/ . P302+P350 - IF ON SKIN: Gently wash with plenty of soap and water. P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing. P331 - Do NOT induce vomiting.
Precautionary Statement: Storage	P403+P233 - Store in a well-ventilated place. Keep container tightly closed.

2.3. Other hazards

Other hazards	PBT not identified as a PBT substance.
----------------------	--

SECTION 3: Composition/information on ingredients

3.2. Mixtures

EC 1272/2008

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification
Hydrocarbons, C9-11, N-alkanes, Isoalkanes, Cyclics, <2% Aromatic Stoddard Solvent 2		8052-41-3	232-489-3	01-2119463258-33	50 - 60%	Flam. Liq. 3: H226; Asp. Tox. 1: H304; STOT SE 3: H336;
propan-2-ol	603-117-00-0	67-63-0	200-661-7	01-2119457558-25	0 - 0.5%	Flam. Liq. 3: H226; Asp. Tox. 1: H304; STOT SE 3: H336; STOT RE 1: H372; Aquatic Chronic 2: H411;
methanol	603-001-00-X	67-56-1	200-659-6	01-2119433307-44	0 - 0.5%	Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336; Acute Tox. 3: H331; Acute Tox. 3: H311; Acute Tox. 3: H301; STOT SE 1: H370;

Further information

Product Shelf Life	RECOMMENDED SHELF LIFE 1 YEAR FROM DATE OF DELIVERY.
Active Ingredients	Ingredients - Less than 5% Aromatic Hydrocarbons, Dimethicone, Amino functional silicone.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	Move the exposed person to fresh air.
Eye contact	Rinse immediately with plenty of water. Contact lenses should be removed.
Skin contact	Remove contaminated clothing. Wash with water and soap as a precaution.
Ingestion	DO NOT INDUCE VOMITING. If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label. Rinse mouth thoroughly.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation	High concentration of vapour in enclosed space may cause irritation, headaches and nausea. May cause irritation to respiratory system.
Eye contact	Irritating to eyes.
Skin contact	May cause skin dryness and irritation. Prolonged contact may cause defatting of the skin.
Ingestion	Harmful if ingested or swallowed.

4.3. Indication of any immediate medical attention and special treatment needed

Inhalation	TREAT SYMPTOMATICALLY. Move the exposed person to fresh air. Seek medical attention if irritation or symptoms persist.
Eye contact	Contact lenses should be removed. Rinse immediately with plenty of water. Seek medical attention if irritation or symptoms persist.

Tyre and Trim

Revision 3

Revision date 2017-08-21

4.3. Indication of any immediate medical attention and special treatment needed

Skin contact	Seek medical attention if irritation or symptoms persist.
Ingestion	Drink 1 to 2 glasses of water. Seek medical attention if irritation or symptoms persist.

General information

	If you feel unwell, seek medical advice (show the label where possible). Treat symptomatically.
--	---

SECTION 5: Firefighting measures

5.1. Extinguishing media

	Flammable liquid. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
--	---

5.2. Special hazards arising from the substance or mixture

	Burning produces irritating, toxic and obnoxious fumes.
--	---

5.3. Advice for firefighters

	Wear suitable respiratory equipment when necessary.
--	---

Further information

	In the event of a fire and/or explosion do not breath fumes. Standard procedure for chemical fires. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
--	---

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

	Wear suitable protective equipment. Flammable liquid. Avoid sparks, flames, heat and sources of ignition.
--	---

6.2. Environmental precautions

	Advise local authorities if large spills cannot be contained.
--	---

6.3. Methods and material for containment and cleaning up

	Absorb with inert, absorbent material. Sweep up. Transfer to suitable, labelled containers for disposal. Avoid sparks, flames, heat and sources of ignition.
--	--

6.4. Reference to other sections

	See section 2, 7, 8, 13 for further information.
--	--

SECTION 7: Handling and storage

7.1. Precautions for safe handling

	Adopt best Manual Handling considerations when handling, carrying and dispensing.
--	---

7.2. Conditions for safe storage, including any incompatibilities

	Flammable liquid. Avoid sparks, flames, heat and sources of ignition. Avoid storing in direct Sun Light. Store in a well-ventilated place. Keep cool. Store in original container. Keep container tightly closed. Keep away from combustible material. Keep out of the reach of children.
--	---

7.3. Specific end use(s)

	No data is available on this product.
--	---------------------------------------

Suitable packaging

	Plastic containers.
--	---------------------

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

	Occupational exposure controls.
--	---------------------------------

Tyre and Trim

Revision 3

Revision date 2017-08-21

8.1.1. Exposure Limit Values

methanol	WEL 8-hr limit ppm: 200 WEL 15 min limit ppm: 250 WEL 8-hr limit mg/m ³ total inhalable dust: - WEL 8-hr limit mg/m ³ total respirable dust: -	WEL 8-hr limit mg/m ³ : 266 WEL 15 min limit mg/m ³ : 333 WEL 15 min limit mg/m ³ total inhalable dust: - WEL 15 min limit mg/m ³ total respirable dust: -
propan-2-ol	WEL 8-hr limit ppm: 400 WEL 15 min limit ppm: 500 WEL 8-hr limit mg/m ³ total inhalable dust: - WEL 8-hr limit mg/m ³ total respirable dust: -	WEL 8-hr limit mg/m ³ : 999 WEL 15 min limit mg/m ³ : 1250 WEL 15 min limit mg/m ³ total inhalable dust: - WEL 15 min limit mg/m ³ total respirable dust: -

DNEL: Derived no-effect level.

Exposure Pattern - Workers

methanol	Acute inhalation - Systemic effects 260 mg/m ³ Acute inhalation - Local effects 260 mg/m ³ Long-term - inhalation - Systemic effects 260 mg/m ³ Long-term - dermal - Systemic effects 40 mg/kg	Acute dermal - Systemic effects 40 mg/kg Long-term - inhalation - Local effects 260 mg/m ³
propan-2-ol	Long-term - inhalation - Systemic effects 500 mg/m ³ Long-term - dermal - Systemic effects 888 mg/kg	

Exposure Pattern - General population

methanol	Acute inhalation - Systemic effects 50 mg/m ³ Acute inhalation - Local effects 50 mg/m ³ Long-term - inhalation - Systemic effects 50 mg/m ³ Long-term - dermal - Systemic effects 8 mg/kg	Acute dermal - Systemic effects 8 mg/kg Long-term - inhalation - Local effects 50 mg/m ³
propan-2-ol	Long-term - inhalation - Systemic effects 89 mg/m ³ Long-term - dermal - Systemic effects 319 mg/kg	Long-term - oral - Systemic effects 26 mg/kg

8.2. Exposure controls

	Adopt best Manual Handling considerations when handling, carrying and dispensing. Avoid contact with skin and eyes. Handle in accordance with good industrial hygiene and safety practice. Use appropriate personal protective equipment. Wear suitable protective clothing and eye/face protection.
8.2.1. Appropriate engineering controls	Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapours below their respective threshold limit value. Ensure eyewash stations and safety showers are close to the workstation location.
Eye / face protection	Avoid contact with eyes. If splashes are likely to occur, wear: safety glasses with side-shields.
Skin protection - Handprotection	Rubber gloves.
Respiratory protection	No personal respiratory protective equipment normally required. In case of insufficient ventilation wear suitable respiratory equipment.
8.2.3. Environmental exposure controls	Prevent further leakage or spillage if safe to do so.

Tyre and Trim

Revision 3

Revision date 2017-08-21

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Appearance	Liquid
Colour	Colourless
Odour	Characteristic
Odour threshold	No data available
pH	No data available
Melting point	No data available
Initial boiling point	No data available
Flash point	40 °C
Evaporation rate	No data available
Flammability (solid, gas)	No data available
Vapour pressure	No data available
Vapour density	No data available
Relative density	0.8 - 0.825
Partition coefficient	No data available
Autoignition temperature	No data available
Viscosity	No data available
Explosive properties	No data available
Oxidising properties	No data available
Solubility	No data available

9.2. Other information

Conductivity	No data available
Surface tension	No data available
Gas group	No data available
Benzene Content	No data available
Lead content	No data available
VOC (Volatile organic compounds)	No data available

SECTION 10: Stability and reactivity**10.1. Reactivity**

	Flammable liquid. Stable under normal conditions.
--	---

10.2. Chemical stability

	Flammable liquid. Stable under normal conditions.
--	---

10.3. Possibility of hazardous reactions

	Oxidising agents. Combustible materials.
--	--

10.4. Conditions to avoid

	Avoid sparks, flames, heat and sources of ignition. Avoid storing in direct Sun Light.
--	--

10.5. Incompatible materials

	Oxidising agents.
--	-------------------

10.6. Hazardous decomposition products

	No Hazardous decomposition products when stored and handled correctly. Burning produces irritating, toxic and obnoxious fumes.
--	--

SECTION 11: Toxicological information**11.1. Information on toxicological effects**

Acute toxicity	based on available data the classification criteria are not met.
-----------------------	--

Tyre and Trim

Revision 3

Revision date 2017-08-21

11.1. Information on toxicological effects

Skin corrosion/irritation	based on available data the classification criteria are not met.
Serious eye damage/irritation	based on available data the classification criteria are not met.
Respiratory or skin sensitisation	based on available data the classification criteria are not met.
Germ cell mutagenicity	based on available data the classification criteria are not met.
Carcinogenicity	based on available data the classification criteria are not met.
Reproductive toxicity	based on available data the classification criteria are not met.
STOT-single exposure	STOT SE category 3. H336 - May cause drowsiness or dizziness.
STOT-repeated exposure	based on available data the classification criteria are not met.
Aspiration hazard	Aspiration Hazard Category 1. H304 - May be fatal if swallowed and enters airways.
Repeated or prolonged exposure	Prolonged contact may cause defatting of the skin.

11.1.2. Mixtures

	No data available.
--	--------------------

11.1.3. Hazard Information

	No data available.
--	--------------------

11.1.4. Toxicological Information

methanol	Oral Rat LD50: 1187 mg/kg	Inhalation Rat LC50/4 h: 128.2
propan-2-ol	Oral Rat LD50: 5000.0 mg/kg	Dermal Rabbit LD50: 5000.0 mg/kg

SECTION 12: Ecological information

12.1. Toxicity

methanol	Daphnia EC50/48h: 10000.0000 mg/l Green algae EC50/96h: 22000	Fish LC50/96h: 15400 mg/l Lepomis_Macrochirus LC50/96h: 15400
propan-2-ol	Daphnia EC50/48h: 100.0000 mg/l Green Algae EC50/48h: >100 mg/l	Fish LC50/96h: 4200.0000 mg/l Golden orfe LC50/48h: >100 mg/l

12.2. Persistence and degradability

	Substance biodegrades at a moderate rate and inherently biodegradable according to the OECD guide lines.
--	--

12.3. Bioaccumulative potential

	No data is available on this product.
--	---------------------------------------

Partition coefficient

	Tyre and Trim No data available	propan-2-ol 0.05 log P
--	---------------------------------	------------------------

12.4. Mobility in soil

	No data is available on this product.
--	---------------------------------------

12.5. Results of PBT and vPvB assessment

	No data is available on this product.
--	---------------------------------------

12.6. Other adverse effects

	No data available.
--	--------------------

SECTION 13: Disposal considerations

13.1. Waste treatment methods

	Dispose of waste and residues in accordance with local authority requirements.
--	--

Tyre and Trim

Revision 3

Revision date 2017-08-21

General information

Dispose of in compliance with all local and national requirements.

Disposal of packaging

Do NOT reuse empty containers. Empty containers can be sent to landfill after cleaning, if in compliance with local and national regulations.

SECTION 14: Transport information

Hazard pictograms



14.1. UN number

UN3295

14.2. UN proper shipping name

HYDROCARBONS, LIQUID, N.O.S.

14.3. Transport hazard class(es)

ADR/RID	3
Subsidiary risk	-
IMDG	3
Subsidiary risk	-
IATA	3
Subsidiary risk	-

14.4. Packing group

Packing group III

14.5. Environmental hazards

Environmental hazards	No
Marine pollutant	No

14.6. Special precautions for user

No additional special precautions.

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable.

ADR/RID

Hazard ID	30
Tunnel Category	(D/E)

IMDG

EmS Code F-E S-D

IATA

Packing Instruction (Cargo)	366
Maximum quantity	220 L
Packing Instruction (Passenger)	355
Maximum quantity	60 L

SECTION 15: Regulatory information

Tyre and Trim

Revision 3

Revision date 2017-08-21

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulations	<p>REGULATION (EC) No 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.</p> <p>COMMISSION REGULATION (EU) No 453/2010 of 20 May 2010 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.</p>
--------------------	--

15.2. Chemical safety assessment

	No information available.
--	---------------------------

SECTION 16: Other information

Other information

Revision	<p>This document differs from the previous version in the following areas:.</p> <ul style="list-style-type: none"> 2 - Precautionary Statement: Prevention. 2 - Precautionary Statement: Response. 2 - Precautionary Statement: Storage. 2 - Precautionary Statement: Disposal. 3 - Active Ingredients. 4 - Ingestion. 4 - Ingestion. 11 - STOT-single exposure. 11 - Aspiration hazard.
Text of Hazard Statements in Section 3	<p>Flam. Liq. 3: H226 - Flammable liquid and vapour. Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways. STOT SE 3: H336 - May cause drowsiness or dizziness. STOT RE 1: H372 - Causes damage to organs through prolonged or repeated exposure . Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects. Flam. Liq. 2: H225 - Highly flammable liquid and vapour. Eye Irrit. 2: H319 - Causes serious eye irritation. Acute Tox. 3: H301 - Toxic if swallowed. Acute Tox. 3: H311 - Toxic in contact with skin. Acute Tox. 3: H331 - Toxic if inhaled. STOT SE 1: H370 - Causes damage to organs .</p>

Further information

	<p>The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.</p>
--	---