# SAFETY DATA SHEET DEFENDER 30

# SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

#### 1.1. Product identifier

Product name	DEFENDER 30
Product No.	DH452

1.2. Relevant identified uses of the substance or mixture and uses advised against

### 1.3. Details of the supplier of the safety data sheet

Supplier
----------

SUPAGARD LIMITED 23, Gavinton Street, Muirend, Glasgow, Scotland, G44 3EF 0141 633 5933 0141 637 7219 james@supagard.co.uk

# 1.4. Emergency telephone number

# SECTION 2: HAZARDS IDENTIFICATION

# 2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical and Chemical Hazards	Flam. Liq. 3 - H226
Human health	EUH066;STOT SE 3 - H336;Asp. Tox. 1 - H304
Environment	Not classified.

# 2.2. Label elements

Contains

### NAPHTHA (PETROLEUM), HYDROTREATED HEAVY

Label In Accordance With (EC) No. 1272/2008



Signal Word	Danger	
Hazard Statements		
	H226	Flammable liquid and vapour.
	H304	May be fatal if swallowed and enters airways.
	H336	May cause drowsiness or dizziness.
Precautionary Statements		
	P102	Keep out of reach of children.
	P103	Read label before use.
	P271	Use only outdoors or in a well-ventilated area.
	P280	Wear protective gloves/protective clothing/eye protection/face protection.
	P405	Store locked up.
	P501	Dispose of contents/container in accordance with local regulations.
Supplementary Precautionary Sta	atements	
	P210	Keep away from heat/sparks/open flames/hot surfaces No smoking.
	P233	Keep container tightly closed.
	P240	Ground/bond container and receiving equipment.
	P241	Use explosion-proof electrical equipment.

	DEFENDER 30
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P261	Avoid breathing vapour/spray.
P370+378	In case of fire: Use foam, carbon dioxide, dry powder or water fog for extinction.
P301+310	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
P303+361+353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P312	Call a POISON CENTER or doctor/physician if you feel unwell.
P331	Do NOT induce vomiting.
P403+233	Store in a well-ventilated place. Keep container tightly closed.
P403+235	Store in a well-ventilated place. Keep cool.
EUH066	Repeated exposure may cause skin dryness or cracking.

# 2.3. Other hazards

Supplemental label information

# SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

## 3.2. Mixtures

NAPHTHA (PETROLEUM), HYDROTREATED HEAVY		60-100%
CAS-No.: 64742-48-9	EC No.: 919-857-5	Registration Number: 01-2119463258-33-XXXX
Classification (EC 1272/2008)		Classification (67/548/EEC)
Flam. Liq. 3 - H226		Xn;R65.
EUH066		R10,R66,R67.
STOT SE 3 - H336		
Asp. Tox. 1 - H304		
Asp. 10x. 1 - 11304		

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

### SECTION 4: FIRST AID MEASURES

### 4.1. Description of first aid measures

General information

NOTE! Effects may be delayed. Keep affected person under observation. NOTE! Keep affected person away from heat, sparks and flames!

Inhalation

Move the exposed person to fresh air at once. Keep the affected person warm and at rest. Get prompt medical attention. Perform artificial respiration if breathing has stopped. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen.

Ingestion

Remove victim immediately from source of exposure. Rinse mouth thoroughly. NOTE! Keep affected person away from heat, sparks and flames! DO NOT induce vomiting. Get medical attention immediately. Skin contact

Remove affected person from source of contamination. Wash the skin immediately with soap and water. Get medical attention if any discomfort continues.

Eye contact

Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

#### 4.2. Most important symptoms and effects, both acute and delayed

#### 4.3. Indication of any immediate medical attention and special treatment needed

# **SECTION 5: FIREFIGHTING MEASURES**

# 5.1. Extinguishing media

#### Extinguishing media

Use: Dry chemicals, sand, dolomite etc. Alcohol resistant foam. Water spray, fog or mist. Carbon dioxide (CO2).

#### 5.2. Special hazards arising from the substance or mixture

Unusual Fire & Explosion Hazards

Vapours are heavier than air and may spread near ground to sources of ignition.

### 5.3. Advice for firefighters

#### Special Fire Fighting Procedures

Ventilate closed spaces before entering them. Move container from fire area if it can be done without risk. Use water to keep fire exposed containers cool and disperse vapours. Do not scatter spilled material with more water than needed to fight the fire. Be aware of danger for fire to re-start. Keep run-off water out of sewers and water sources. Dike for water control.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

## 6.1. Personal precautions, protective equipment and emergency procedures

## 6.2. Environmental precautions

# 6.3. Methods and material for containment and cleaning up

Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Stop leak if possible without risk. Ventilate well. Wear necessary protective equipment. Absorb in vermiculite, dry sand or earth and place into containers.

### 6.4. Reference to other sections

# SECTION 7: HANDLING AND STORAGE

## 7.1. Precautions for safe handling

Keep away from heat, sparks and open flame. Avoid spilling, skin and eye contact. Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level. Risk of vapour concentration on the floor and in low-lying areas. Static electricity and formation of sparks must be prevented.

### 7.2. Conditions for safe storage, including any incompatibilities

Flammable/combustible - Keep away from oxidisers, heat and flames. Keep containers tightly closed. Storage Class Flammable liquid storage.

#### 7.3. Specific end use(s)

# SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

#### 8.1. Control parameters

Name	STD	TWA	- 8 Hrs	STEL	- 15 Min	Notes
NAPHTHA (PETROLEUM), HYDROTREATED HEAVY			1000 mg/m3			

# 8.2. Exposure controls

Protective equipment



Process conditions

Provide eyewash station.

Engineering measures

No specific ventilation requirements noted, but forced ventilation may still be required if air contamination exceeds acceptable level.

Respiratory equipment

No specific recommendation made, but respiratory protection must be used if the general level exceeds the recommended occupational exposure limit.

Hand protection

Use protective gloves.

Eye protection

Use eye protection.

Other Protection

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.

Hygiene measures

Wash hands at the end of each work shift and before eating, smoking and using the toilet. Wash promptly if skin becomes contaminated. Promptly remove any clothing that becomes wet or contaminated. When using do not eat, drink or smoke. DO NOT SMOKE IN WORK AREA!

# SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

# 9.1. Information on basic physical and chemical properties

Appearance	Liquid
Colour	Typical
Odour	Characteristic.
Relative density	<1.0

## 9.2. Other information

# SECTION 10: STABILITY AND REACTIVITY

## 10.1. Reactivity

#### 10.2. Chemical stability

Stable under normal temperature conditions.

### 10.3. Possibility of hazardous reactions

#### 10.4. Conditions to avoid

Avoid heat, flames and other sources of ignition. Avoid contact with strong oxidisers.

#### 10.5. Incompatible materials

### 10.6. Hazardous decomposition products

Fire creates: Toxic gases/vapours/fumes of: Carbon monoxide (CO). Carbon dioxide (CO2).

# SECTION 11: TOXICOLOGICAL INFORMATION

# 11.1. Information on toxicological effects

Inhalation

Vapours may cause headache, fatigue, dizziness and nausea. Vapour may affect central nervous system and cause headache, discomfort, vomiting or intoxication. High concentrations of vapours may irritate respiratory system and lead to headache, fatigue, nausea and vomiting.

Ingestion

May cause stomach pain or vomiting. Gastrointestinal symptoms, including upset stomach.

Skin contact

Prolonged or repeated exposure may cause severe irritation. Acts as a defatting agent on skin. May cause cracking of skin, and eczema.

#### Eye contact

Irritating to eyes. Irritation, burning, lachrymation, blurred vision after liquid splash.

#### Health Warnings

Repeated exposure may cause chronic eye irritation. Swallowing concentrated chemical may cause severe internal injury.

Route of entry Inhalation. Ingestion. Skin and/or eye contact. Medical Symptoms Irritation of eyes and mucous membranes. Dilated pupils. Rhinitis (inflammation of the nasal mucous membranes).

# SECTION 12: ECOLOGICAL INFORMATION

#### Ecotoxicity

Dangerous for the environment if discharged into watercourses.

#### 12.1. Toxicity

# 12.2. Persistence and degradability

#### 12.3. Bioaccumulative potential

### 12.4. Mobility in soil

# 12.5. Results of PBT and vPvB assessment

# 12.6. Other adverse effects

# SECTION 13: DISPOSAL CONSIDERATIONS

# 13.1. Waste treatment methods

Collect on absorbent material, place in cardboard kegs and incinerate. Incinerate in suitable combustion chamber. Do not allow runoff to sewer, waterway or ground. Dispose of waste and residues in accordance with local authority requirements.

# SECTION 14: TRANSPORT INFORMATION

# 14.1. UN number

UN No. (ADR/RID/ADN)	1993
UN No. (IMDG)	1993
UN No. (ICAO)	1993

### 14.2. UN proper shipping name

FLAMMABLE LIQUID, N.O.S. (contains Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics) Proper Shipping Name FLAMMABLE LIQUID, N.O.S.

#### 14.3. Transport hazard class(es)

ADR/RID/ADN Class	3
ADR/RID/ADN Class	Class 3: Flammable liquids.
ADR Label No.	3
IMDG Class	3
ICAO Class/Division	3
Transport Labels	



Ш

#### 14.4. Packing group

ADR/RID/ADN Packing group

IMDG Packing group	Ш
ICAO Packing group	Ш

# 14.5. Environmental hazards

Environmentally Hazardous Substance/Marine Pollutant No.

# 14.6. Special precautions for user

EMS	F-E, S-E
Emergency Action Code	•3Y
Hazard No. (ADR)	30
Hazard No. (ADR)	30 Flammable liquid (flash-point between 23°C and 60°C, inclusive) or flammable liquid or solid in the molten state with a flash-point above 60°C, heated to a temperature equal to or above its flash-point, or self heating liquid.
Tunnel Restriction Code	(D/E)

## 14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

# SECTION 15: REGULATORY INFORMATION

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Guidance Notes Workplace Exposure Limits EH40. Introduction to Local Exhaust Ventilation HS(G)37. EU Legislation Regulation (EC) No.1272/2008 The Classification, Labelling and Packaging of substances and mixtures Regulations Regulation (EC) No. 1907/2006 The Registration, Evaluation, Authorisation and Restriction of Chemicals Regulations (REACH) 2001/95/EC The General Product Safety Directive (GPSD) Commission Regulation (EU) 2015/830 Requirements for the compilation of safety data sheets (amending REACH) Authorisations (Title VII Regulation 1907/2006) No specific authorisations are noted for this product. Restrictions (Title VIII Regulation 1907/2006) No specific restrictions of use are noted for this product.

# 15.2. Chemical Safety Assessment

# **SECTION 16: OTHER INFORMATION**

Revision Date	08/01/2018
Revision	2
Supersedes date	06/01/2005

Hazard Statements In Full

EUH066 Repeated exposure may cause skin dryness or cracking. , H226 Flammable liquid and vapour. , H304 May be fatal if swallowed and enters airways. , H336 May cause drowsiness or dizziness.