

## SAFETY DATA SHEET WAX CONSERVER 200LTR

### SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

#### 1.1. Product identifier

Product name WAX CONSERVER 200LTR  
Product No. 000998082967

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses As product description

#### 1.3. Details of the supplier of the safety data sheet

Supplier SUPAGARD LIMITED  
23, Gavinton Street,  
Muirend,  
Glasgow,  
Scotland,  
G44 3EF  
0141 633 5933  
0141 637 7219  
james@supagard.co.uk

#### 1.4. Emergency telephone number

### SECTION 2: HAZARDS IDENTIFICATION

#### 2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical and Chemical Hazards	Flam. Liq. 3 - H226
Human health	Skin Irrit. 2 - H315; Eye Irrit. 2 - H319
Environment	Not classified.

#### 2.2. Label elements

Label In Accordance With (EC) No. 1272/2008



Signal Word Warning

Hazard Statements

H226	Flammable liquid and vapour.
H315	Causes skin irritation.
H319	Causes serious eye irritation.

Precautionary Statements

P102	Keep out of reach of children.
P210	Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P305+351+338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+313	If eye irritation persists: Get medical advice/attention.
P501	Dispose of contents/container in accordance with local regulations.

Supplementary Precautionary Statements

P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical equipment.
P242	Use only non-sparking tools.

## WAX CONSERVER 200LTR

P243	Take precautionary measures against static discharge.
P264	Wash contaminated skin thoroughly after handling.
P321	Specific treatment (see medical advice on this label).
P370+378	In case of fire: Use foam, carbon dioxide, dry powder or water fog for extinction.
P302+352	IF ON SKIN: Wash with plenty of soap and water.
P332+313	If skin irritation occurs: Get medical advice/attention.
P362	Take off contaminated clothing and wash before reuse.
P403+235	Store in a well-ventilated place. Keep cool.

### 2.3. Other hazards

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

### 3.2. Mixtures

2-BUTOXYETHANOL	10-30%
CAS-No.: 111-76-2	EC No.: 203-905-0
Registration Number: 01-2119475108-36-XXXX	
Classification (EC 1272/2008) Acute Tox. 4 - H302 Acute Tox. 4 - H312 Acute Tox. 4 - H332 Skin Irrit. 2 - H315 Eye Irrit. 2 - H319	Classification (67/548/EEC) Xn;R20/21/22 Xi;R36/38
ACETIC ACID ...%	1-5%
CAS-No.: 64-19-7	EC No.: 200-580-7
Registration Number: 01-2119475328-30-XXXX	
Classification (EC 1272/2008) Skin Corr. 1A - H314	Classification (67/548/EEC) R10 C;R35
PROPAN-2-OL	10-30%
CAS-No.: 67-63-0	EC No.: 200-661-7
Registration Number: 01-2119457558-25-XXXX	
Classification (EC 1272/2008) Flam. Liq. 2 - H225 Eye Irrit. 2 - H319 STOT SE 3 - H336	Classification (67/548/EEC) F;R11 Xi;R36 R67
QUATERNARY COCO ALKYL METHYL AMINE ETHOXYLATE METHYL CHLORIDE	1-5%
CAS-No.: 863679-20-3	EC No.:
Classification (EC 1272/2008) Acute Tox. 4 - H302 Skin Irrit. 2 - H315 Eye Dam. 1 - H318 Aquatic Acute 1 - H400	Classification (67/548/EEC) Xn;R22. Xi;R38,R41. N;R50.

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

## SECTION 4: FIRST AID MEASURES

### 4.1. Description of first aid measures

# WAX CONSERVER 200LTR

## General information

NOTE! Effects may be delayed. Keep affected person under observation. NOTE! Keep affected person away from heat, sparks and flames!

### Inhalation

Move the exposed person to fresh air at once. Keep the affected person warm and at rest. Get prompt medical attention. Perform artificial respiration if breathing has stopped. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen.

### Ingestion

Remove victim immediately from source of exposure. Rinse mouth thoroughly. NOTE! Keep affected person away from heat, sparks and flames! DO NOT induce vomiting. Get medical attention immediately.

### Skin contact

Remove affected person from source of contamination. Wash the skin immediately with soap and water. Get medical attention if any discomfort continues.

### Eye contact

Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

## **4.2. Most important symptoms and effects, both acute and delayed**

## **4.3. Indication of any immediate medical attention and special treatment needed**

## **SECTION 5: FIREFIGHTING MEASURES**

### **5.1. Extinguishing media**

#### Extinguishing media

Use: Dry chemicals, sand, dolomite etc. Alcohol resistant foam. Water spray, fog or mist. Carbon dioxide (CO<sub>2</sub>).

### **5.2. Special hazards arising from the substance or mixture**

#### Unusual Fire & Explosion Hazards

Vapours are heavier than air and may spread near ground to sources of ignition.

### **5.3. Advice for firefighters**

#### Special Fire Fighting Procedures

Ventilate closed spaces before entering them. Move container from fire area if it can be done without risk. Use water to keep fire exposed containers cool and disperse vapours. Do not scatter spilled material with more water than needed to fight the fire. Be aware of danger for fire to re-start. Keep run-off water out of sewers and water sources. Dike for water control.

## **SECTION 6: ACCIDENTAL RELEASE MEASURES**

### **6.1. Personal precautions, protective equipment and emergency procedures**

### **6.2. Environmental precautions**

### **6.3. Methods and material for containment and cleaning up**

Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Stop leak if possible without risk. Ventilate well. Wear necessary protective equipment. Absorb in vermiculite, dry sand or earth and place into containers. Small quantities may be flushed to drains with plenty of water.

### **6.4. Reference to other sections**

## **SECTION 7: HANDLING AND STORAGE**

### **7.1. Precautions for safe handling**

Keep away from heat, sparks and open flame. Avoid spilling, skin and eye contact. Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level. Risk of vapour concentration on the floor and in low-lying areas. Static electricity and formation of sparks must be prevented.

### **7.2. Conditions for safe storage, including any incompatibilities**

Flammable/combustible - Keep away from oxidisers, heat and flames. Keep containers tightly closed.

#### Storage Class

Flammable liquid storage.

### **7.3. Specific end use(s)**

# WAX CONSERVER 200LTR

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1. Control parameters

Name	STD	TWA - 8 Hrs		STEL - 15 Min		Notes
2-BUTOXYETHANOL	WEL	25 ppm(Sk)		50 ppm(Sk)		
PROPAN-2-OL	WEL	400 ppm	999 mg/m3	500 ppm	1250 mg/m3	

WEL = Workplace Exposure Limit.

### 8.2. Exposure controls

Protective equipment



Process conditions

Provide eyewash station.

Engineering measures

No specific ventilation requirements noted, but forced ventilation may still be required if air contamination exceeds acceptable level.

Respiratory equipment

No specific recommendation made, but respiratory protection must be used if the general level exceeds the recommended occupational exposure limit. Use chemical cartridge protection with appropriate cartridge.

Hand protection

Use protective gloves.

Eye protection

Use approved safety goggles or face shield.

Other Protection

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.

Hygiene measures

Wash hands at the end of each work shift and before eating, smoking and using the toilet. Wash promptly if skin becomes contaminated. Promptly remove any clothing that becomes wet or contaminated. When using do not eat, drink or smoke. DO NOT SMOKE IN WORK AREA!

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1. Information on basic physical and chemical properties

Appearance

Liquid

Colour

Typical

Odour

Characteristic.

### 9.2. Other information

## SECTION 10: STABILITY AND REACTIVITY

### 10.1. Reactivity

### 10.2. Chemical stability

Stable under normal temperature conditions.

### 10.3. Possibility of hazardous reactions

### 10.4. Conditions to avoid

Avoid heat, flames and other sources of ignition. Avoid contact with strong oxidisers.

### 10.5. Incompatible materials

# WAX CONSERVER 200LTR

## **10.6. Hazardous decomposition products**

Fire creates: Toxic gases/vapours/fumes of: Carbon monoxide (CO). Carbon dioxide (CO<sub>2</sub>).

## **SECTION 11: TOXICOLOGICAL INFORMATION**

### **11.1. Information on toxicological effects**

#### Inhalation

Vapours may cause headache, fatigue, dizziness and nausea. Vapour may affect central nervous system and cause headache, discomfort, vomiting or intoxication. High concentrations of vapours may irritate respiratory system and lead to headache, fatigue, nausea and vomiting.

#### Ingestion

May cause stomach pain or vomiting. Gastrointestinal symptoms, including upset stomach.

#### Skin contact

Prolonged or repeated exposure may cause severe irritation. Acts as a defatting agent on skin. May cause cracking of skin, and eczema. Irritating to skin. May cause allergic contact eczema.

#### Eye contact

Irritating to eyes. Irritation, burning, lachrymation, blurred vision after liquid splash.

#### Health Warnings

Repeated exposure may cause chronic eye irritation. Swallowing concentrated chemical may cause severe internal injury.

#### Route of entry

Inhalation. Ingestion. Skin and/or eye contact.

#### Medical Symptoms

Irritation of eyes and mucous membranes. Dilated pupils. Rhinitis (inflammation of the nasal mucous membranes).

## **SECTION 12: ECOLOGICAL INFORMATION**

#### Ecotoxicity

Dangerous for the environment if discharged into watercourses.

### **12.1. Toxicity**

### **12.2. Persistence and degradability**

### **12.3. Bioaccumulative potential**

### **12.4. Mobility in soil**

### **12.5. Results of PBT and vPvB assessment**

### **12.6. Other adverse effects**

## **SECTION 13: DISPOSAL CONSIDERATIONS**

### **13.1. Waste treatment methods**

Collect on absorbent material, place in cardboard kegs and incinerate. Incinerate in suitable combustion chamber. Do not allow runoff to sewer, waterway or ground. Dispose of waste and residues in accordance with local authority requirements.

## **SECTION 14: TRANSPORT INFORMATION**

### **14.1. UN number**

UN No. (ADR/RID/ADN)	1993
UN No. (IMDG)	1993
UN No. (ICAO)	1993

# WAX CONSERVER 200LTR

## 14.2. UN proper shipping name

Proper Shipping Name                      FLAMMABLE LIQUID, N.O.S. (ORANGE TERPENES)

## 14.3. Transport hazard class(es)

ADR/RID/ADN Class                      3  
ADR/RID/ADN Class                      Class 3: Flammable liquids.  
ADR Label No.                              3  
IMDG Class                                  3  
ICAO Class/Division                      3  
Transport Labels



## 14.4. Packing group

ADR/RID/ADN Packing group              III  
IMDG Packing group                        III  
ICAO Packing group                        III

## 14.5. Environmental hazards

Environmentally Hazardous Substance/Marine Pollutant  
No.

## 14.6. Special precautions for user

EMS    3-07  
Emergency Action Code                    3Y  
Hazard No. (ADR)                            30  
Hazard No. (ADR)                            30 Flammable liquid (flash-point between 23°C and 60°C, inclusive) or flammable liquid or solid in the molten state with a flash-point above 60°C, heated to a temperature equal to or above its flash-point, or self heating liquid.

## 14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

## SECTION 15: REGULATORY INFORMATION

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Guidance Notes

Workplace Exposure Limits EH40.

Introduction to Local Exhaust Ventilation HS(G)37.

EU Legislation

Regulation (EC) No.1272/2008 The Classification, Labelling and Packaging of substances and mixtures Regulations

Regulation (EC) No. 1907/2006 The Registration, Evaluation, Authorisation and Restriction of Chemicals Regulations (REACH)

2001/95/EC The General Product Safety Directive (GPSD)

Commission Regulation (EU) 2015/830 Requirements for the compilation of safety data sheets (amending REACH)

Authorisations (Title VII Regulation 1907/2006)

No specific authorisations are noted for this product.

Restrictions (Title VIII Regulation 1907/2006)

No specific restrictions of use are noted for this product.

### 15.2. Chemical Safety Assessment

## WAX CONSERVER 200LTR

### SECTION 16: OTHER INFORMATION

Revision Date 02/01/2018

Revision 4

Supersedes date 02/01/2018

#### Hazard Statements In Full

H225 Highly flammable liquid and vapour. , H226 Flammable liquid and vapour. , H302 Harmful if swallowed. , H312 Harmful in contact with skin. , H314 Causes severe skin burns and eye damage. , H315 Causes skin irritation. , H318 Causes serious eye damage. , H319 Causes serious eye irritation. , H332 Harmful if inhaled. , H336 May cause drowsiness or dizziness. , H400 Very toxic to aquatic life.