Revision Date 02/01/2018

Revision 4

Supersedes date 29/05/2014

# SAFETY DATA SHEET **UPHOLSTERY CLEANER**



## SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name

UPHOLSTERY CLEANER

Product No.

000998008507

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Fabric and fibre cleaner

1.3. Details of the supplier of the safety data sheet

Supplier

SUPAGARD LIMITED 23, Gavinton Street,

Muirend, Glasgow, Scotland, G44 3EF 0141 633 5933 0141 637 7219

james@supagard.co.uk

1.4. Emergency telephone number

#### **SECTION 2: HAZARDS IDENTIFICATION**

## 2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical and Chemical Hazards Flam. Aerosol 1 - H222

Human health

Not classified.

Environment

Not classified.

## 2.2. Label elements

Detergent Labelling:

< 5%

non-ionic surfactants

anionic surfactants

perfumes

Contains

NATRIUMNITRIET, SODIUM BENZOATE, BENZYL SALICYLATE, HEXYL

CINNAMAL

Label In Accordance With (EC) No. 1272/2008



Signal Word

Danger

Hazard Statements

H222

Extremely flammable aerosol.

Precautionary Statements

P102 P261

Keep out of reach of children. Avoid breathing vapour/spray.

P271

Use only outdoors or in a well-ventilated area.

P501

Dispose of contents/container in accordance with local regulations.

Supplementary Precautionary Statements

P210

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 P410+412 Pressurized container: Do not pierce or burn, even after use.

Protect from sunlight. Do not expose to temperatures exceeding 50

°C/122°F.

Supplemental label information

H229

Pressurised container: May burst if heated

## 2.3. Other hazards

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

## 3.2. Mixtures

1-METHOXY-2-PROPANOL			5-10%
CAS-No.: 107-98-2	EC No.: 203-539-1		Registration Number: 01-2119457435-35-XXX
Classification (EC 1272/2008) Flam. Liq. 3 - H226 STOT SE 3 - H336		Classification (67/5 R10 R67	548/EEC)
2-BUTOXYETHANOL	V		1-5%
CAS-No.: 111-76-2	EC No.: 203-905-0		Registration Number: 01-2119475108-36-XXXX
Classification (EC 1272/2008) Acute Tox. 4 - H302 Acute Tox. 4 - H312		Classification (67/5 Xn;R20/21/22 Xi;R36/38	548/EEC)
Acute Tox. 4 - H332 Skin Irrit. 2 - H315 Eye Irrit. 2 - H319	,	- 2 0	
BUTANE			5-109
CAS-No.: 106-97-8	EC No.: 203-448-7		Registration Number: Exempt - Naturally occuring
Classification (EC 1272/2008) Flam. Gas 1 - H220		Classification (67/5 F+;R12	548/EEC)
ISOBUTANE	//	er -	1-5%

ISOBUTANE		eo	1-5%
CAS-No.: 75-28-5	EC No.: 200-857-2		Registration Number: Exempt - Naturally occuring
Classification (EC 1272/2008) Flam. Gas 1 - H220		Classification F+;R12	(67/548/EEC)

SODIUM NITRITE		< 1%
CAS-No.: 7632-00-0	EC No.: 231-555-9	Registration Number: 01-2119471836-27-XXXX
Classification (EC 1272/2008)		Classification (67/548/EEC)
Ox. Sol. 3 - H272		O;R8
Acute Tox. 3 - H301		T;R25
Aquatic Acute 1 - H400		N;R50

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

## **SECTION 4: FIRST AID MEASURES**

#### 4.1. Description of first aid measures

General information

Move the exposed person to fresh air at once. Get medical attention if any discomfort continues.

Inhalation

Move the exposed person to fresh air at once. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Keep the affected person warm and at rest. Get prompt medical attention.

DO NOT INDUCE VOMITING! Rinse mouth thoroughly with water and give large amounts of milk or water to people not unconscious. Get medical attention if any discomfort continues.

Skin contact

Wash the skin immediately with soap and water. Get medical attention if any discomfort continues.

Eye contact

Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

#### 4.2. Most important symptoms and effects, both acute and delayed

General information

NOTE! Effects may be delayed. Keep affected person under observation.

#### 4.3. Indication of any immediate medical attention and special treatment needed

No specific first aid measures noted.

#### **SECTION 5: FIREFIGHTING MEASURES**

#### 5.1. Extinguishing media

Extinguishing media

Use: Powder. Dry chemicals, sand, dolomite etc. Water spray, fog or mist.

#### 5.2. Special hazards arising from the substance or mixture

Unusual Fire & Explosion Hazards

Aerosol cans may explode in a fire.

#### 5.3. Advice for firefighters

Special Fire Fighting Procedures

Containers close to fire should be removed or cooled with water. Use water to keep fire exposed containers cool and disperse vapours.

#### **SECTION 6: ACCIDENTAL RELEASE MEASURES**

### 6.1. Personal precautions, protective equipment and emergency procedures

#### 6.2. Environmental precautions

#### 6.3. Methods and material for containment and cleaning up

Wear necessary protective equipment. Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Let evaporate. Keep out of confined spaces because of explosion risk. If leakage cannot be stopped, evacuate area.

#### 6.4. Reference to other sections

#### **SECTION 7: HANDLING AND STORAGE**

#### 7.1. Precautions for safe handling

Keep away from heat, sparks and open flame. Avoid spilling, skin and eye contact. Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level.

### 7.2. Conditions for safe storage, including any incompatibilities

Aerosol cans: Must not be exposed to direct sunlight or temperatures above 50°C.

### 7.3. Specific end use(s)

### SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Supagard

19-27 GAVINTON STREET

GLASGOW

0141 633 5933

## 8.1. Control parameters

Name	STD	TWA - 8 Hrs		STEL - 15 Mir		19-7	Notes GOV
1-METHOXY-2-PROPANOL	WEL	100 ppm(Sk)	375 mg/m3(Sk)	150 ppm(Sk)	560 mg/m3(	(Sk)	0141 633 5933
2-BUTOXYETHANOL	WEL	25 ppm(Sk)		50 ppm(Sk)			
BUTANE	WEL	600 ppm	1450 mg/m3	750 ppm	1810 n	ng/m3	

WEL = Workplace Exposure Limit.

#### 8.2. Exposure controls

Protective equipment





Engineering measures

Provide adequate general and local exhaust ventilation.

Respiratory equipment

No specific recommendation made, but respiratory protection must be used if the general level exceeds the recommended occupational exposure limit. Use chemical cartridge protection with appropriate cartridge.

Hand protection

Use protective gloves.

Eye protection

Wear approved chemical safety goggles where eye exposure is reasonably probable.

Other Protection

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.

Hygiene measures

DO NOT SMOKE IN WORK AREA! Wash hands at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. When using do not eat, drink or smoke.

#### SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

## 9.1. Information on basic physical and chemical properties

Appearance

Aerosol.

Colour

Typical

Odour

Characteristic.

Flammability Limit - Lower(%)

0.8

Flammability Limit - Upper(%)

9.0

## 9.2. Other information

#### SECTION 10: STABILITY AND REACTIVITY

#### 10.1. Reactivity

No specific reactivity hazards associated with this product.

## 10.2. Chemical stability

Stable under normal temperature conditions.


## 10.3. Possibility of hazardous reactions

Not known.

#### 10.4. Conditions to avoid

Avoid heat, flames and other sources of ignition. Avoid contact with: Strong oxidising agents. Strong alkalis. Strong mineral acids.

#### 10.5. Incompatible materials



Fire creates: Vapours/gases/fumes of: Carbon monoxide (CO). Carbon dioxide (CO2).

## **SECTION 11: TOXICOLOGICAL INFORMATION**

# Supagard 19-27 GAVINTON STREET GLASSOW

## 11.1. Information on toxicological effects

#### Inhalation

May cause irritation to the respiratory system. Vapours may cause headache, fatigue, dizziness and nausea. Prolonged inhalation of high concentrations may damage respiratory system.

#### Ingestion

May cause discomfort if swallowed. May cause stomach pain or vomiting. Gastrointestinal symptoms, including upset stomach.

#### Skin contact

Prolonged or repeated exposure may cause severe irritation. Acts as a defatting agent on skin. May cause cracking of skin, and eczema.

#### Eye contact

Irritating to eyes. May cause chemical eye burns.

Route of entry

Inhalation. Skin and/or eye contact.

#### **SECTION 12: ECOLOGICAL INFORMATION**

#### **Ecotoxicity**

Dangerous for the environment if discharged into watercourses.

#### 12.1. Toxicity

Data set not currently available.

## 12.2. Persistence and degradability

#### 12.3. Bioaccumulative potential

Bioaccumulative potential

No data available on bioaccumulation.

## 12.4. Mobility in soil

## 12.5. Results of PBT and vPvB assessment

#### 12.6. Other adverse effects

Not known.

## **SECTION 13: DISPOSAL CONSIDERATIONS**

## 13.1. Waste treatment methods

Empty containers must not be burned because of explosion hazard. Dispose of waste and residues in accordance with local authority requirements.

# SECTION 14: TRANSPORT INFORMATION

#### 14.1. UN number

UN No. (ADR/RID/ADN)

1950

UN No. (IMDG)

1950

UN No. (ICAO)


1950

## 14.2. UN proper shipping name

Proper Shipping Name

**AEROSOLS** 

#### OPTIOLSTERT CLLA



ADR/RID/ADN Class

2

ADR/RID/ADN Class

Class 2: Gases

ADR Label No.

2.1

IMDG Class

2.1

ICAO Class/Division

2.1

Transport Labels



#### 14.4. Packing group

ADR/RID/ADN Packing group

Not Applicable

IMDG Packing group

Not Applicable

ICAO Packing group

Not Applicable

#### 14.5. Environmental hazards

Environmentally Hazardous Substance/Marine Pollutant

No.

## 14.6. Special precautions for user

EMS

F-D, S-U

## 14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

## **SECTION 15: REGULATORY INFORMATION**

# 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Statutory Instruments

The Aerosol Dispensers (Amendment) Regulations 2014 No.1130

**Guidance Notes** 

Workplace Exposure Limits EH40.

Introduction to Local Exhaust Ventilation HS(G)37.

**EU** Legislation

The Aerosol Dispensers Directive 1975/324 EEC

Regulation (EC) No.1272/2008 The Classification, Labelling and Packaging of substances and mixtures Regulations

Regulation (EC) No. 1907/2006 The Registration, Evaluation, Authorisation and Restriction of Chemicals Regulations (REACH)

2001/95/EC The General Product Safety Directive (GPSD)

Commission Regulation (EU) 2015/830 Requirements for the compilation of safety data sheets (amending REACH)

Authorisations (Title VII Regulation 1907/2006)

No specific authorisations are noted for this product.

Restrictions (Title VIII Regulation 1907/2006)

No specific restrictions of use are noted for this product.

## 15.2. Chemical Safety Assessment

# **SECTION 16: OTHER INFORMATION**

Revision Date

02/01/2018

Revision

4

Supersedes date

29/05/2014



Hazard Statements In Full

H220 Extremely flammable gas., H222 Extremely flammable aerosol., H226 Flammable liquid and vapour., H272 May intensify fire; oxidiser., H301 Toxic if swallowed., H302 Harmful if swallowed., H312 Harmful in contact with skin., H315 Causes skin irritation., H319 Causes serious eye irritation., H332 Harmful if inhaled., H336 May cause drowsiness or dizziness., H400 Very toxic to aquatic life.

