

according to Regulation (EU) 2020/878

Page 1/10

## Harry Fairbairn Tyre & Trim Shine

 Revision
 10

 Revision date
 2022-11-21

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier	
Product name	Harry Fairbairn Tyre & Trim Shine
1.2. Relevant identified uses of t	he substance or mixture and uses advised against
Product Use	[SU22] Professional uses: Public domain (administration, education, entertainment, services, craftsmen); [PC35] Washing and cleaning products (including solvent based products);
	[SU21] Consumer uses: Private households (= general public = consumers); [PC35] Washing and cleaning products (including solvent based products);
Description	This new water resistant coating has been carefully formulated for the renovation of all plastics, PVC, rubber etc, throughout your vehicle.
1.3. Details of the supplier of the	safety data sheet
Company	SUPAGARD LIMITED
Address	19-27 Gavinton Street
	Muirend
	Glasgow G44 3EF
Web	www.supagard.com
Telephone	0141 633 5933
Fax	01416377219
Email	James.Smyth@supagard.com
Email address of the	James.Smyth@supagard.com
competent person	
1.4. Emergency telephone numb	
Emergency telephone number	01416335933
	8.30am to 5.00pm
	For medical advice or information you should contact your GP or NHS 111 (or NHS 24 in Scotland) on 111 (for 24 hour health advice) If you are a healthcare professional with an enquiry please visit www.TOXBASE.org
SECTION 2: Hazards identifi	cation
2.1. Classification of the substan	
2.1.2. Classification - EC 1272/2008	Flam. Liq. 3: H226; Asp. Tox. 1: H304; STOT SE 3: H336;



2.2. Label elements	
Hazard pictograms	
Signal Word	Danger
Hazard Statement	Flam. Liq. 3: H226 - Flammable liquid and vapour.
	Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways.
	STOT SE 3: H336 - May cause drowsiness or dizziness.
Precautionary Statement:	P102 - Keep out of reach of children.
Prevention	P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Precautionary Statement:	P301+P310+P330+P331 - IF SWALLOWED: Immediately call a POISON CENTER/doctor. Rinse
Response	mouth. Do NOT induce vomiting.
	P302+P350 - IF ON SKIN: Gently wash with plenty of soap and water.
	P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.
Precautionary Statement: Storage	P403+P233 - Store in a well-ventilated place. Keep container tightly closed.
SUPPLEMENTAL HAZARD	Ingredients as required by Regulation (EC) No 648/2004:.
INFORMATION	Less than 5% Aromatic Hydrocarbons, Dimethicone, Amino functional silicone.
	Contains - Hydrocarbons, C9-11, N-alkanes, Isoalkanes, Cyclics, <2% Aromatic.
2.3. Other hazards	
Other hazards	This substance/mixture is not classified as PBT or vPvB according to current criteria. The substance/mixture does not contain substances with endocrine disrupting properties.
Further information	

RECOMMENDED SHELF LIFE 1 YEAR FROM DATE OF DELIVERY.

## SECTION 3: Composition/information on ingredients

#### 3.2. Mixtures

#### EC 1272/2008

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification
Hydrocarbons, C9-11, N-alkanes, Isoalkanes, Cyclics, <2% Aromatic		1174522-20-	3 919-857-5	01-2119463258-33	50 - 60%	Flam. Liq. 3: H226; Asp. Tox. 1: H304; STOT SE 3: H336;

## **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

Inhalation	Move the exposed person to fresh air.
Eye contact	Rinse immediately with plenty of water. Contact lenses should be removed.
Skin contact	Remove contaminated clothing. Wash with water and soap as a precaution.
Ingestion	DO NOT INDUCE VOMITING. If swallowed, do not induce vomiting: seek medical advice
	immediately and show this container or label. Rinse mouth thoroughly.

#### 4.2. Most important symptoms and effects, both acute and delayed

Inhalation	High concentration of vapour in enclosed space may cause irritation, headaches and nausea. May cause irritation to respiratory system.
Eye contact	Irritating to eyes.
Skin contact	May cause skin dryness and irritation. Prolonged contact may cause defatting of the skin.
Ingestion	Harmful if ingested or swallowed.
4.3 Indication of any immediate	modical attention and appeals tractment peoded

#### 4.3. Indication of any immediate medical attention and special treatment needed



Revision date 2022-11-21

4.3. Indication of any immediate	medical attention and special treatment needed
	TREAT SYMPTOMATICALLY.
Inhalation	Move the exposed person to fresh air. Seek medical attention if irritation or symptoms persist.
Eye contact	Contact lenses should be removed. Rinse immediately with plenty of water. Seek medical attention if irritation or symptoms persist.
Skin contact	Seek medical attention if irritation or symptoms persist.
Ingestion	Drink 1 to 2 glasses of water. Seek medical attention if irritation or symptoms persist.
General information	
	If you feel unwell, seek medical advice (show the label where possible). Treat symptomatically.
SECTION 5: Firefighting mea	asures
5.1. Extinguishing media	
	Flammable liquid. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
5.2. Special hazards arising from	n the substance or mixture
	Burning produces irritating, toxic and obnoxious fumes.
5.3. Advice for firefighters	
	Fire fighters should wear self contained positive pressure breathing apparatus (SCBA) and full turnout gear.
Further information	
	In the event of a fire and/or explosion do not breath fumes. Standard procedure for chemical fires. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
SECTION 6: Accidental relea	ase measures
6.1. Personal precautions, prote	ctive equipment and emergency procedures
	Wear suitable protective equipment. Flammable liquid. Avoid sparks, flames, heat and sources of ignition.
6.2. Environmental precautions	
	Advise local authorities if large spills cannot be contained.
6.3. Methods and material for co	ntainment and cleaning up
	Absorb with inert, absorbent material. Sweep up. Transfer to suitable, labelled containers for disposal. Avoid sparks, flames, heat and sources of ignition.
6.4. Reference to other sections	
	See section 2, 7, 8, 13 for further information.
SECTION 7: Handling and st	lorage
7.1. Precautions for safe handlin	g
	Adopt best Manual Handling considerations when handling, carrying and dispensing.
7.2. Conditions for safe storage,	including any incompatibilities
	Flammable liquid. Avoid sparks, flames, heat and sources of ignition. Avoid storing in direct Sun Light. Store in a well-ventilated place. Keep cool. Store in original container. Keep container tightly closed. Keep away from combustible material. Keep out of the reach of children.
7.3. Specific end use(s)	
	This new water resistant coating has been carefully formulated for the renovation of all plastics, PVC, rubber etc. throughout your vehicle.
Suitable packaging	



Suitable packaging

## Plastic containers.

## SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

#### Occupational exposure controls.

Ethylbenzene (ethyl benzol) (Ethylbenzene)	WEL 8-hr limit ppm: 100	WEL 8-hr limit mg/m3: 441
	WEL 15 min limit ppm: 125	WEL 15 min limit mg/m3: 552
	WEL 8-hr limit mg/m3 total -	WEL 15 min limit mg/m3 total -
	inhalable dust:	inhalable dust:
	WEL 8-hr limit mg/m3 total -	WEL 15 min limit mg/m3 total -
	respirable dust:	respirable dust:
methanol	WEL 8-hr limit ppm: 200	WEL 8-hr limit mg/m3: 266
	WEL 15 min limit ppm: 250	WEL 15 min limit mg/m3: 333
	WEL 8-hr limit mg/m3 total -	WEL 15 min limit mg/m3 total -
	inhalable dust:	inhalable dust:
	WEL 8-hr limit mg/m3 total -	WEL 15 min limit mg/m3 total -
	respirable dust:	respirable dust:
propan-2-ol	WEL 8-hr limit ppm: 400	WEL 8-hr limit mg/m3: 999
	WEL 15 min limit ppm: 500	WEL 15 min limit mg/m3: 1250
	WEL 8-hr limit mg/m3 total -	WEL 15 min limit mg/m3 total -
	inhalable dust:	inhalable dust:
	WEL 8-hr limit mg/m3 total -	WEL 15 min limit mg/m3 total -
	respirable dust:	respirable dust:

#### DNEL: Derived no-effect level.

Ethylbenzene (ethyl benzol)	Acute inhalation - Local effects	293 mg/m³		
	Long-term - inhalation - Systemic effects	77 mg/m³	Long-term - dermal - Systemic effects	180 mg/kg
methanol	Acute inhalation - Systemic effects	130 mg/m <sup>3</sup>		
	Acute inhalation - Local effects	130 mg/m³	Acute dermal - Systemic effects	20 mg/kg
	Long-term - inhalation - Systemic effects	130 mg/m³	Long-term - inhalation - Local effects	130 mg/m³
	Long-term - dermal - Systemic effects	20 mg/kg		
propan-2-ol	Long-term - inhalation - Systemic effects	500 mg/m <sup>3</sup>		
	Long-term - dermal - Systemic effects	888 mg/kg		

**Exposure Pattern - General population** 

#### Copyright © 2022 ChemSoft. All rights reserved.



 Revision
 10

 Revision date
 2022-11-21

#### Exposure Pattern - General population

Ethylbenzene (ethyl benzol)	Long-term - inhalation - Systemic	15 mg/m <sup>3</sup>		
	effects	15 mg/m		
	Long-term - oral - Systemic	1.6 mg/kg		
	effects	1.0 mg/kg		
		00		
methanol	Acute inhalation - Systemic	26 mg/m <sup>3</sup>		
	effects			
	Acute inhalation - Local effects	26 mg/m³	Acute dermal - Systemic effects	5 mg/kg
	Acute oral - Systemic effects	5 mg/kg	Long-term - inhalation - Systemic	26 mg/m³
	-		effects	
	Long-term - inhalation - Local	26 mg/m³	Long-term - dermal - Systemic	5 mg/kg
	effects		effects	
	Long-term - oral - Systemic	5 mg/kg		
	effects			
propan-2-ol	Long-term - inhalation - Systemic	89 mg/m³		
	effects			
	Long-term - dermal - Systemic	319 mg/kg	Long-term - oral - Systemic effects	26 mg/kg
	effects			

#### 8.2. Exposure controls

	Adopt best Manual Handling considerations when handling, carrying and dispensing. Avoid contact with skin and eyes. Handle in accordance with good industrial hygiene and safety practice. Use appropriate personal protective equipment. Wear suitable protective clothing and eye/face protection.
8.2.1. Appropriate engineering controls	Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapours below there respective threshold limit value. Ensure eyewash stations and safety showers are close to the workstation location.
Eye / face protection	Avoid contact with eyes. If splashes are likely to occur, wear: safety glasses with side-shields.
Skin protection - Handprotection	Rubber gloves.
Respiratory protection	No personal respiratory protective equipment normally required. In case of insufficient ventilation wear suitable respiratory equipment.
8.2.3. Environmental exposure controls	Prevent further leakage or spillage if safe to do so.
SECTION 9: Physical and ch	emical properties

9.1. Information on basic physical and chemical properties



#### 9.1. Information on basic physical and chemical properties

Appearance	Liquid
Colour	Colourless
Odour	Characteristic
Odour threshold	No data available
pH	No data available
Melting point	No data available
Initial boiling point	No data available
Flash point	40 °C
Evaporation rate	No data available
Flammability (solid, gas)	No data available
Vapour pressure	No data available
Relative Vapour Density	No data available
Density / Relative Density	0.8 - 0.825
Partition coefficient	No data available
Autoignition temperature	No data available
Viscosity	No data available
Explosive properties	No data available
Oxidising properties	No data available
Solubility	No data available

#### 9.2. Other information

Conductivity	No data available
Surface tension	No data available
Gas group	No data available
Benzene Content	No data available
Lead content	No data available
VOC (Volatile organic	No data available
compounds)	

#### 9.2.1. Information with regard to physical hazard classes

No data is available on this product.

## 9.2.2. Other safety characteristics

No data is available on this product.

Oxidising agents. Combustible materials.

## SECTION 10: Stability and reactivity

10.1. Reactivity

Flammable liquid. Stable under normal conditions.

#### 10.2. Chemical stability

Flammable liquid. Stable under normal conditions.

## 10.3. Possibility of hazardous reactions

10.4. Conditions to avoid

Avoid sparks, flames, heat and sources of ignition. Avoid storing in direct Sun Light.

## 10.5. Incompatible materials

Oxidising agents.

## 10.6. Hazardous decomposition products

No Hazardous decomposition products when stored and handled correctly.



Revision date 2022-11-21

### SECTION 11: Toxicological information

#### 11.1 Information on hazard classes

This mixture has not been tested as a whole for health effects. The health effects have been calculated using the methods outlined in Regulation (EC) No 1272/2008 (CLP).
based on available data the classification criteria are not met.
Oral ATE = >10,000 mg/kg.
Dermal ATE = >10,000 mg/kg.
Inhalation - Dust/Mist ATE = >10,000 mg/l.
based on available data the classification criteria are not met.
based on available data the classification criteria are not met.
based on available data the classification criteria are not met.
based on available data the classification criteria are not met.
based on available data the classification criteria are not met.
based on available data the classification criteria are not met.
STOT SE category 3. H336 - May cause drowsiness or dizziness.
based on available data the classification criteria are not met.
Aspiration Hazard Category 1. H304 - May be fatal if swallowed and enters airways.
Prolonged contact may cause defatting of the skin.

No data available.

## 11.1.3. Hazard Information

### No data available.

### 11.1.4. Toxicological Information

Ethylbenzene (ethyl benzol)	Oral Rat LD50: 3500 mg/kg	Dermal Rabbit LD50: 5001.0 mg/kg
	Inhalation Rat LC50/4 h: 17.2 mg/l	
methanol	Oral Rat LD50: 100.0 mg/kg	Dermal Rabbit LD50: 300.0 mg/kg
	Inhalation Rat LC50/4 h: 3.0 mg/l	
propan-2-ol	Inhalation Rat LC50/6 h: >10000ppm	Oral Rat LD50: 5840 mg/kg
	Dermal Rabbit LD50: 13900 mg/kg	

#### 11.2 Information on other hazards

No dat		ailabla	on thi	c produ	uct
NO Gai	a is av	ailable	on thi	s prou	uci.

### **SECTION 12: Ecological information**

#### 12.1. Toxicity

Ethylbenzene (ethyl benzol)	Daphnia EC50/48h: 1.8000 mg/l         Algae EC50/72h: 5.4 r	
	Rainbow trout LC50/96h: 4.2 mg/l	
methanol	Daphnia EC50/48h: 18260.0000 mg/l	Green algae EC50/96h: 22000.0 mg/l
	Fathead minnows LC50/96h: >100 mg/l	Bluegill sunfish LC50/96h: 15400.0 mg/l
	Lepomis_Macrochirus LC50/96h: 15400 mg/l	
propan-2-ol	Daphnia EC50/48h: 10000.0000 mg/l Fish LC50/96h: 4200.000	
	Fathead minnows LC50/96h: 9640 mg/l	

#### 12.2. Persistence and degradability

	Substance biodegrades at a moderate rate and inherently biodegradable according to the OECD guide lines.
12.3. Bioaccumulative potential	



Revision 10

Revision date 2022-11-21

#### 12.3. Bioaccumulative potential

	The product is not bioaccumulating.
Partition coefficient	
	Harry Fairbairn Tyre & Trim No data available propan-2-ol 0.05 log P
	Shinemethanol -0.74 Log PowEthylbenzene (ethyl benzol) 3.5
12.4. Mobility in soil	
	Immiscible in water.
12.5. Results of PBT and vPvB a	assessment
	This substance/mixture is not classified as PBT or vPvB according to current criteria.
12.6 Endocrine disrupting prope	rties
	No data is available on this product.
12.7. Other adverse effects	
	No data is available on this product.
SECTION 13: Disposal cons	iderations
13.1. Waste treatment methods	
	Dispose of waste and residues in accordance with local authority requirements.
General information	
	Dispose of in compliance with all local and national requirements.
Disposal of packaging	
	Do NOT reuse empty containers. Empty containers can be sent to landfill after cleaning, if in compliance with local and national regulations.
SECTION 14: Transport info	rmation
SECTION 14: Transport info Hazard pictograms	rmation
	rmation
Hazard pictograms	
Hazard pictograms	
Hazard pictograms 14.1. UN number	
Hazard pictograms 14.1. UN number	UN3295 HYDROCARBONS, LIQUID, N.O.S.
Hazard pictograms 14.1. UN number 14.2. UN proper shipping name 14.3. Transport hazard class(es) ADR/RID	UN3295 HYDROCARBONS, LIQUID, N.O.S.
Hazard pictograms Hazard pictograms 14.1. UN number 14.2. UN proper shipping name 14.3. Transport hazard class(es) ADR/RID Subsidiary risk	UN3295 HYDROCARBONS, LIQUID, N.O.S. 3 -
Hazard pictograms          14.1. UN number         14.2. UN proper shipping name         14.3. Transport hazard class(es)         ADR/RID         Subsidiary risk         IMDG	UN3295 HYDROCARBONS, LIQUID, N.O.S.
Hazard pictograms 14.2. UN number 14.2. UN proper shipping name 14.3. Transport hazard class(es) ADR/RID Subsidiary risk IMDG Subsidiary risk	UN3295 HYDROCARBONS, LIQUID, N.O.S. 3 - 3 -
Hazard pictograms          14.1. UN number         14.2. UN proper shipping name         14.3. Transport hazard class(es)         ADR/RID         Subsidiary risk         IMDG	UN3295 HYDROCARBONS, LIQUID, N.O.S. 3 -
Hazard pictograms Hazard pictograms 14.1. UN number 14.2. UN proper shipping name 14.3. Transport hazard class(es) ADR/RID Subsidiary risk IMDG Subsidiary risk IATA	UN3295 HYDROCARBONS, LIQUID, N.O.S. 3 - 3 -



	Revision date 2022-11-
14.5. Environmental hazards	
Environmental hazards	No
Marine pollutant	No
14.6. Special precautions for u	iser
	No additional special precautions.
14.7 Maritime Transport in bul	k according to IMO instruments
	Not applicable.
ADR/RID	
Hazard ID	30
Tunnel Category	(D/E)
MDG	
EmS Code	F-E S-D
ATA	
Packing Instruction (Cargo)	366
Maximum quantity	220 L
Packing Instruction	355
(Passenger)	
Maximum quantity	60 L
SECTION 15: Regulatory in	nformation
15.1. Safety, health and enviro	onmental regulations/legislation specific for the substance or mixture
	<ul> <li>REGULATION (EC) No 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/E and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.</li> <li>COMMISSION REGULATION (EU) No 453/2010 of 20 May 2010 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency amending Directive 1999/45/EC and repealing Council Regulation (EC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/105/EC and 2000/21/EC.</li> <li>COMMISSION REGULATION (EU) 2020/878 of 18 June 2020 amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).</li> </ul>
15.2. Chemical safety assessr	
	No information available.
SECTION 16: Other inform	ation
Other information	
Revision	<ul> <li>This document differs from the previous version in the following areas:.</li> <li>2 - Other hazards.</li> <li>2 - Precautionary Statement: Prevention.</li> <li>2 - Precautionary Statement: Response.</li> <li>2 - Precautionary Statement: Storage.</li> <li>2 - Precautionary Statement: Disposal.</li> <li>2 - Further information</li> </ul>

- 2 Further information.
- 2 SUPPLEMENTAL HAZARD INFORMATION.



Other information	
	<ul> <li>9 - 9.2.2. Other safety characteristics.</li> <li>9 - 9.2.1. Information with regard to physical hazard classes.</li> <li>11 - 11.2 Information on other hazards.</li> <li>12 - 12.6 Endocrine disrupting properties.</li> <li>12 - 12.7. Other adverse effects.</li> <li>15 - Regulations.</li> </ul>
Data sources	Classification and Procedure used to derive the classification for mixtures according to Regulation (EC) No. 1272/2008, as retained and amended in UK law. Flam. Liq. 3: H226 - Flammable liquid and vapour Flash Point - 40 degC. Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways Calculation Method. STOT SE 3: H336 - May cause drowsiness or dizziness Calculation Method.
Text of Hazard Statements in Section 3	Flam. Liq. 3: H226 - Flammable liquid and vapour. Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways. STOT SE 3: H336 - May cause drowsiness or dizziness.
Further information	
	The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.

