

according to Regulation (EU) 2020/878

# Eastern Western Glass Cleaner

Revision 20

Page

1/9

Revision date 2022-11-09

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier	
Product name	Eastern Western Glass Cleaner
1.2. Relevant identified uses of t	he substance or mixture and uses advised against
Product Use	[SU21] Consumer uses: Private households (= general public = consumers); [PC35] Washing and cleaning products (including solvent based products);
	[SU22] Professional uses: Public domain (administration, education, entertainment, services, craftsmen); [PC35] Washing and cleaning products (including solvent based products);
Description	This powerful cleaner breaks through even the toughest dirt and grime on screens, windows and mirrors, leaving a sparkling streak free finish.
1.3. Details of the supplier of the	safety data sheet
Company	SUPAGARD LIMITED
Address	19-27 Gavinton Street Muirend Glasgow G44 3EF
Web	www.supagard.com
Telephone	0141 633 5933
Fax	01416377219
Email	James.Smyth@supagard.com
Email address of the competent person	James.Smyth@supagard.com
1.4. Emergency telephone numb	
Emergency telephone number	01416335933
	8.30am to 5.00pm
	For medical advice or information you should contact your GP or NHS 111 (or NHS 24 in Scotland) on 111 (for 24 hour health advice)
	If you are a healthcare professional with an enquiry please visit www.TOXBASE.org
SECTION 2: Hazards identif	cation
2.1. Classification of the substar	ice or mixture
2.1.2. Classification - EC 1272/2008	Flam. Liq. 3: H226; Eye Irrit. 2: H319;
2.2. Label elements	



#### 2.2. Label elements Hazard pictograms Signal Word Warning Hazard Statement Flam. Lig. 3: H226 - Flammable liquid and vapour. Eye Irrit. 2: H319 - Causes serious eye irritation. **Precautionary Statement:** P102 - Keep out of reach of children. P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No Prevention smoking. P264 - Wash hands and other contacted skin thoroughly after handling. **Precautionary Statement:** P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact Response lenses, if present and easy to do. Continue rinsing. **Precautionary Statement:** P403+P235 - Store in a well-ventilated place. Keep cool. Storage **Precautionary Statement:** P501 - Dispose of contents/container to an approved disposal site, in accordance with local Disposal regulations. SUPPLEMENTAL HAZARD Ingredients as required by Regulation (EC) No 648/2004:. **INFORMATION** Isopropyl Alcohol, Butylene Glycol, Less than 5% Non-ionic Surfactants. Contains - Propan-2-ol, 2-butoxyethanol. 2.3. Other hazards Other hazards This substance/mixture is not classified as PBT or vPvB according to current criteria. The substance/mixture does not contain substances with endocrine disrupting properties. **Further information**

RECOMMENDED SHELF LIFE 1 YEAR FROM DATE OF DELIVERY.

## SECTION 3: Composition/information on ingredients

3.2. Mixtures

### EC 1272/2008

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. Classification (%w/w)
propan-2-ol	603-117-00-0	67-63-0	200-661-7	01-2119457558-25	1 - 10% Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336;
2-butoxyethanol	603-014-00-0	111-76-2	203-905-0	01-2119475108-36	1 - 10% Acute Tox. 4: H332; Acute Tox. 4: H312; Acute Tox. 4: H302; Eye Irrit. 2: H319; Skin Irrit. 2: H315;

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

Inhalation	Move the exposed person to fresh air.		
Eye contact	Rinse immediately with plenty of water. Contact lenses should be removed.		
Skin contact	Remove contaminated clothing. Wash with water and soap as a precaution.		
Ingestion	DO NOT INDUCE VOMITING. Rinse mouth thoroughly.		
4.2. Most important symptoms and effects, both acute and delayed			
Inhalation	High concentration of vapour in enclosed space may cause irritation, headaches and nausea. May cause irritation to respiratory system.		
Eye contact	Irritating to eyes.		
Skin contact	May cause skin dryness and irritation. Prolonged contact may cause defatting of the skin.		



Revision date 2022-11-09

4.2. Most important symptoms and effects, both acute and delayed				
Ingestion	May cause irritation to mucous membranes.			
4.3. Indication of any immediate medical attention and special treatment needed				
	TREAT SYMPTOMATICALLY.			
Inhalation	Move the exposed person to fresh air. Seek medical attention if irritation or symptoms persist.			
Eye contact	Contact lenses should be removed. Rinse immediately with plenty of water. Seek medical attention if irritation or symptoms persist.			
Skin contact	Seek medical attention if irritation or symptoms persist.			
Ingestion	Drink 1 to 2 glasses of water. Seek medical attention if irritation or symptoms persist.			
General information				
	If you feel unwell, seek medical advice (show the label where possible). Treat symptomatically.			
SECTION 5: Firefighting mea	asures			
5.1. Extinguishing media				
	Flammable liquid. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.			
5.2. Special hazards arising from	n the substance or mixture			
	Flammable liquid and vapour.			
5.3. Advice for firefighters				
	Fire fighters should wear self contained positive pressure breathing apparatus (SCBA) and full turnout gear.			
Further information				
	In the event of a fire and/or explosion do not breath fumes. Standard procedure for chemical fires. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.			
SECTION 6: Accidental relea	ase measures			
6.1. Personal precautions, prote	ctive equipment and emergency procedures			
	Wear suitable protective equipment. Flammable liquid. Avoid sparks, flames, heat and sources of ignition.			
6.2. Environmental precautions				
	Advise local authorities if large spills cannot be contained.			
6.3. Methods and material for co	ntainment and cleaning up			
	Absorb with inert, absorbent material. Sweep up. Transfer to suitable, labelled containers for disposal. Avoid sparks, flames, heat and sources of ignition.			
6.4. Reference to other sections				
	See section 2, 7, 8, 13 for further information.			
SECTION 7: Handling and st	torage			
7.1. Precautions for safe handlin	g			
	Adopt best Manual Handling considerations when handling, carrying and dispensing.			
7.2. Conditions for safe storage,	including any incompatibilities			
	Flammable liquid. Avoid sparks, flames, heat and sources of ignition. Avoid storing in direct Sun Light. Store in a well-ventilated place. Keep cool. Store in original container. Keep container tightly closed. Keep away from combustible material. Keep out of the reach of children.			
7.3. Specific end use(s)				
	This powerful cleaner breaks through even the toughest dirt and grime on screens, windows and			



7.3. Specific end use(s)

mirrors, leaving a sparkling streak free finish.

### Suitable packaging

Plastic containers.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

Occupational exposure controls.

8.1.1. Exposure Limit Values				
2-butoxyethanol	WEL 8-hr limit ppm: 25	WEL 8-hr limit mg/m3: 123		
	WEL 15 min limit ppm: 50	WEL 15 min limit mg/m3: 101.2		
	WEL 8-hr limit mg/m3 total -	WEL 15 min limit mg/m3 total -		
	inhalable dust:	inhalable dust:		
WEL 8-hr limit mg/m3 total -		WEL 15 min limit mg/m3 total -		
	respirable dust:	respirable dust:		
propan-2-ol	WEL 8-hr limit ppm: 400	WEL 8-hr limit mg/m3: 999		
	WEL 15 min limit ppm: 500	WEL 15 min limit mg/m3: 1250		
	WEL 8-hr limit mg/m3 total -	WEL 15 min limit mg/m3 total -		
	inhalable dust:	inhalable dust:		
	WEL 8-hr limit mg/m3 total -	WEL 15 min limit mg/m3 total -		
	respirable dust:	respirable dust:		

DNEL: Derived no-effect level.

Exposure Pattern - Workers					
2-butoxyethanol Acute inhalation - Systemic 1091 mg/m <sup>3</sup> effects					
	Acute inhalation - Local effects 246 mg/m <sup>3</sup>	Acute dermal - Systemic effects 89 mg/kg			
	Long-term - inhalation - Systemic 98 mg/m <sup>3</sup>	Long-term - dermal - Systemic 125 mg/kg			
	effects	effects			
propan-2-ol	Long-term - inhalation - Systemic 500 mg/m <sup>3</sup>				
	effects				
	Long-term - dermal - Systemic 888 mg/kg				
	effects				

### Exposure Pattern - General population

2-butoxyethanol	Acute inhalation - Systemic effects Acute dermal - Systemic effects	C C	Acute oral - Systemic effects	26.7 mg/kg
	Long-term - inhalation - Systemic effects	59 mg/m³	Long-term - inhalation - Local effects	147 mg/m³
	Long-term - dermal - Systemic effects	75 mg/kg	Long-term - oral - Systemic effects	6.3 mg/kg
propan-2-ol	Long-term - inhalation - Systemic effects	89 mg/m³		
	Long-term - dermal - Systemic effects	319 mg/kg	Long-term - oral - Systemic effects	26 mg/kg

#### 8.2. Exposure controls



8.2. Exposure controls	
	Adopt best Manual Handling considerations when handling, carrying and dispensing. Avoid contact with skin and eyes. Handle in accordance with good industrial hygiene and safety practice. Use appropriate personal protective equipment. Wear suitable protective clothing and eye/face protection.
8.2.1. Appropriate engineering controls	Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapours below there respective threshold limit value. Ensure eyewash stations and safety showers are close to the workstation location.
Eye / face protection	Avoid contact with eyes. If splashes are likely to occur, wear: safety glasses with side-shields.
Skin protection - Handprotection	Rubber gloves.
Respiratory protection	No personal respiratory protective equipment normally required. In case of insufficient ventilation wear suitable respiratory equipment.
8.2.3. Environmental exposure controls	Prevent further leakage or spillage if safe to do so.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Appearance	Liquid
Colour	Clear/Blue
Odour	Alcoholic
рH	6 - 9
Melting point	No data available
Initial boiling point	No data available
Flash point	40 °C
Evaporation rate	No data available
Flammability (solid, gas)	No data available
Vapour Flammability	No data available
Vapour pressure	No data available
Relative Vapour Density	No data available
Density / Relative Density	No data available
Partition coefficient	No data available
Autoignition temperature	No data available
Viscosity	< 50 centipoise
Explosive properties	No data available
Oxidising properties	No data available
Solubility	Soluble in water

### 9.2. Other information

VOC (Volatile organic	No data available
compounds)	
Conductivity	No data available
Surface tension	No data available
Specific gravity	0.98 - 0.99 g/cm³
Gas group	Not applicable.
Benzene Content	Not applicable.
Lead content	Not applicable.

Water solubility

Soluble.

# 9.2.1. Information with regard to physical hazard classes

No data is available on this product.



Revision 20 Revision date 2022-11-09

#### 9.2.2. Other safety characteristics

	No data is available on this product.			
SECTION 10: Stability and reactivity				
10.1. Reactivity				
	Flammable liquid. Stable under normal conditions.			
10.2. Chemical stability				
	Flammable liquid. Stable under normal conditions.			
10.3. Possibility of hazardous rea	10.3. Possibility of hazardous reactions			
	Oxidising agents. Combustible materials.			
10.4. Conditions to avoid	10.4. Conditions to avoid			
	Avoid sparks, flames, heat and sources of ignition. Avoid storing in direct Sun Light.			
10.5. Incompatible materials				
	Oxidising agents.			
10.6. Hazardous decomposition products				
	No Hazardous decomposition products when stored and handled correctly.			
SECTION 11: Toxicological i	nformation			
11.1 Information on hazard classes				

#### This mixture has not been tested as a whole for health effects. The health effects have been calculated using the methods outlined in Regulation (EC) No 1272/2008 (CLP). based on available data the classification criteria are not met. Acute toxicity Oral ATE = >10,000 mg/kg. Dermal ATE = >10,000 mg/kg. Inhalation - Dust/Mist ATE = >20mg/l. Skin corrosion/irritation based on available data the classification criteria are not met. Eye Irrit. 2: H319 - Causes serious eye irritation. Serious eye damage/irritation Respiratory or skin based on available data the classification criteria are not met. sensitisation Germ cell mutagenicity based on available data the classification criteria are not met. Carcinogenicity based on available data the classification criteria are not met. Reproductive toxicity based on available data the classification criteria are not met. STOT-single exposure based on available data the classification criteria are not met. STOT-repeated exposure based on available data the classification criteria are not met. Aspiration hazard based on available data the classification criteria are not met. Repeated or prolonged based on available data the classification criteria are not met. exposure 11.1.2. Mixtures No data available. 11.1.3. Hazard Information No data available. 11.1.4. Toxicological Information Dermal Rat LD50: 1100 mg/kg 2-butoxyethanol Oral Rat LD50: 1300 mg/kg Inhalation Rat LC50/4 h: 11.0 mg/l propan-2-ol Inhalation Rat LC50/6 h: >10000ppm Oral Rat LD50: 5840 mg/kg



Dermal Rabbit LD50: 13900 mg/kg

 Revision
 20

 Revision date
 2022-11-09

### 11.2 Information on other hazards

No data is available on this product.

### SECTION 12: Ecological information

12.1.	Toxici	ty
-------	--------	----

2-butoxyethanol	Daphnia EC50/48h: 1550.0000 mg/l	Algae EC50/72h: 1840 mg/
	Rainbow trout LC50/96h: 1474 mg/l	
	EC50 for marine or freshwater >100.0000 mg/l	LC50 for marine or freshwater >100.0000 mg/l
	organisms	organisms
propan-2-ol	Daphnia EC50/48h: 10000.0000 mg/l	Fish LC50/96h: 4200.0000 mg/l
	Fathead minnows LC50/96h: 9640 mg/l	

#### 12.2. Persistence and degradability

Substance biodegrades at a moderate rate and inherently biodegradable according to the OECD
guide lines.

#### 12.3. Bioaccumulative potential

	The product is not bioaccumulating.	
Partition coefficient		
	Eastern Western Glass Cleaner No data available	propan-2-ol 0.05 log P
	2-butoxyethanol 0.8 log P	

### 12.4. Mobility in soil

This product is soluble in water.

## 12.5. Results of PBT and vPvB assessment

This substance/mixture is not classified as PBT or vPvB according to current criteria.

### 12.6 Endocrine disrupting properties

No data is available on this product.

#### 12.7. Other adverse effects

No data is available on this product.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

	Dispose of waste and residues in accordance with local authority requirements.
General information	
	Dispose of in compliance with all local and national requirements.
Disposal of packaging	
	Do NOT reuse empty containers. Empty containers can be sent to landfill after cleaning, if in compliance with local and national regulations.
SECTION 14: Transport information	

#### Hazard pictograms



### 14.1. UN number



 Revision
 20

 Revision date
 2022-11-09

14.1. UN number		
	UN1993	
14.2. UN proper shipping name		
	FLAMMABLE LIQUID, N.O.S. (contains Isopropanol)	
14.3. Transport hazard class(es)		
ADR/RID	3	
Subsidiary risk	-	
IMDG	3	
Subsidiary risk	-	
IATA	3	
Subsidiary risk	-	
14.4. Packing group		
Packing group	111	
14.5. Environmental hazards		
Environmental hazards	No	
Marine pollutant	No	
14.6. Special precautions for use	Pr	
	No additional special precautions.	
14.7 Maritime Transport in bulk a	according to IMO instruments	
	Not applicable.	
ADR/RID		
Hazard ID	30	
Tunnel Category	(D/E)	
IMDG		
EmS Code	F-E S-E	
ΙΑΤΑ		
Packing Instruction (Cargo)	366	
Maximum quantity	220 L	
Packing Instruction	355	
(Passenger)		
Maximum quantity	60 L	
SECTION 15: Regulatory information		
15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture		

Regulations	REGULATION (EC) No 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.
	COMMISSION REGULATION (EU) No 453/2010 of 20 May 2010 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.



## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

(EC) No 1007/2006 of the European Deviewant and of the Council concerning the Devietnetion	
(EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration,	
Evaluation, Authorisation and Restriction of Chemicals (REACH).	

### 15.2. Chemical safety assessment

No information available

### SECTION 16: Other information

### Other information

Deudalan		
Revision	This document differs from the previous version in the following areas:	
	2 - Other hazards.	
	2 - Further information.	
	2 - SUPPLEMENTAL HAZARD INFORMATION.	
	9 - 9.2.2. Other safety characteristics.	
	9 - 9.2.1. Information with regard to physical hazard classes.	
	11 - Acute toxicity.	
	11 - Repeated or prolonged exposure.	
	11 - 11.2 Information on other hazards.	
	12 - 12.1. Toxicity.	
	12 - 12.6 Endocrine disrupting properties.	
	12 - 12.7. Other adverse effects.	
	15 - Regulations.	
Data sources	Classification and Procedure used to derive the classification for mixtures according to Regulation	
	(EC) No. 1272/2008, as retained and amended in UK law.	
	Flam. Liq. 3: H226 - Flammable liquid and vapour Flash Point - 40 degC.	
	Eye Irrit. 2: H319 - Causes serious eye irritation Calculation Method.	
Text of Hazard Statements in	Flam. Liq. 2: H225 - Highly flammable liquid and vapour.	
Section 3	Eye Irrit. 2: H319 - Causes serious eye irritation.	
	STOT SE 3: H336 - May cause drowsiness or dizziness.	
	Acute Tox. 4: H302+H312+H332 - Harmful if swallowed, in contact with skin or if inhaled	
	Skin Irrit. 2: H315 - Causes skin irritation.	
Further information		
	The information supplied in this Safety Data Sheet is designed only as guidance for the safe use,	
	storage and handling of the product. This information is correct to the best of our knowledge and	
	belief at the date of publication however no guarantee is made to its accuracy. This information	
	relates only to the specific material designated and may not be valid for such material used in	
	combination with any other materials or in any other process.	

