

according to Regulation (EU) 2020/878

Page 1/10

## Eastern Western Tyre and Trim Dressing

 Revision
 10

 Revision date
 2022-11-21

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier		
Product name	Eastern Western Tyre and Trim Dressing	
1.2. Relevant identified uses of the substance or mixture and uses advised against		
Product Use	[SU22] Professional uses: Public domain (administration, education, entertainment, services, craftsmen); [PC35] Washing and cleaning products (including solvent based products);	
	[SU21] Consumer uses: Private households (= general public = consumers); [PC35] Washing and cleaning products (including solvent based products);	
Description	This new water resistant coating has been carefully formulated for the renovation of all plastics, PVC, rubber etc, throughout your vehicle.	
1.3. Details of the supplier of the	safety data sheet	
Company	SUPAGARD LIMITED	
Address	19-27 Gavinton Street Muirend	
	Glasgow G44 3EF	
Web	www.supagard.com	
Telephone	0141 633 5933	
Fax	01416377219	
Email	James.Smyth@supagard.com	
Email address of the competent person	James.Smyth@supagard.com	
1.4. Emergency telephone numb	ber	
Emergency telephone number	01416335933	
	8.30am to 5.00pm	
	For medical advice or information you should contact your GP or NHS 111 (or NHS 24 in Scotland) on 111 (for 24 hour health advice)	
	If you are a healthcare professional with an enquiry please visit www.TOXBASE.org	
SECTION 2: Hazards identifi	cation	
2.1. Classification of the substar	ice or mixture	
2.1.2. Classification - EC 1272/2008	Flam. Liq. 3: H226; Asp. Tox. 1: H304; STOT SE 3: H336;	
2.2. Label elements		



 Revision
 10

 Revision date
 2022-11-21

2.2. Label elements	
Hazard pictograms	
Signal Word	Danger
Hazard Statement	Flam. Liq. 3: H226 - Flammable liquid and vapour. Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways. STOT SE 3: H336 - May cause drowsiness or dizziness.
Precautionary Statement: Prevention	P102 - Keep out of reach of children. P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Precautionary Statement: Response	<ul> <li>P301+P310+P330+P331 - IF SWALLOWED: Immediately call a POISON CENTER/doctor. Rinse mouth. Do NOT induce vomiting.</li> <li>P302+P350 - IF ON SKIN: Gently wash with plenty of soap and water.</li> <li>P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.</li> </ul>
Precautionary Statement: Storage	P403+P233 - Store in a well-ventilated place. Keep container tightly closed.
SUPPLEMENTAL HAZARD	Ingredients as required by Regulation (EC) No 648/2004:. Less than 5% Aromatic Hydrocarbons, Dimethicone, Amino functional silicone.
	Contains - Hydrocarbons, C9-11, N-alkanes, Isoalkanes, Cyclics, <2% Aromatic.
2.3. Other hazards	
Other hazards	This substance/mixture is not classified as PBT or vPvB according to current criteria. The substance/mixture does not contain substances with endocrine disrupting properties.
Further information	

RECOMMENDED SHELF LIFE 1 YEAR FROM DATE OF DELIVERY.

## SECTION 3: Composition/information on ingredients

#### 3.2. Mixtures

#### EC 1272/2008

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification
Hydrocarbons, C9-11, N-alkanes, Isoalkanes, Cyclics, <2% Aromatic		1174522-20-3	3 919-857-5	01-2119463258-33	50 - 60%	Flam. Liq. 3: H226; Asp. Tox. 1: H304; STOT SE 3: H336;

### **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

Inhalation	Move the exposed person to fresh air.
Eye contact	Rinse immediately with plenty of water. Contact lenses should be removed.
Skin contact	Remove contaminated clothing. Wash with water and soap as a precaution.
Ingestion	DO NOT INDUCE VOMITING. If swallowed, do not induce vomiting: seek medical advice
	immediately and show this container or label. Rinse mouth thoroughly.

#### 4.2. Most important symptoms and effects, both acute and delayed

Inhalation	High concentration of vapour in enclosed space may cause irritation, headaches and nausea. May cause irritation to respiratory system.	
Eye contact	Irritating to eyes.	
Skin contact	May cause skin dryness and irritation. Prolonged contact may cause defatting of the skin.	
Ingestion	Harmful if ingested or swallowed.	
4.2. Indication of any immediate medical attention and appeal treatment peopled		

#### 4.3. Indication of any immediate medical attention and special treatment needed



Revision date 2022-11-21

4.3. Indication of any immediate	medical attention and special treatment needed
	TREAT SYMPTOMATICALLY.
Inhalation	Move the exposed person to fresh air. Seek medical attention if irritation or symptoms persist.
Eye contact	Contact lenses should be removed. Rinse immediately with plenty of water. Seek medical attention
	if irritation or symptoms persist.
Skin contact	Seek medical attention if irritation or symptoms persist.
Ingestion	Drink 1 to 2 glasses of water. Seek medical attention if irritation or symptoms persist.
General information	
	If you feel unwell, seek medical advice (show the label where possible). Treat symptomatically.
SECTION 5: Firefighting mea	asures
5.1. Extinguishing media	
	Flammable liquid. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
5.2. Special hazards arising from	n the substance or mixture
	Burning produces irritating, toxic and obnoxious fumes.
5.3. Advice for firefighters	
	Fire fighters should wear self contained positive pressure breathing apparatus (SCBA) and full turnout gear.
Further information	
	In the event of a fire and/or explosion do not breath fumes. Standard procedure for chemical fires. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
SECTION 6: Accidental relea	ase measures
6.1. Personal precautions, prote	ctive equipment and emergency procedures
	Wear suitable protective equipment. Flammable liquid. Avoid sparks, flames, heat and sources of ignition.
6.2. Environmental precautions	
	Advise local authorities if large spills cannot be contained.
6.3. Methods and material for co	ntainment and cleaning up
	Absorb with inert, absorbent material. Sweep up. Transfer to suitable, labelled containers for disposal. Avoid sparks, flames, heat and sources of ignition.
6.4. Reference to other sections	
	See section 2, 7, 8, 13 for further information.
SECTION 7: Handling and s	torage
7.1. Precautions for safe handlin	g
	Adopt best Manual Handling considerations when handling, carrying and dispensing.
7.2. Conditions for safe storage,	including any incompatibilities
	Flammable liquid. Avoid sparks, flames, heat and sources of ignition. Avoid storing in direct Sun Light. Store in a well-ventilated place. Keep cool. Store in original container. Keep container tightly closed. Keep away from combustible material. Keep out of the reach of children.
7.3. Specific end use(s)	
	This new water resistant coating has been carefully formulated for the renovation of all plastics, PVC, rubber etc. throughout your vehicle.
Suitable packaging	



Suitable packaging

### Plastic containers.

## SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

#### Occupational exposure controls.

8.1.1. Exposure	Limit Values
-----------------	--------------

Ethylbenzene (ethyl benzol) (Ethylbenzene)	WEL 8-hr limit ppm: 100	WEL 8-hr limit mg/m3: 441
	WEL 15 min limit ppm: 125	WEL 15 min limit mg/m3: 552
	WEL 8-hr limit mg/m3 total - inhalable dust:	WEL 15 min limit mg/m3 total - inhalable dust:
	WEL 8-hr limit mg/m3 total - respirable dust:	WEL 15 min limit mg/m3 total - respirable dust:
methanol	WEL 8-hr limit ppm: 200	WEL 8-hr limit mg/m3: 266
	WEL 15 min limit ppm: 250	WEL 15 min limit mg/m3: 333
	WEL 8-hr limit mg/m3 total - inhalable dust:	WEL 15 min limit mg/m3 total - inhalable dust:
	WEL 8-hr limit mg/m3 total - respirable dust:	WEL 15 min limit mg/m3 total - respirable dust:
propan-2-ol	WEL 8-hr limit ppm: 400	WEL 8-hr limit mg/m3: 999
	WEL 15 min limit ppm: 500	WEL 15 min limit mg/m3: 1250
	WEL 8-hr limit mg/m3 total - inhalable dust:	WEL 15 min limit mg/m3 total - inhalable dust:
	WEL 8-hr limit mg/m3 total - respirable dust:	WEL 15 min limit mg/m3 total - respirable dust:

#### DNEL: Derived no-effect level.

Ethylbenzene (ethyl benzol)	Acute inhalation - Local effects	293 mg/m <sup>3</sup>		
	Long-term - inhalation - Systemic effects	77 mg/m³	Long-term - dermal - Systemic effects	180 mg/kg
methanol	Acute inhalation - Systemic effects	130 mg/m <sup>3</sup>		
	Acute inhalation - Local effects	130 mg/m³	Acute dermal - Systemic effects	20 mg/kg
	Long-term - inhalation - Systemic effects	130 mg/m³	Long-term - inhalation - Local effects	130 mg/m <sup>3</sup>
	Long-term - dermal - Systemic effects	20 mg/kg		
propan-2-ol	Long-term - inhalation - Systemic effects	500 mg/m <sup>3</sup>		
	Long-term - dermal - Systemic effects	888 mg/kg		

Exposure Pattern - General population

#### Copyright © 2022 ChemSoft. All rights reserved.



#### Exposure Pattern - General population

Ethylbenzene (ethyl benzol)	Long-term - inhalation - Systemic	15 ma/m <sup>3</sup>		
	effects	•		
	Long-term - oral - Systemic	1.6 mg/kg		
	effects	0.0		
methanol	Acute inhalation - Systemic	26 mg/m <sup>3</sup>		
	effects			
	Acute inhalation - Local effects	26 mg/m³	Acute dermal - Systemic effects	5 mg/kg
	Acute oral - Systemic effects	5 mg/kg	Long-term - inhalation - Systemic effects	26 mg/m³
	Long-term - inhalation - Local	26 mg/m³	Long-term - dermal - Systemic	5 mg/kg
	effects		effects	
	Long-term - oral - Systemic	5 mg/kg		
	effects			
propan-2-ol	Long-term - inhalation - Systemic	89 mg/m³		
	effects			
	Long-term - dermal - Systemic	319 mg/kg	Long-term - oral - Systemic effects	26 mg/kg
	effects			

#### 8.2. Exposure controls

	Adopt best Manual Handling considerations when handling, carrying and dispensing. Avoid contact with skin and eyes. Handle in accordance with good industrial hygiene and safety practice. Use appropriate personal protective equipment. Wear suitable protective clothing and eye/face protection.
8.2.1. Appropriate engineering controls	Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapours below there respective threshold limit value. Ensure eyewash stations and safety showers are close to the workstation location.
Eye / face protection	Avoid contact with eyes. If splashes are likely to occur, wear: safety glasses with side-shields.
Skin protection - Handprotection	Rubber gloves.
Respiratory protection	No personal respiratory protective equipment normally required. In case of insufficient ventilation wear suitable respiratory equipment.
8.2.3. Environmental exposure controls	Prevent further leakage or spillage if safe to do so.
SECTION 9: Physical and ch	iemical properties

9.1. Information on basic physical and chemical properties



#### 9.1. Information on basic physical and chemical properties

Appearance	Liquid
Colour	Colourless
Odour	Characteristic
Oxidising properties	No data available
Odour threshold	No data available
рH	No data available
Melting point	No data available
Initial boiling point	No data available
Flash point	40 °C
Evaporation rate	No data available
Flammability (solid, gas)	No data available
Vapour pressure	No data available
Relative Vapour Density	No data available
Density / Relative Density	0.8 - 0.825
Partition coefficient	No data available
Autoignition temperature	No data available
Viscosity	No data available
Explosive properties	No data available
Solubility	No data available

#### 9.2. Other information

Conductivity	No data available
-	No data available
	No data available
	No data available
	No data available
VOC (Volatile organic	
compounds)	

#### 9.2.1. Information with regard to physical hazard classes

No data is available on this product.

## 9.2.2. Other safety characteristics

No data is available on this product.

Oxidising agents. Combustible materials.

### SECTION 10: Stability and reactivity

10.1. Reactivity

Flammable liquid. Stable under normal conditions.

#### 10.2. Chemical stability

Flammable liquid. Stable under normal conditions.

## 10.3. Possibility of hazardous reactions

10.4. Conditions to avoid

Avoid sparks, flames, heat and sources of ignition. Avoid storing in direct Sun Light.

### 10.5. Incompatible materials

Oxidising agents.

## 10.6. Hazardous decomposition products

No Hazardous decomposition products when stored and handled correctly.



Revision 10

Revision date 2022-11-21

## SECTION 11: Toxicological information

#### 11.1 Information on hazard classes

	This mixture has not been tested as a whole for health effects. The health effects have been calculated using the methods outlined in Regulation (EC) No 1272/2008 (CLP).
Acute toxicity	based on available data the classification criteria are not met.
	Oral ATE = >10,000 mg/kg.
	Dermal ATE = >10,000 mg/kg.
	Inhalation - Dust/Mist ATE = >10,000 mg/l.
Skin corrosion/irritation	based on available data the classification criteria are not met.
Serious eye damage/irritation	based on available data the classification criteria are not met.
Respiratory or skin sensitisation	based on available data the classification criteria are not met.
Germ cell mutagenicity	based on available data the classification criteria are not met.
Carcinogenicity	based on available data the classification criteria are not met.
Reproductive toxicity	based on available data the classification criteria are not met.
STOT-single exposure	STOT SE category 3. H336 - May cause drowsiness or dizziness.
STOT-repeated exposure	based on available data the classification criteria are not met.
Aspiration hazard	Aspiration Hazard Category 1. H304 - May be fatal if swallowed and enters airways.
Repeated or prolonged	Prolonged contact may cause defatting of the skin.
exposure	
11.1.2. Mixtures	

No data available.

## 11.1.3. Hazard Information

## No data available.

## 11.1.4. Toxicological Information

Ethylbenzene (ethyl benzol)	Oral Rat LD50: 3500 mg/kg	Dermal Rabbit LD50: 5001.0 mg/kg
	Inhalation Rat LC50/4 h: 17.2 mg/l	
methanol	Oral Rat LD50: 100.0 mg/kg	Dermal Rabbit LD50: 300.0 mg/kg
	Inhalation Rat LC50/4 h: 3.0 mg/l	
propan-2-ol	Inhalation Rat LC50/6 h: >10000ppm	Oral Rat LD50: 5840 mg/kg
	Dermal Rabbit LD50: 13900 mg/kg	

#### 11.2 Information on other hazards

No data is available on this product.

### SECTION 12: Ecological information

#### 12.1. Toxicity

Ethylbenzene (ethyl benzol)	Daphnia EC50/48h: 1.8000 mg/l	Algae EC50/72h: 5.4 mg/l
	Rainbow trout LC50/96h: 4.2 mg/l	
methanol	Daphnia EC50/48h: 18260.0000 mg/l	Green algae EC50/96h: 22000.0 mg/l
	Fathead minnows LC50/96h: >100 mg/l	Bluegill sunfish LC50/96h: 15400.0 mg/l
	Lepomis_Macrochirus LC50/96h: 15400 mg/l	
propan-2-ol	Daphnia EC50/48h: 10000.0000 mg/l	Fish LC50/96h: 4200.0000 mg/l
	Fathead minnows LC50/96h: 9640 mg/l	

#### 12.2. Persistence and degradability

	Substance biodegrades at a moderate rate and inherently biodegradable according to the OECD guide lines.
12.3. Bioaccumulative potential	



 Revision
 10

 Revision date
 2022-11-21

12.3. Bioaccumulative potential

	The product is not bioaccumulating.
Partition coefficient	
	Eastern Western Tyre and Trim No data available propan-2-ol 0.05 log P
	Dressing methanol -0.74 Log Pow Ethylbenzene (ethyl benzol) 3.5
12.4. Mobility in soil	
	Immiscible in water.
12.5. Results of PBT and vPvB	assessment
	This substance/mixture is not classified as PBT or vPvB according to current criteria.
12.6 Endocrine disrupting prope	rties
	No data is available on this product.
12.7. Other adverse effects	
	No data is available on this product.
SECTION 13: Disposal cons	iderations
13.1. Waste treatment methods	
	Dispose of waste and residues in accordance with local authority requirements.
General information	
	Dispose of in compliance with all local and national requirements.
Disposal of packaging	
	Do NOT reuse empty containers. Empty containers can be sent to landfill after cleaning, if in
	compliance with local and national regulations.
SECTION 14: Transport info	
SECTION 14: Transport info Hazard pictograms	
Hazard pictograms	
Hazard pictograms	rmation
Hazard pictograms	rmation
Hazard pictograms	rmation UN3295 HYDROCARBONS, LIQUID, N.O.S.
Hazard pictograms          Hazard pictograms         14.1. UN number         14.2. UN proper shipping name	rmation UN3295 HYDROCARBONS, LIQUID, N.O.S.
Hazard pictograms          Hazard pictograms         14.1. UN number         14.2. UN proper shipping name         14.3. Transport hazard class(es	rmation UN3295 HYDROCARBONS, LIQUID, N.O.S.
Hazard pictograms          Hazard pictograms         14.1. UN number         14.2. UN proper shipping name         14.3. Transport hazard class(es         ADR/RID         Subsidiary risk         IMDG	rmation UN3295 HYDROCARBONS, LIQUID, N.O.S.
Hazard pictograms         14.1. UN number         14.2. UN proper shipping name         14.3. Transport hazard class(es         ADR/RID         Subsidiary risk         IMDG         Subsidiary risk	rmation UN3295 HYDROCARBONS, LIQUID, N.O.S. 3 -
Hazard pictograms Hazard pictograms 14.1. UN number 14.2. UN proper shipping name 14.3. Transport hazard class(es ADR/RID Subsidiary risk IMDG Subsidiary risk IATA	rmation UN3295 HYDROCARBONS, LIQUID, N.O.S. 3 -
Hazard pictograms         14.1. UN number         14.2. UN proper shipping name         14.3. Transport hazard class(es         ADR/RID         Subsidiary risk         IMDG         Subsidiary risk         IATA         Subsidiary risk	rmation UN3295 UN3295 I HYDROCARBONS, LIQUID, N.O.S. 3 - 3 - 3 - 3 -
Hazard pictograms Hazard pictograms 14.1. UN number 14.2. UN proper shipping name 14.3. Transport hazard class(es ADR/RID Subsidiary risk IMDG Subsidiary risk IATA	rmation UN3295 UN3295 I HYDROCARBONS, LIQUID, N.O.S. 3 - 3 - 3 - 3 -



14.5. Environmental hazards	
Environmental hazards	No
Marine pollutant	No
14.6. Special precautions for use	er en
	No additional special precautions.
14.7 Maritime Transport in bulk a	
	Not applicable.
ADR/RID	
Hazard ID	30
Tunnel Category	(D/E)
IMDG	
EmS Code	F-E S-D
IATA	
	266
Packing Instruction (Cargo) Maximum quantity	366 220 L
Packing Instruction	355
(Passenger)	
Maximum quantity	60 L
SECTION 15: Regulatory info	ormation
	mental regulations/legislation specific for the substance or mixture
Regulations	REGULATION (EC) No 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL
	of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.
	COMMISSION REGULATION (EU) No 453/2010 of 20 May 2010 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.
	COMMISSION REGULATION (EU) 2020/878 of 18 June 2020 amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).
15.2. Chemical safety assessme	ent
	No information available.
SECTION 16: Other informat	lion
Other information	
Revision	<ul> <li>This document differs from the previous version in the following areas:.</li> <li>2 - Other hazards.</li> <li>2 - Precautionary Statement: Prevention.</li> <li>2 - Precautionary Statement: Response.</li> <li>2 - Precautionary Statement: Storage.</li> <li>2 - Precautionary Statement: Disposal.</li> </ul>



Other information	
	9 - 9.2.2. Other safety characteristics.
	9 - 9.2.1. Information with regard to physical hazard classes.
	11 - 11.2 Information on other hazards.
	12 - 12.6 Endocrine disrupting properties.
	12 - 12.7. Other adverse effects.
	15 - Regulations.
Data sources	Classification and Procedure used to derive the classification for mixtures according to Regulation
	(EC) No. 1272/2008, as retained and amended in UK law.
	Flam. Liq. 3: H226 - Flammable liquid and vapour Flash Point - 40 degC.
	Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways Calculation Method.
	STOT SE 3: H336 - May cause drowsiness or dizziness Calculation Method.
Text of Hazard Statements in	Flam. Liq. 3: H226 - Flammable liquid and vapour.
Section 3	Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways.
	STOT SE 3: H336 - May cause drowsiness or dizziness.
Further information	
	The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.

