SAFETY DATA SHEET

according to Regulation (EU) 2020/878

Vehicle Paintwork Water Spot Remover Concentrate

Revision 25

Revision date 2022-11-03

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name	Vehicle Paintwork Water Spot Remover Concentrate

1.2. Relevant identified uses of the substance or mixture and uses advised against

Product Use	[SU22] Professional uses: Public domain (administration, education, entertainment, services, craftsmen); [PC35] Washing and cleaning products (including solvent based products);
Description	A concentrated acid cleaning solution containing Oxalic Acid, for the removal of iron brake block dust from railway rolling stock. Dilute at the rate of 1 part concentrate to 2 parts water.

1.3. Details of the supplier of the safety data sheet

Company	SUPAGARD LIMITED
Address	19-27 Gavinton Street Muirend Glasgow G44 3EF
Web	www.supagard.com
Telephone	0141 633 5933
Fax	01416377219
Email	James.Smyth@supagard.com
Email address of the competent person	James.Smyth@supagard.com

1.4. Emergency telephone number

Emergency telephone number	01416335933 8.30am to 5.00pm For medical advice or information you should contact your GP or NHS 111 (or NHS 24 in Scotland) on 111 (for 24 hour health advice) If you are a healthcare professional with an enquiry please visit www.TOXBASE.org

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

2.1.2. Classification - EC 1272/2008	Eye Dam. 1: H318;

2.2. Label elements

Hazard pictograms	
Signal Word	Danger

Vehicle Paintwork Water Spot Remover Concentrate

2.2. Label elements

Hazard Statement	Eye Dam. 1: H318 - Causes serious eye damage.
Precautionary Statement: Prevention	P280 - Wear protective gloves/protective clothing/eye protection/face protection.
Precautionary Statement: Response	P302+P350 - IF ON SKIN: Gently wash with plenty of soap and water. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P332+P313 - If skin irritation occurs: Get medical advice/attention. P337+P313 - If eye irritation persists: Get medical advice/attention.
SUPPLEMENTAL HAZARD INFORMATION	Ingredients - Triethanolamine, Ethanedioic Acid, Less than 5% Non-ionic surfactants, Butylene Glycol. Contains - C9-11 Alcohol, ethoxylated, 2,2',2''-Nitrilotriethanol, Oxalic Acid, 2-butoxyethanol.

2.3. Other hazards

Other hazards	This substance/mixture is not classified as PBT or vPvB according to current criteria. The substance/mixture does not contain substances with endocrine disrupting properties.

Further information

	RECOMMENDED SHELF LIFE 1 YEAR FROM DATE OF DELIVERY.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

EC 1272/2008

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification
C9-11 Alcohol, ethoxylated		68439-45-2			1 - 10%	Acute Tox. 4: H302; Eye Dam. 1: H318;
2,2',2''-Nitrilotriethanol		102-71-6	203-049-8	01-2119486482-31	1 - 10%	
Oxalic Acid (Oxalic acid)		6153-56-6	205-634-3	01-2119534576-33	1 - 10%	Acute Tox. 4: H302; Acute Tox. 4: H312; Eye Dam. 1: H318;
2-butoxyethanol	603-014-00-0	111-76-2	203-905-0	01-2119475108-36	1 - 10%	Acute Tox. 4: H332; Acute Tox. 4: H312; Acute Tox. 4: H302; Eye Irrit. 2: H319; Skin Irrit. 2: H315;

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	Move the exposed person to fresh air.
Eye contact	Rinse immediately with plenty of water. Contact lenses should be removed.
Skin contact	Remove contaminated clothing. Wash with water and soap as a precaution.
Ingestion	DO NOT INDUCE VOMITING. Rinse mouth thoroughly.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation	Irritating to respiratory system.
Eye contact	Causes serious eye damage.
Skin contact	Irritating to skin.
Ingestion	Irritating to mucous membranes.

4.3. Indication of any immediate medical attention and special treatment needed

Inhalation	Move the exposed person to fresh air. Seek medical attention if irritation or symptoms persist.
Eye contact	Contact lenses should be removed. Rinse immediately with plenty of water. Seek medical attention if irritation or symptoms persist.
Skin contact	Seek medical attention if irritation or symptoms persist.

Vehicle Paintwork Water Spot Remover Concentrate

4.3. Indication of any immediate medical attention and special treatment needed

Ingestion	Drink 1 to 2 glasses of water. Seek medical attention if irritation or symptoms persist.

General information

	If you feel unwell, seek medical advice (show the label where possible). Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

	This product is not flammable . Use fire-extinguishing media appropriate for surrounding materials.

5.2. Special hazards arising from the substance or mixture

	Burning produces irritating, toxic and obnoxious fumes.

5.3. Advice for firefighters

	Fire fighters should wear self contained positive pressure breathing apparatus (SCBA) and full turnout gear.

Further information

	In the event of a fire and/or explosion do not breath fumes. Standard procedure for chemical fires. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

	Wear suitable protective equipment.

6.2. Environmental precautions

	Advise local authorities if large spills cannot be contained.

6.3. Methods and material for containment and cleaning up

	For large spills:. Absorb with inert, absorbent material. Sweep up. Transfer to suitable, labelled containers for disposal. Clean spillage area thoroughly with plenty of water. For small spills:. Flush down the drain with plenty of water.

6.4. Reference to other sections

	See section 2, 7, 8, 13 for further information.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

	Adopt best Manual Handling considerations when handling, carrying and dispensing.

7.2. Conditions for safe storage, including any incompatibilities

	Store in a cool, dry area. Keep container tightly closed. Keep out of the reach of children. Store in original container.

7.3. Specific end use(s)

	A concentrated acid cleaning solution containing Oxalic Acid, for the removal of iron brake block dust from railway rolling stock. Dilute at the rate of 1 part concentrate to 2 parts water.

Suitable packaging

	Plastic containers.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

	Occupational exposure controls.

Vehicle Paintwork Water Spot Remover Concentrate

8.1.1. Exposure Limit Values

2-butoxyethanol	WEL 8-hr limit ppm:	25	WEL 8-hr limit mg/m3:	123
	WEL 15 min limit ppm:	50	WEL 15 min limit mg/m3:	101.2
	WEL 8-hr limit mg/m3 total inhalable dust:	-	WEL 15 min limit mg/m3 total inhalable dust:	-
	WEL 8-hr limit mg/m3 total respirable dust:	-	WEL 15 min limit mg/m3 total respirable dust:	-
Oxalic Acid (Oxalic acid)	WEL 8-hr limit ppm:	-	WEL 8-hr limit mg/m3:	1
	WEL 15 min limit ppm:	-	WEL 15 min limit mg/m3:	2
	WEL 8-hr limit mg/m3 total inhalable dust:	-	WEL 15 min limit mg/m3 total inhalable dust:	-
	WEL 8-hr limit mg/m3 total respirable dust:	-	WEL 15 min limit mg/m3 total respirable dust:	-

DNEL: Derived no-effect level.

Exposure Pattern - Workers

2,2',2"-Nitrilotriethanol	Long-term - inhalation - Systemic effects	5 mg/m³		
	Long-term - inhalation - Local effects	5 mg/m³	Long-term - dermal - Systemic effects	6.3 mg/kg
2-butoxyethanol	Acute inhalation - Systemic effects	1091 mg/m³		
	Acute inhalation - Local effects	246 mg/m³	Acute dermal - Systemic effects	89 mg/kg
	Long-term - inhalation - Systemic effects	98 mg/m³	Long-term - dermal - Systemic effects	125 mg/kg
Oxalic Acid	Long-term - inhalation - Systemic effects	3.11 mg/m³		
	Long-term - dermal - Systemic effects	0.882 mg/kg		

Exposure Pattern - General population

2,2',2"-Nitrilotriethanol	Long-term - inhalation - Systemic effects	1.25 mg/m³		
	Long-term - inhalation - Local effects	1.25 mg/m³	Long-term - dermal - Systemic effects	3.1 mg/kg
	Long-term - oral - Systemic effects	13 mg/kg		
2-butoxyethanol	Acute inhalation - Systemic effects	426 mg/m³		
	Acute dermal - Systemic effects	89 mg/kg	Acute oral - Systemic effects	26.7 mg/kg
	Long-term - inhalation - Systemic effects	59 mg/m³	Long-term - inhalation - Local effects	147 mg/m³
	Long-term - dermal - Systemic effects	75 mg/kg	Long-term - oral - Systemic effects	6.3 mg/kg
Oxalic Acid	Long-term - inhalation - Systemic effects	0.466 mg/m³		
	Long-term - dermal - Systemic effects	0.315 mg/kg	Long-term - oral - Systemic effects	0.315 mg/m³

8.2. Exposure controls

Adopt best Manual Handling considerations when handling, carrying and dispensing. Avoid contact with skin and eyes. Handle in accordance with good industrial hygiene and safety practice. Use

Vehicle Paintwork Water Spot Remover Concentrate

8.2. Exposure controls

	appropriate personal protective equipment. Wear suitable protective clothing and eye/face protection.
8.2.1. Appropriate engineering controls	Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapours below there respective threshold limit value. Ensure eyewash stations and safety showers are close to the workstation location.
Eye / face protection	Avoid contact with eyes. If splashes are likely to occur, wear: safety glasses with side-shields. Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. The following protection should be worn: Wear chemical splash goggles. Personal protective equipment for eye and face protection should comply with European Standard EN166.
Skin protection - Handprotection	Rubber gloves. Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer.
Respiratory protection	No personal respiratory protective equipment normally required. In case of insufficient ventilation wear suitable respiratory equipment.
8.2.3. Environmental exposure controls	Prevent further leakage or spillage if safe to do so.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Liquid
Colour	Clear/Amber
Odour	Mild
Odour threshold	No data available
pH	2.1 - 2.5
Melting point	No data available
Initial boiling point	No data available
Flash point	No data available
Evaporation rate	No data available
Flammability (solid, gas)	NOT-FLAMMABLE
Vapour pressure	No data available
Relative Vapour Density	No data available
Density / Relative Density	1.04 - 1.06 (H2O = 1 @ 20 °C)
Water solubility	100 g/cm³
Partition coefficient	No data available
Autoignition temperature	No data available
Viscosity	< 50 centipoise
Explosive properties	No data available
Oxidising properties	No data available
Solubility	Soluble in water

9.2. Other information

Conductivity	No data available
Surface tension	No data available
Gas group	No data available
Benzene Content	No data available
Lead content	No data available
VOC (Volatile organic compounds)	No data available

9.2.1. Information with regard to physical hazard classes

	No data is available on this product.

Vehicle Paintwork Water Spot Remover Concentrate

9.2.2. Other safety characteristics

	No data is available on this product.

SECTION 10: Stability and reactivity

10.1. Reactivity

	Stable under normal conditions.

10.2. Chemical stability

	Stable under normal conditions.

10.3. Possibility of hazardous reactions

	Strong acids. Strong oxidising agents.

10.4. Conditions to avoid

	Protect from frost. Avoid storing in direct Sun Light.

10.5. Incompatible materials

	Strong acids. Strong oxidising agents.

10.6. Hazardous decomposition products

	No Hazardous decomposition products when stored and handled correctly.

SECTION 11: Toxicological information

11.1 Information on hazard classes

	This mixture has not been tested as a whole for health effects. The health effects have been calculated using the methods outlined in Regulation (EC) No 1272/2008 (CLP).
Acute toxicity	based on available data the classification criteria are not met. Oral ATE = >2,000 mg/kg. Dermal ATE = >5,000 mg/kg. Inhalation - Dust/Mist ATE = >20 mg/l.
Skin corrosion/irritation	based on available data the classification criteria are not met.
Serious eye damage/irritation	Eye Dam. 1: H318 - Causes serious eye damage.
Respiratory or skin sensitisation	based on available data the classification criteria are not met.
Germ cell mutagenicity	based on available data the classification criteria are not met.
Carcinogenicity	based on available data the classification criteria are not met.
Reproductive toxicity	based on available data the classification criteria are not met.
STOT-single exposure	based on available data the classification criteria are not met.
STOT-repeated exposure	based on available data the classification criteria are not met.
Aspiration hazard	based on available data the classification criteria are not met.
Repeated or prolonged exposure	based on available data the classification criteria are not met.

11.1.2. Mixtures

	No data available.

11.1.3. Hazard Information

	No data available.

11.1.4. Toxicological Information

Vehicle Paintwork Water Spot Remover Concentrate

11.1.4. Toxicological Information

2,2',2"-Nitrilotriethanol	**Dermal Rat LD50:** >2000 mg/kg	**Oral Rat LD50:** 6400 mg/kg
2-butoxyethanol	**Dermal Rat LD50:** 1100 mg/kg **Inhalation Rat LC50/4 h:** 11.0 mg/l	**Oral Rat LD50:** 1300 mg/kg
C9-11 Alcohol, ethoxylated	**Dermal Rat LD50:** > 2000 mg/kg	**Oral Rat LD50 = >300 - <= 2000 mg/kg:**
Oxalic Acid	**Oral Rat LD50:** 500.0 mg/kg	**Dermal Rabbit LD50:** 1100.0 mg/kg

11.2 Information on other hazards

No data is available on this product.

SECTION 12: Ecological information

12.1. Toxicity

2,2',2"-Nitrilotriethanol	**Daphnia EC50/48h:** 2038.0000 mg/l **Fathead minnows LC50/96h:** 11800 mg/l	**Algae EC50/72h:** 512 mg/l
2-butoxyethanol	**Daphnia EC50/48h:** 1550.0000 mg/l **Rainbow trout LC50/96h:** 1474 mg/l **EC50 for marine or freshwater organisms** >100.0000 mg/l	**Algae EC50/72h:** 1840 mg/ **LC50 for marine or freshwater organisms** >100.0000 mg/l
Oxalic Acid	**Daphnia EC50/48h:** 162.2000 mg/l	**Fish LC50/96h:** 160 mg/l

12.2. Persistence and degradability

Substance biodegrades at a moderate rate and inherently biodegradable according to the OECD guide lines.

12.3. Bioaccumulative potential

The product is not bioaccumulating.

Partition coefficient

Vehicle Paintwork Water Spot Remover Concentrate	No data available	**2,2',2"-Nitrilotriethanol** -2.3 Log Pow
Oxalic Acid	-1.7 Log Pow	**2-butoxyethanol** 0.8 log P

12.4. Mobility in soil

This product is soluble in water.

12.5. Results of PBT and vPvB assessment

This substance/mixture is not classified as PBT or vPvB according to current criteria.

12.6 Endocrine disrupting properties

No data is available on this product.

12.7. Other adverse effects

No data is available on this product.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Dispose of waste and residues in accordance with local authority requirements.

General information

Dispose of in compliance with all local and national requirements.

Disposal of packaging

Do NOT reuse empty containers. Empty containers can be sent to landfill after cleaning, if in compliance with local and national regulations.

Vehicle Paintwork Water Spot Remover Concentrate

SECTION 14: Transport information

14.1. UN number

	The product is not classified as dangerous for carriage.

14.2. UN proper shipping name

	The product is not classified as dangerous for carriage.

14.3. Transport hazard class(es)

	The product is not classified as dangerous for carriage.

14.4. Packing group

	The product is not classified as dangerous for carriage.

14.5. Environmental hazards

	The product is not classified as dangerous for carriage.

14.6. Special precautions for user

	The product is not classified as dangerous for carriage.

14.7 Maritime Transport in bulk according to IMO instruments

	The product is not classified as dangerous for carriage.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulations	REGULATION (EC) No 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC. COMMISSION REGULATION (EU) No 453/2010 of 20 May 2010 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC. COMMISSION REGULATION (EU) 2020/878 of 18 June 2020 amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).

15.2. Chemical safety assessment

	No information available.

SECTION 16: Other information

Other information

Revision	This document differs from the previous version in the following areas:. 2 - Other hazards. 2 - Further information. 2 - SUPPLEMENTAL HAZARD INFORMATION. 9 - 9.2.2. Other safety characteristics. 9 - 9.2.1. Information with regard to physical hazard classes. 10 - 10.2. Chemical stability. 10 - 10.1. Reactivity. 11 - Acute toxicity. 11 - Repeated or prolonged exposure.

Vehicle Paintwork Water Spot Remover Concentrate

Revision 25
Revision date 2022-11-03

Other information

	11 - 11.2 Information on other hazards. 12 - 12.1. Toxicity. 12 - 12.6 Endocrine disrupting properties. 12 - 12.7. Other adverse effects. 15 - Regulations.
Data sources	Classification and Procedure used to derive the classification for mixtures according to Regulation (EC) No. 1272/2008, as retained and amended in UK law. Eye Dam. 1: H318 - Causes serious eye damage. - Calculation Method.
Text of Hazard Statements in Section 3	Acute Tox. 4: H302 - Harmful if swallowed. Eye Dam. 1: H318 - Causes serious eye damage. Acute Tox. 4: H302+H312 - Harmful if swallowed or in contact with skin Acute Tox. 4: H302+H312+H332 - Harmful if swallowed, in contact with skin or if inhaled Skin Irrit. 2: H315 - Causes skin irritation. Eye Irrit. 2: H319 - Causes serious eye irritation.

Further information

	The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.