

SAFETY DATA SHEET
(SUPAGARD) PETROL FUEL ADDITIVE

Page: 1
Compilation date: 24/11/2021
Revision date: 14/05/2024
Revision No: 3

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: (SUPAGARD) PETROL FUEL ADDITIVE

Product code: HC1712

Synonyms: PD0417

HC1712

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: PC13: Fuels.

1.3. Details of the supplier of the safety data sheet

Company name: SUPAGARD LIMITED

23 Gavinton Street

Muirend

Glasgow

Scotland

G44 3EF

Tel: 0141 633 5933

Email: james@supagard.co.uk

1.4. Emergency telephone number

Emergency tel: 0141 633 5933

(office hours only)

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Asp. Tox. 1: H304; Skin Irrit. 2: H315; Aquatic Chronic 3: H412

Most important adverse effects: May be fatal if swallowed and enters airways. Causes skin irritation. Harmful to aquatic life with long lasting effects.

2.2. Label elements

Label elements:

Hazard statements: H304: May be fatal if swallowed and enters airways.

H315: Causes skin irritation.

H412: Harmful to aquatic life with long lasting effects.

Hazard pictograms: GHS08: Health hazard

GHS07: Exclamation mark



[cont...]

SAFETY DATA SHEET
(SUPAGARD) PETROL FUEL ADDITIVE

Page: 2

Signal words: Danger

Precautionary statements: P102: Keep out of reach of children.
P273: Avoid release to the environment.
P302+P352: IF ON SKIN: Wash with plenty of soap and water.
P301+P310: IF SWALLOWED: Immediately call a POISON CENTER or doctor.
P331: Do NOT induce vomiting.
P405: Store locked up.
P501: Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

Haz. ingredients (label): Contains:
HYDROCARBONS, C11-C14, ISOALKANES, LOW AROMATICS; HYDROCARBONS, C9-C11, ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

HYDROCARBONS, C11-C14, ISOALKANES, LOW AROMATICS - REACH registered number(s): 01-2119456620-43-XXXX

EINECS	CAS	PBT / WEL	CLP Classification	Percent
926-141-6	64742-47-8	-	Asp. Tox. 1: H304; -: EUH066	>90%

HYDROCARBONS, C9-C11, ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS - REACH registered number(s): 01-2119463258-33-XXXX

919-857-5	1174522-20-3	-	Flam. Liq. 3: H226; STOT SE 3: H336; Asp. Tox. 1: H304; -: EUH066	1-10%
-----------	--------------	---	---	-------

1-PROPENE, 2-METHYL-HOMOPOLYMER, AMMONIUM SALT - REACH registered number(s): 1-2119475608-26-XXXX

-	337367-30-3	-	Skin Irrit. 2: H315; Aquatic Chronic 3: H412	1-10%
---	-------------	---	--	-------

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Wash immediately with plenty of soap and water.
Eye contact: Bathe the eye with running water for 15 minutes.
Ingestion: Wash out mouth with water. Do not induce vomiting. If conscious, give half a litre of water to drink immediately. Transfer to hospital as soon as possible.
Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Move to fresh air in case of accidental inhalation of vapours. Consult a doctor.

[cont...]

SAFETY DATA SHEET
(SUPAGARD) PETROL FUEL ADDITIVE

Page: 3

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be soreness and redness of the mouth and throat. There may be difficulty swallowing. Nausea and stomach pain may occur. There may be vomiting.

Inhalation: Absorption through the lungs can occur causing symptoms similar to those of ingestion.

4.3. Indication of any immediate medical attention and special treatment needed

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method. Wash the ground with an appropriate self-emulsifying solvent.

6.4. Reference to other sections

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid the formation or spread of mists in the air. Avoid direct contact with the substance.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed.

[cont...]

SAFETY DATA SHEET
(SUPAGARD) PETROL FUEL ADDITIVE

Page: 4

7.3. Specific end use(s)

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

HYDROCARBONS, C11-C14, ISOALKANES, LOW AROMATICS

Workplace exposure limits:

Respirable dust:

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	1200 mg/cm ³	-	-	-

HYDROCARBONS, C9-C11, ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS

UK	100 ppm	150 ppm	-	-
----	---------	---------	---	---

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: Respiratory protection not required.

Hand protection: Protective gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid

Colour: Pale yellow

Odour: Paraffinic

Evaporation rate: Slow

Solubility in water: Insoluble

Viscosity: Non-viscous

Boiling point/range°C: >100

Melting point/range°C: -30

Flammability limits %: lower: 0.9

upper: 4.0

Flash point°C: 60 - 93

Part.coeff. n-octanol/water: No data available.

Autoflammability°C: >200

Vapour pressure: No data available.

Relative density: 0.815

pH: No data available.

VOC g/l: No data available.

9.2. Other information

Other information: No data available.

[cont...]

SAFETY DATA SHEET
(SUPAGARD) PETROL FUEL ADDITIVE

Page: 5

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

10.4. Conditions to avoid

Conditions to avoid: Heat.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

HYDROCARBONS, C11-C14, ISOALKANES, LOW AROMATICS

DERMAL	RBT	LD50	>5000	mg/kg
ORAL	RAT	LD50	>5000	mg/kg
VAPOURS	RAT	4H LC50	>5000	mg/kg

HYDROCARBONS, C9-C11, ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS

DERMAL	RBT	LD50	>5000	mg/kg
ORAL	RAT	LD50	>5000	mg/kg
VAPOURS	RAT	4H LC50	>5000	mg/l

Relevant hazards for product:

Hazard	Route	Basis
Skin corrosion/irritation	DRM	Hazardous: calculated
Aspiration hazard	-	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be soreness and redness of the mouth and throat. There may be difficulty swallowing. Nausea and stomach pain may occur. There may be vomiting.

[cont...]

SAFETY DATA SHEET
(SUPAGARD) PETROL FUEL ADDITIVE

Page: 6

Inhalation: Absorption through the lungs can occur causing symptoms similar to those of ingestion.

Section 12: Ecological information

12.1. Toxicity

Hazardous ingredients:

HYDROCARBONS, C11-C14, ISOALKANES, LOW AROMATICS

Daphnia magna	48H EC50	>250	mg/l
RAINBOW TROUT (Oncorhynchus mykiss)	96H LC50	>1000	mg/l

HYDROCARBONS, C9-C11, ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS

ALGAE	72H IC50	>1000	mg/l
RAINBOW TROUT (Oncorhynchus mykiss)	96H LC50	>1000	mg/l

12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil. Volatile. Insoluble in water. Floats on water. Vapour is heavier than air.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Harmful to aquatic organisms.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company.

Recovery operations: Solvent reclamation/regeneration.

Waste code number: 20 01 13

Disposal of packaging: Dispose of as normal industrial waste. Arrange for collection by specialised disposal company.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

Transport class: This product does not require a classification for transport.

[cont...]

SAFETY DATA SHEET
(SUPAGARD) PETROL FUEL ADDITIVE

Page: 7

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No 2015/830.

IMPORTANT NOTE:

Risk phrases in this section below relate to the INDIVIDUAL COMPONENTS in the formulation when used at their FULL CONCENTRATIONS, and not at the reduced levels in the mixed product.

See sections 2 and 3 for the calculated hazard and risk phrases for the blended product.

Phrases used in s.2 and s.3: EUH066: Repeated exposure may cause skin dryness or cracking.

H226: Flammable liquid and vapour.

H304: May be fatal if swallowed and enters airways.

H315: Causes skin irritation.

H336: May cause drowsiness or dizziness.

H412: Harmful to aquatic life with long lasting effects.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.