(SUPAGARD) WHEEL CLEANER

Page: 1

Compilation date: 10/11/2021

Revision date: 14/05/2024

Revision No: 3

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: (SUPAGARD) WHEEL CLEANER

Product code: HC8429
Synonyms: HC8429

PD0385-5

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: Aerosol foaming cleanser.

1.3. Details of the supplier of the safety data sheet

Company name: SUPAGARD LIMITED

23 Gavinton Street

Muirend Glasgow Scotland G44 3EF

Tel: 0141 633 5933

Email: james@supagard.co.uk

1.4. Emergency telephone number

Emergency tel: 0141 633 5933

(office hours only)

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Eye Irrit. 2: H319; Flam. Aerosol 1: H222; -: H229

Most important adverse effects: Extremely flammable aerosol. Pressurised container: May burst if heated. Causes

serious eye irritation.

2.2. Label elements

Label elements:

Hazard statements: H222: Extremely flammable aerosol.

H229: Pressurised container: May burst if heated.

H319: Causes serious eye irritation.

Hazard pictograms: GHS02: Flame

GHS07: Exclamation mark





(SUPAGARD) WHEEL CLEANER

Page: 2

Signal words: Danger

Precautionary statements: P102: Keep out of reach of children.

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P211: Do not spray on an open flame or other ignition source.

P251: Do not pierce or burn, even after use.

P410+P412: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122

°F.

P260: Do not breathe spray.

P302+P350: IF ON SKIN: Gently wash with plenty of soap and water.

P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for

breathing.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

Haz. ingredients (label): Contains:

TETRAPOTASSIUM PYROPHOSPHATE

LIQUIFIED PETROLEUM GAS PROPELLANT

2.3. Other hazards

Other hazards: In use, may form flammable / explosive vapour-air mixture.

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

BUTANE, <0.1% 1,3 BUTADIENE - REACH registered number(s): 01-2119474691-32-XXXX

	EINECS	CAS	PBT / WEL	CLP Classification	Percent
2	03-448-7	106-97-8	Substance with a Community workplace exposure limit.	Flam. Gas 1: H220; Press. Gas: H280	1-10%

PROPANE, <0.1% 1,3 BUTADIENE - REACH registered number(s): 01-2119486944-21-XXXX

200-827-9	74-98-6	Substance with a Community	Flam. Gas 1: H220; Press. Gas: H280	1-10%	
		workplace exposure limit.			

BENZENE SULPHONIC ACID, 4-C10/C13-SEC-ALKYL DERIVATIVE WITH 2-PROPANAMINE - REACH registered number(s): 01-2119985163-33-XXXX

284-66-9	84961-74-0	-	Skin Irrit. 2: H315; Eye Irrit. 2: H319;	1-10%
			Aquatic Chronic 3: H412	

(SUPAGARD) WHEEL CLEANER

Page: 3

TETRAPOTASSIUM PYROPHOSPHATE - REACH registered number(s): 01-2119489369-18-XXXX

PRIMARY ALCOHOL ETHOXYLATE C9-11 6 MOLE - REACH registered number(s): 01-2119980051-45-XXXX

- 68439-46-3 - Acute Tox. 4: H302; Eye Dam. 1: H318 1-	_	68439-46-3	-	Acute Tox. 4: H302; Eye Dam. 1: H318	1-10%
--	---	------------	---	--------------------------------------	-------

TRIETHANOLAMINE - REACH registered number(s): 01-2119486482-31-XXXX

203-049-8	102-71-6	Substance with a Community	-	1-10%	
		workplace exposure limit.			

Non-classified ingredients:

2-BUTOXYETHANOL - REACH registered number(s): 01-2119475108-36-XXXX

EINECS	CAS	PBT / WEL	CLP Classification	Percent
203-905-0	111-76-2	-	Acute Tox. 4: H332; Acute Tox. 4: H312; Acute Tox. 4: H302; Eye Irrit. 2: H319;	<1%
			Skin Irrit. 2: H315	

POTASSIUM HYDROXIDE - REACH registered number(s): 01-2119487136-33-XXXX

215-181-3	1310-58-3	-	Acute Tox. 4: H302; Skin Corr. 1A:	<1%
			H314	

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash

immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Wash out mouth with water. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Move to

fresh air in case of accidental inhalation of vapours. Consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may

cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Eye bathing equipment should be available on the premises.

Section 5: Fire-fighting measures

(SUPAGARD) WHEEL CLEANER

Page: 4

5.1. Extinguishing media

Extinguishing media: Alcohol resistant foam. Water spray. Carbon dioxide. Dry chemical powder. Use water

spray to cool containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: Highly flammable. In combustion emits toxic fumes. Forms explosive air-vapour mixture.

Vapour may travel considerable distance to source of ignition and flash back. Aerosol

cans may explode during a fire, giving a high speed projectile.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact

with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. If outside do not approach from

downwind. If outside keep bystanders upwind and away from danger point. Mark out the

contaminated area with signs and prevent access to unauthorised personnel. Eliminate

all sources of ignition. Cover leaking can until the discharge has stopped, before

attempting cleanup operations.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for

disposal by an appropriate method. Do not use equipment in clean-up procedure which

may produce sparks. Wash the spillage site with large amounts of water.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area.

Do not handle in a confined space. Avoid the formation or spread of mists in the air.

Smoking is forbidden. Use non-sparking tools.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep away from sources of ignition. Keep away from

direct sunlight.

(SUPAGARD) WHEEL CLEANER

Page: 5

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

BUTANE, <0.1% 1,3 BUTADIENE

Workplace exposure limits:

Respirable dust:

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	1450 mg/m3	1810 mg/m3	-	-

PROPANE, <0.1% 1,3 BUTADIENE

UK Asphyxiating Asphyxiating -	-
--------------------------------	---

TRIETHANOLAMINE

UK	5 mg/m3 (no std.)	_	_	-
. •	og, (o ta)			

Non-classified ingredients:

2-BUTOXYETHANOL

Workplace exposure limits:

Respirable dust:

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	25 ppm	50 ppm	-	-

POTASSIUM HYDROXIDE

1.117		0 / 0		
UK	_	2 mg/m3	_	_

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area. Ensure lighting and electrical

equipment are not a source of ignition.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency.

Hand protection: Protective gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Aerosol
Colour: Colourless

Odour: Perceptible odour

(SUPAGARD) WHEEL CLEANER

Page: 6

Evaporation rate: Slow
Solubility in water: Soluble

Viscosity: Non-viscous

Boiling point/range°C: No data available. Melting point/range°C: No data available.

Flammability limits %: lower: 0.9 upper: 12.0

Flash point°C: -40 Part.coeff. n-octanol/water: No data available.

Autoflammability°C: >230 Vapour pressure: No data available.

Relative density: No data available. pH: 11-11.5

VOC g/I: No data available.

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions. Stable at room temperature.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat. Hot surfaces. Sources of ignition. Flames. Direct sunlight.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

BENZENE SULPHONIC ACID, 4-C10/C13-SEC-ALKYL DERIVATIVE WITH 2-PROPANAMINE

ORL	RAT	LD50	>2000	ma/ka
· · · =			_000	

(SUPAGARD) WHEEL CLEANER

Page: 7

TETRAPOTASSIUM PYROPHOSPHATE

OBL	DDT	1.050	. 2222	//
ORL	RBT	LD50	>2000	mg/kg

PRIMARY ALCOHOL ETHOXYLATE C9-11 6 MOLE

IHL	RAT	LC50	>5	mg/l
ORL	RAT	LD50	200-2000	mg/kg
SKN	RAT	LD50	>2000	mg/kg

TRIETHANOLAMINE

ORL	RAT	LD50	>2	g/kg
SKN	RBT	LD50	>10	g/kg

Non-classified ingredients:

2-BUTOXYETHANOL

IVN	RAT	LD50	307	mg/kg
ORL	MUS	LD50	1230	mg/kg
ORL	RAT	LD50	470	mg/kg

POTASSIUM HYDROXIDE

ORAL	RAT	LD50	333	mg/kg

Relevant hazards for product:

Hazard	Route	Basis
Serious eye damage/irritation	OPT	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may

cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

Section 12: Ecological information

12.1. Toxicity

Hazardous ingredients:

(SUPAGARD) WHEEL CLEANER

Page: 8

BENZENE SULPHONIC ACID, 4-C10/C13-SEC-ALKYL DERIVATIVE WITH 2-PROPANAMINE

ALGAE	72H ErC50	160	mg/l
Daphnia magna	48H EC50	3.7-12	mg/l
FISH	96H ErC50	1.67-6.8	mg/l

TETRAPOTASSIUM PYROPHOSPHATE

RAINBOW TROUT (Oncorhynchus mykiss)	96H LC50	100	mall
RAINBOW TROUT (Oncorhynchus mykiss)	90H LC30	100	mg/l

PRIMARY ALCOHOL ETHOXYLATE C9-11 6 MOLE

TRIETHANOLAMINE

FISH	48H EC50	1390	mg/l
FISH	96H LC50	>5000	mg/l

12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil. Volatile. Soluble in water. Vapour is heavier than air.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal

company.

Recovery operations: Recycling/reclamation of metals and metal compounds.

Waste code number: 16 05 05

Disposal of packaging: Dispose of as normal industrial waste. Empty cans must not be burned because of

explosion hazard.

NB: The user's attention is drawn to the possible existence of regional or national

regulations regarding disposal.

(SUPAGARD) WHEEL CLEANER

Page: 9

Section 14: Transport information

14.1. UN number

UN number: UN1950

14.2. UN proper shipping name

Shipping name: AEROSOLS

14.3. Transport hazard class(es)

Transport class: 2

14.4. Packing group

14.5. Environmental hazards

Environmentally hazardous: No Marine pollutant: No

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: D
Transport category: 2

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture

by the supplier.

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No

2015/830.

IMPORTANT NOTE:

Risk phases in this section below relate to the INDIVIDUAL COMPONENTS in the

formulation when used at their FULL CONCENTRATIONS, and not at the reduced levels

in the mixed product.

See sections 2 and 3 for the calculated hazard and risk phrases for the blended product.

Phrases used in s.2 and s.3: H220: Extremely flammable gas.

H222: Extremely flammable aerosol.

H229: Pressurised container: May burst if heated.

H302: Harmful if swallowed.

H312: Harmful in contact with skin.

(SUPAGARD) WHEEL CLEANER

Page: 10

H314: Causes severe skin burns and eye damage.

H315: Causes skin irritation.

H318: Causes serious eye damage.

H319: Causes serious eye irritation.

H332: Harmful if inhaled.

H412: Harmful to aquatic life with long lasting effects.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive

and shall be used only as a guide. This company shall not be held liable for any

damage resulting from handling or from contact with the above product.