(SUPAGARD) TYRE & TRIM DRESSING

Page: 1

Compilation date: 10/11/2021

Revision No: 1

# Section 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Product name: (SUPAGARD) TYRE & TRIM DRESSING

Product code: HC8433
Synonyms: HC8433

PD0432-1

# 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: Aerosol cleaner and polish.

### 1.3. Details of the supplier of the safety data sheet

Company name: SUPAGARD LIMITED

23 Gavinton Street

Muirend
Glasgow
Scotland
G44 3EF

**Tel:** 0141 633 5933

Email: james@supagard.co.uk

# 1.4. Emergency telephone number

**Emergency tel:** 0141 633 5933

(office hours only)

### **Section 2: Hazards identification**

# 2.1. Classification of the substance or mixture

Classification under CLP: Flam. Aerosol 1: H222; -: H229

Most important adverse effects: Extremely flammable aerosol. Pressurised container: May burst if heated.

# 2.2. Label elements

Label elements:

**Hazard statements:** H222: Extremely flammable aerosol.

H229: Pressurised container: May burst if heated.

Hazard pictograms: GHS02: Flame



Signal words: Danger

Precautionary statements: P102: Keep out of reach of children.

(SUPAGARD) TYRE & TRIM DRESSING

Page: 2

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P211: Do not spray on an open flame or other ignition source.

P251: Do not pierce or burn, even after use.

P410+P412: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122

°F.

P260: Do not breathe spray.

P302+P350: IF ON SKIN: Gently wash with plenty of soap and water.

P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for

breathing.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

Haz. ingredients (label): Contains:

LIQUIFIED PETROLEUM GAS PROPELLANT

### 2.3. Other hazards

Other hazards: In use, may form flammable / explosive vapour-air mixture.

PBT: This product is not identified as a PBT/vPvB substance.

# Section 3: Composition/information on ingredients

### 3.2. Mixtures

### **Hazardous ingredients:**

GLYCERINE - REACH registered number(s): EXEMPT

EINECS	CAS	PBT / WEL	CLP Classification	Percent
200-289-5	56-81-5	Substance with a Community workplace exposure limit.	-	10-30%

# BUTANE, <0.1% 1,3 BUTADIENE - REACH registered number(s): 01-2119474691-32-XXXX

203-448-7	106-97-8	Substance with a Community	Flam. Gas 1: H220; Press. Gas: H280	1-10%	
		workplace exposure limit.			

### PROPANE, <0.1% 1,3 BUTADIENE - REACH registered number(s): 01-2119486944-21-XXXX

200-827-9	74-98-6	Substance with a Community	Flam. Gas 1: H220; Press. Gas: H280	1-10%
		workplace exposure limit.		

# PROPAN-2-OL - REACH registered number(s): 01-2119457558-25

200-661-7	67-63-0	-	Flam. Liq. 2: H225; Eye Irrit. 2: H319;	1-10%
			STOT SE 3: H336	

(SUPAGARD) TYRE & TRIM DRESSING

Page: 3

### Non-classified ingredients:

TRIETHANOLAMINE - REACH registered number(s): 01-2119486482-31-XXXX

EINECS	CAS	PBT / WEL	CLP Classification	Percent
203-049-8	102-71-6	-	-	<1%

#### Section 4: First aid measures

### 4.1. Description of first aid measures

**Skin contact:** Wash immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Do not induce vomiting. If conscious, give half a litre of water to drink immediately.

Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a

doctor. Move to fresh air in case of accidental inhalation of vapours.

### 4.2. Most important symptoms and effects, both acute and delayed

**Skin contact:** There may be mild irritation at the site of contact.

**Eye contact:** There may be irritation and redness. **Ingestion:** There may be irritation of the throat.

**Inhalation:** There may be a feeling of tightness in the chest with shortness of breath.

# 4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Not applicable.

## Section 5: Fire-fighting measures

# 5.1. Extinguishing media

Extinguishing media: Alcohol resistant foam. Water spray. Carbon dioxide. Dry chemical powder.

#### 5.2. Special hazards arising from the substance or mixture

Exposure hazards: Highly flammable. In combustion emits toxic fumes. Forms explosive air-vapour mixture.

Vapour may travel considerable distance to source of ignition and flash back. Aerosol

cans may explode during a fire, giving a high speed projectile.

# 5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact

with skin and eyes.

### Section 6: Accidental release measures

## 6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. Notify the police and fire

brigade immediately. Eliminate all sources of ignition. Cover leaking can until the discharge has stopped, before attempting cleanup operations. Spillage will create

slippery surface.

(SUPAGARD) TYRE & TRIM DRESSING

Page: 4

### 6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

## 6.3. Methods and material for containment and cleaning up

Clean-up procedures: Do not use equipment in clean-up procedure which may produce sparks. Absorb into dry

earth or sand. Clean-up should be dealt with only by qualified personnel familiar with the

specific substance. Wash the spillage site with large amounts of water.

### 6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

## Section 7: Handling and storage

# 7.1. Precautions for safe handling

Handling requirements: Smoking is forbidden. Use non-sparking tools. Ensure there is sufficient ventilation of

the area. Do not handle in a confined space. Avoid the formation or spread of mists in

the air.

## 7.2. Conditions for safe storage, including any incompatibilities

**Storage conditions:** Store in a cool, well ventilated area. Keep away from sources of ignition. Keep away from direct sunlight.

### 7.3. Specific end use(s)

Specific end use(s): No data available.

# Section 8: Exposure controls/personal protection

# 8.1. Control parameters

# Hazardous ingredients:

# **GLYCERINE**

### Workplace exposure limits:

### Respirable dust:

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	not determined	-	-	-

### **BUTANE, <0.1% 1,3 BUTADIENE**

UK   1450 mg/m3   1610 mg/m3   -	UK	1450 mg/m3	1810 mg/m3	-	-
----------------------------------	----	------------	------------	---	---

# PROPANE, <0.1% 1,3 BUTADIENE

UK Asphyxiating Asphyxiating	-		-
------------------------------	---	--	---

# **PROPAN-2-OL**

UK	400 ppm	500 ppm	-	-
----	---------	---------	---	---

(SUPAGARD) TYRE & TRIM DRESSING

Page: 5

### Non-classified ingredients:

#### **TRIETHANOLAMINE**

# Workplace exposure limits:

### Respirable dust:

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	5 mg/m3 (no std.)	-	-	-

### **DNEL/PNEC Values**

**DNEL / PNEC** No data available.

## 8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area. Ensure lighting and electrical

equipment are not a source of ignition.

Respiratory protection: Respiratory protection not required.

Hand protection: Protective gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing.

### Section 9: Physical and chemical properties

# 9.1. Information on basic physical and chemical properties

State: Aerosol

Colour: Colourless

Odour: Perceptible odour

Evaporation rate: Slow

Solubility in water: Soluble

Viscosity: Non-viscous

Boiling point/range°C: No data available. Melting point/range°C: No data available.

Flammability limits %: lower: 0.9 upper: 9.0

Flash point°C: -40 Part.coeff. n-octanol/water: No data available.

Autoflammability°C: >230 Vapour pressure: No data available.

**Relative density:** No data available. **pH:** 9 - 10

VOC g/I: No data available.

### 9.2. Other information

Other information: No data available.

# Section 10: Stability and reactivity

# 10.1. Reactivity

**Reactivity:** Stable under recommended transport or storage conditions.

(SUPAGARD) TYRE & TRIM DRESSING

Page: 6

# 10.2. Chemical stability

Chemical stability: Stable under normal conditions. Stable at room temperature.

# 10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

## 10.4. Conditions to avoid

Conditions to avoid: Heat. Hot surfaces. Sources of ignition. Flames. Direct sunlight.

#### 10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

### 10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

# **Section 11: Toxicological information**

# 11.1. Information on toxicological effects

# **Hazardous ingredients:**

### **GLYCERINE**

ORL		RAT	LD50	>2000	mg/Kg
-----	--	-----	------	-------	-------

#### PROPAN-2-OL

ORAL	RAT	LD50	4700	mg/kg
ORAL	RBT	LD50	>2000	mg/kg
VAPOURS	RAT	4H LC50	46.5	mg/l

# Non-classified ingredients:

## **TRIETHANOLAMINE**

ORL	RAT	LD50	>2	g/kg
SKN	RBT	LD50	>10	g/kg

Toxicity values: No data available.

# Symptoms / routes of exposure

**Skin contact:** There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.Ingestion: There may be irritation of the throat.

**Inhalation:** There may be a feeling of tightness in the chest with shortness of breath.

## **Section 12: Ecological information**

(SUPAGARD) TYRE & TRIM DRESSING

Page: 7

## 12.1. Toxicity

#### Hazardous ingredients:

### **GLYCERINE**

Not specified	96H LC50	>1000	ma/ka
· ·			J 3

### **PROPAN-2-OL**

Daphnia magna	48H EC50	>100	mg/l
FISH	48H EC50	>100	mg/l

#### **TRIETHANOLAMINE**

FISH	48H EC50	1390	mg/l
FISH	96H LC50	>5000	mg/l

## 12.2. Persistence and degradability

Persistence and degradability: Biodegradable. The surfactant(s) contained in this preparation complies (comply) with

the biodegradability criteria as laid down in Regulation (EC) No. 648/2004 on

detergents.

# 12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

# 12.4. Mobility in soil

Mobility: Readily absorbed into soil. Volatile. Soluble in water.

### 12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

### 12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

## Section 13: Disposal considerations

# 13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal

company.

**Recovery operations:** Recycling/reclamation of metals and metal compounds.

Waste code number: 16 05 05

**Disposal of packaging:** Dispose of as normal industrial waste. Clean with water.

NB: The user's attention is drawn to the possible existence of regional or national

regulations regarding disposal.

(SUPAGARD) TYRE & TRIM DRESSING

Page: 8

### **Section 14: Transport information**

#### 14.1. UN number

UN number: UN1950

### 14.2. UN proper shipping name

Shipping name: AEROSOLS

### 14.3. Transport hazard class(es)

Transport class: 2

### 14.4. Packing group

#### 14.5. Environmental hazards

Environmentally hazardous: No Marine pollutant: No

## 14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: D
Transport category: 2

## **Section 15: Regulatory information**

# 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

## 15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture

by the supplier.

# **Section 16: Other information**

#### Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No

2015/830.

IMPORTANT NOTE:

Risk phases in this section below relate to the INDIVIDUAL COMPONENTS in the

formulation when used at their FULL CONCENTRATIONS, and not at the reduced levels

in the mixed product.

See sections 2 and 3 for the calculated hazard and risk phrases for the blended product.

Phrases used in s.2 and s.3: H220: Extremely flammable gas.

H222: Extremely flammable aerosol.

H225: Highly flammable liquid and vapour.

H229: Pressurised container: May burst if heated.

H319: Causes serious eye irritation.

H336: May cause drowsiness or dizziness.

(SUPAGARD) TYRE & TRIM DRESSING

Page: 9

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive

and shall be used only as a guide. This company shall not be held liable for any

damage resulting from handling or from contact with the above product.