



SAFETY DATA SHEET

according to Regulation (EU) 2020/878

Page 1/9

Supagard Tyre and Trim Dressing

Revision 10
Revision date 2022-11-21

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name	Supagard Tyre and Trim Dressing
--------------	---------------------------------

1.2. Relevant identified uses of the substance or mixture and uses advised against

Product Use	[SU22] Professional uses: Public domain (administration, education, entertainment, services, craftsmen); [PC35] Washing and cleaning products (including solvent based products); ----- [SU21] Consumer uses: Private households (= general public = consumers); [PC35] Washing and cleaning products (including solvent based products);
Description	This new water resistant coating has been carefully formulated for the renovation of all plastics, PVC, rubber etc, throughout your vehicle.

1.3. Details of the supplier of the safety data sheet

Company	SUPAGARD LIMITED
Address	19-27 Gavinton Street Muirend Glasgow G44 3EF
Web	www.supagard.com
Telephone	0141 633 5933
Fax	01416377219
Email	James.Smyth@supagard.com
Email address of the competent person	James.Smyth@supagard.com

1.4. Emergency telephone number

Emergency telephone number	01416335933 8.30am to 5.00pm For medical advice or information you should contact your GP or NHS 111 (or NHS 24 in Scotland) on 111 (for 24 hour health advice) If you are a healthcare professional with an enquiry please visit www.TOXBASE.org
----------------------------	---

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

2.1.2. Classification - EC 1272/2008	Flam. Liq. 3: H226; Asp. Tox. 1: H304; STOT SE 3: H336;
--------------------------------------	---


2.2. Label elements

Supagard Tyre and Trim Dressing

Revision 10

Revision date 2022-11-21

2.2. Label elements

Hazard pictograms	
Signal Word	Danger
Hazard Statement	Flam. Liq. 3: H226 - Flammable liquid and vapour. Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways. STOT SE 3: H336 - May cause drowsiness or dizziness.
Precautionary Statement: Prevention	P102 - Keep out of reach of children. P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Precautionary Statement: Response	P301+P310+P330+P331 - IF SWALLOWED: Immediately call a POISON CENTER/doctor. Rinse mouth. Do NOT induce vomiting. P302+P350 - IF ON SKIN: Gently wash with plenty of soap and water. P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.
Precautionary Statement: Storage	P403+P233 - Store in a well-ventilated place. Keep container tightly closed.
SUPPLEMENTAL HAZARD INFORMATION	Ingredients as required by Regulation (EC) No 648/2004: Less than 5% Aromatic Hydrocarbons, Dimethicone, Amino functional silicone. Contains - Hydrocarbons, C9-11, N-alkanes, Isoalkanes, Cyclics, <2% Aromatic.

2.3. Other hazards

Other hazards	This substance/mixture is not classified as PBT or vPvB according to current criteria. The substance/mixture does not contain substances with endocrine disrupting properties.
---------------	--

Further information

	RECOMMENDED SHELF LIFE 1 YEAR FROM DATE OF DELIVERY.
--	--

SECTION 3: Composition/information on ingredients

3.2. Mixtures

EC 1272/2008

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification
Hydrocarbons, C9-11, N-alkanes, Isoalkanes, Cyclics, <2% Aromatic		1174522-20-3	919-857-5	01-2119463258-33	50 - 60%	: EUH066; Flam. Liq. 3: H226; Asp. Tox. 1: H304; STOT SE 3: H336;

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	Move the exposed person to fresh air.
Eye contact	Rinse immediately with plenty of water. Contact lenses should be removed.
Skin contact	Remove contaminated clothing. Wash with water and soap as a precaution.
Ingestion	DO NOT INDUCE VOMITING. If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label. Rinse mouth thoroughly.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation	High concentration of vapour in enclosed space may cause irritation, headaches and nausea. May cause irritation to respiratory system.
Eye contact	Irritating to eyes.
Skin contact	May cause skin dryness and irritation. Prolonged contact may cause defatting of the skin.
Ingestion	Harmful if ingested or swallowed.

Supagard Tyre and Trim Dressing

Revision 10

Revision date 2022-11-21

4.3. Indication of any immediate medical attention and special treatment needed

Inhalation	TREAT SYMPTOMATICALLY. Move the exposed person to fresh air. Seek medical attention if irritation or symptoms persist.
Eye contact	Contact lenses should be removed. Rinse immediately with plenty of water. Seek medical attention if irritation or symptoms persist.
Skin contact	Seek medical attention if irritation or symptoms persist.
Ingestion	Drink 1 to 2 glasses of water. Seek medical attention if irritation or symptoms persist.

General information

	If you feel unwell, seek medical advice (show the label where possible). Treat symptomatically.
--	---

SECTION 5: Firefighting measures**5.1. Extinguishing media**

	Flammable liquid. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
--	---

5.2. Special hazards arising from the substance or mixture

	Burning produces irritating, toxic and obnoxious fumes.
--	---

5.3. Advice for firefighters

	Fire fighters should wear self contained positive pressure breathing apparatus (SCBA) and full turnout gear.
--	--

Further information

	In the event of a fire and/or explosion do not breath fumes. Standard procedure for chemical fires. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
--	---

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

	Wear suitable protective equipment. Flammable liquid. Avoid sparks, flames, heat and sources of ignition.
--	---

6.2. Environmental precautions

	Advise local authorities if large spills cannot be contained.
--	---

6.3. Methods and material for containment and cleaning up

	Absorb with inert, absorbent material. Sweep up. Transfer to suitable, labelled containers for disposal. Avoid sparks, flames, heat and sources of ignition.
--	--

6.4. Reference to other sections

	See section 2, 7, 8, 13 for further information.
--	--

SECTION 7: Handling and storage**7.1. Precautions for safe handling**

	Adopt best Manual Handling considerations when handling, carrying and dispensing.
--	---

7.2. Conditions for safe storage, including any incompatibilities

	Flammable liquid. Avoid sparks, flames, heat and sources of ignition. Avoid storing in direct Sun Light. Store in a well-ventilated place. Keep cool. Store in original container. Keep container tightly closed. Keep away from combustible material. Keep out of the reach of children.
--	---

7.3. Specific end use(s)

	This new water resistant coating has been carefully formulated for the renovation of all plastics, PVC, rubber etc. throughout your vehicle.
--	--

Suitable packaging

Supagard Tyre and Trim Dressing

Revision 10
Revision date 2022-11-21

Suitable packaging

Plastic containers.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure controls.

8.1.1. Exposure Limit Values

methanol	WEL 8-hr limit ppm: 200	WEL 8-hr limit mg/m ³ : 266
	WEL 15 min limit ppm: 250	WEL 15 min limit mg/m ³ : 333
	WEL 8-hr limit mg/m ³ total inhalable dust: -	WEL 15 min limit mg/m ³ total inhalable dust: -
	WEL 8-hr limit mg/m ³ total respirable dust: -	WEL 15 min limit mg/m ³ total respirable dust: -
propan-2-ol	WEL 8-hr limit ppm: 400	WEL 8-hr limit mg/m ³ : 999
	WEL 15 min limit ppm: 500	WEL 15 min limit mg/m ³ : 1250
	WEL 8-hr limit mg/m ³ total inhalable dust: -	WEL 15 min limit mg/m ³ total inhalable dust: -
	WEL 8-hr limit mg/m ³ total respirable dust: -	WEL 15 min limit mg/m ³ total respirable dust: -

DNEL: Derived no-effect level.

Exposure Pattern - Workers

methanol	Acute inhalation - Systemic effects	130 mg/m ³	
	Acute inhalation - Local effects	130 mg/m ³	Acute dermal - Systemic effects
	Long-term - inhalation - Systemic effects	130 mg/m ³	Long-term - inhalation - Local effects
	Long-term - dermal - Systemic effects	20 mg/kg	
propan-2-ol	Long-term - inhalation - Systemic effects	500 mg/m ³	
	Long-term - dermal - Systemic effects	888 mg/kg	

Exposure Pattern - General population


methanol	Acute inhalation - Systemic effects	26 mg/m ³	
	Acute inhalation - Local effects	26 mg/m ³	Acute dermal - Systemic effects
	Acute oral - Systemic effects	5 mg/kg	Long-term - inhalation - Systemic effects
	Long-term - inhalation - Local effects	26 mg/m ³	Long-term - dermal - Systemic effects
	Long-term - oral - Systemic effects	5 mg/kg	
propan-2-ol	Long-term - inhalation - Systemic effects	89 mg/m ³	
	Long-term - dermal - Systemic effects	319 mg/kg	Long-term - oral - Systemic effects

8.2. Exposure controls

Supagard Tyre and Trim Dressing

Revision 10
Revision date 2022-11-21

8.2. Exposure controls

		
	Adopt best Manual Handling considerations when handling, carrying and dispensing. Avoid contact with skin and eyes. Handle in accordance with good industrial hygiene and safety practice. Use appropriate personal protective equipment. Wear suitable protective clothing and eye/face protection.	
	8.2.1. Appropriate engineering controls	Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapours below their respective threshold limit value. Ensure eyewash stations and safety showers are close to the workstation location.
	Eye / face protection	Avoid contact with eyes. If splashes are likely to occur, wear: safety glasses with side-shields.
	Skin protection - Handprotection	Rubber gloves.
Respiratory protection	No personal respiratory protective equipment normally required. In case of insufficient ventilation wear suitable respiratory equipment.	
8.2.3. Environmental exposure controls	Prevent further leakage or spillage if safe to do so.	

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Liquid
Colour	Colourless
Odour	Characteristic
Odour threshold	No data available
pH	No data available
Melting point	No data available
Initial boiling point	No data available
Flash point	40 °C
Evaporation rate	No data available
Flammability (solid, gas)	No data available
Vapour pressure	No data available
Relative Vapour Density	No data available
Density / Relative Density	0.8 - 0.825
Partition coefficient	No data available
Autoignition temperature	No data available
Viscosity	No data available
Explosive properties	No data available
Oxidising properties	No data available
Solubility	No data available

9.2. Other information

Conductivity	No data available
Surface tension	No data available
Gas group	No data available
Benzene Content	No data available
Lead content	No data available
VOC (Volatile organic compounds)	No data available

9.2.1. Information with regard to physical hazard classes

Supagard Tyre and Trim Dressing

Revision 10
Revision date 2022-11-21

9.2.1. Information with regard to physical hazard classes

No data is available on this product.

9.2.2. Other safety characteristics

No data is available on this product.

SECTION 10: Stability and reactivity

10.1. Reactivity

Flammable liquid. Stable under normal conditions.

10.2. Chemical stability

Flammable liquid. Stable under normal conditions.

10.3. Possibility of hazardous reactions

Oxidising agents. Combustible materials.

10.4. Conditions to avoid

Avoid sparks, flames, heat and sources of ignition. Avoid storing in direct Sun Light.

10.5. Incompatible materials

Oxidising agents.

10.6. Hazardous decomposition products

No Hazardous decomposition products when stored and handled correctly.

SECTION 11: Toxicological information

11.1 Information on hazard classes

Acute toxicity	This mixture has not been tested as a whole for health effects. The health effects have been calculated from raw material supplier LD50 and Acute Toxicity Estimates (ATE) as outlined in the Regulation (EC) No. 1272/2008 (CLP) as amended by UK law.
	based on available data the classification criteria are not met. Oral ATE = >10,000 mg/kg. Dermal ATE = >10,000 mg/kg. Inhalation - Dust/Mist ATE = >10,000 mg/l.
Skin corrosion/irritation	based on available data the classification criteria are not met.
Serious eye damage/irritation	based on available data the classification criteria are not met.
Respiratory or skin sensitisation	based on available data the classification criteria are not met.
Germ cell mutagenicity	based on available data the classification criteria are not met.
Carcinogenicity	based on available data the classification criteria are not met.
Reproductive toxicity	based on available data the classification criteria are not met.
STOT-single exposure	STOT SE category 3. H336 - May cause drowsiness or dizziness.
STOT-repeated exposure	based on available data the classification criteria are not met.
Aspiration hazard	Aspiration Hazard Category 1. H304 - May be fatal if swallowed and enters airways.
Repeated or prolonged exposure	Prolonged contact may cause defatting of the skin.

11.1.2. Mixtures

No data available.

11.1.3. Hazard Information

No data available.

11.1.4. Toxicological Information

Supagard Tyre and Trim Dressing

Revision 10

Revision date 2022-11-21

11.1.4. Toxicological Information

methanol	Oral Rat LD50: 50 - 300.0 mg/kg Inhalation Rat LC50/4 h: 10 - 20 mg/l	Dermal Rabbit LD50: 1000 - 2000 mg/kg
propan-2-ol	Inhalation Rat LC50/6 h: >10000ppm Dermal Rabbit LD50: 12800 mg/kg	Oral Rat LD50: 5840 mg/kg

11.2 Information on other hazards

No data is available on this product.

SECTION 12: Ecological information

12.1. Toxicity

methanol	Daphnia EC50/48h: 18260.0000 mg/l Fathead minnows LC50/96h: >100 mg/l Lepomis_Macrochirus LC50/96h: 15400 mg/l	Green algae EC50/96h: 22000.0 mg/l Bluegill sunfish LC50/96h: 15400.0 mg/l
octamethylcyclotetrasiloxane	NOEC / EC10 for marine or freshwater organisms: 0.0044 mg/l	
propan-2-ol	Daphnia EC50/48h: 10000.0000 mg/l	Fathead minnows LC50/96h: 9640 mg/l

12.2. Persistence and degradability

Substance biodegrades at a moderate rate and inherently biodegradable according to the OECD guide lines.

12.3. Bioaccumulative potential

The product is not bioaccumulating.

Partition coefficient

	Supagard Tyre and Trim Dressing methanol -0.74 Log Pow	propan-2-ol 0.05 log P
--	---	------------------------

12.4. Mobility in soil

Immiscible in water.

12.5. Results of PBT and vPvB assessment

This substance/mixture is not classified as PBT or vPvB according to current criteria.

12.6 Endocrine disrupting properties

No data is available on this product.

12.7. Other adverse effects

No data is available on this product.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Dispose of waste and residues in accordance with local authority requirements.

General information

Dispose of in compliance with all local and national requirements.

Disposal of packaging

Do NOT reuse empty containers. Empty containers can be sent to landfill after cleaning, if in compliance with local and national regulations.

SECTION 14: Transport information

Supagard Tyre and Trim Dressing

Revision 10
Revision date 2022-11-21

Hazard pictograms

	
--	---

14.1. UN number

	UN3295
--	--------

14.2. UN proper shipping name

	HYDROCARBONS, LIQUID, N.O.S. (HYDROCARBONS, C9 - C11, n-alkanes, isoalkanes, cyclics, <2% aromatics.)
--	---

14.3. Transport hazard class(es)

ADR/RID	3
Subsidiary risk	-
IMDG	3
Subsidiary risk	-
IATA	3
Subsidiary risk	-

14.4. Packing group

Packing group	III
---------------	-----

14.5. Environmental hazards

Environmental hazards	No
Marine pollutant	No

14.6. Special precautions for user

	No additional special precautions.
--	------------------------------------

14.7 Maritime Transport in bulk according to IMO instruments

	Not applicable.
--	-----------------

ADR/RID

Hazard ID	30
Tunnel Category	(D/E)

IMDG

EmS Code	F-E S-D
----------	---------

IATA

Packing Instruction (Cargo)	366
Maximum quantity	220 L
Packing Instruction (Passenger)	355
Maximum quantity	60 L

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulations	REGULATION (EC) No 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC. As retained and amended in UK law.
-------------	--

Supagard Tyre and Trim Dressing

Revision 10

Revision date 2022-11-21

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

COMMISSION REGULATION (EU) No 453/2010 of 20 May 2010 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC. As retained and amended in UK law.

COMMISSION REGULATION (EU) 2020/878 of 18 June 2020 amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH). As retained and amended in UK law.

15.2. Chemical safety assessment

No information available.

SECTION 16: Other information

Other information

Revision	<p>This document differs from the previous version in the following areas:.</p> <ul style="list-style-type: none"> 2 - Other hazards. 2 - Precautionary Statement: Prevention. 2 - Precautionary Statement: Response. 2 - Precautionary Statement: Storage. 2 - Precautionary Statement: Disposal. 2 - Further information. 2 - SUPPLEMENTAL HAZARD INFORMATION. 9 - 9.2.2. Other safety characteristics. 9 - 9.2.1. Information with regard to physical hazard classes. 11 - 11.2 Information on other hazards. 12 - 12.6 Endocrine disrupting properties. 12 - 12.7. Other adverse effects. 15 - Regulations.
Data sources	<p>Classification and Procedure used to derive the classification for mixtures according to Regulation (EC) No. 1272/2008, as retained and amended in UK law.</p> <p>Flam. Liq. 3: H226 - Flammable liquid and vapour. - Flash Point - 40 degC.</p> <p>Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways. - Calculation Method.</p> <p>STOT SE 3: H336 - May cause drowsiness or dizziness. - Calculation Method.</p>
Text of Hazard Statements in Section 3	<p>EUH066 - Repeated exposure may cause skin dryness or cracking.</p> <p>Flam. Liq. 3: H226 - Flammable liquid and vapour.</p> <p>Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways.</p> <p>STOT SE 3: H336 - May cause drowsiness or dizziness.</p>

Further information

The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.