

SAFETY DATA SHEET

according to Regulation (EU) 2020/878

Page 1/10

Wheel Cleaner

Revision 11

Revision date 2022-11-17

SECTION 1: Identification of	the substance/mixture and of the company/undertaking
1.1. Product identifier	
Product name	Wheel Cleaner
1.2. Relevant identified uses of t	he substance or mixture and uses advised against
Product Use	[SU21] Consumer uses: Private households (= general public = consumers); [PC35] Washing and cleaning products (including solvent based products);
	[SU22] Professional uses: Public domain (administration, education, entertainment, services, craftsmen); [PC35] Washing and cleaning products (including solvent based products);
Description	Removes stubborn marks left be brake dust and road grime without damaging coatings, lacquers or tyres.
1.3. Details of the supplier of the	e safety data sheet
Company	SUPAGARD LIMITED
Address	19-27 Gavinton Street Muirend Glasgow G44 3EF
Web	www.supagard.com
Telephone	0141 633 5933
Fax	01416377219
Email	James.Smyth@supagard.com
Email address of the competent person	James.Smyth@supagard.com
1.4. Emergency telephone numb	Der
Emergency telephone number	01416335933
	8.30am to 5.00pm
	For medical advice or information you should contact your GP or NHS 111 (or NHS 24 in Scotland) on 111 (for 24 hour health advice)
	If you are a healthcare professional with an enquiry please visit www.TOXBASE.org
SECTION 2: Hazards identif	ication
2.1. Classification of the substar	nce or mixture
2.1.2. Classification - EC	Skin Corr. 1A: H314;

Powered by ChemSoft EH&S

1272/2008

2.2. Label elements

Copyright © 2022 ChemSoft. All rights reserved.

Revision 11 Revision date 2022-11-17

2.2. Label elements

Hazard pictograms	
Signal Word	Danger
Hazard Statement	Skin Corr. 1A: H314 - Causes severe skin burns and eye damage.
Precautionary Statement:	P102 - Keep out of reach of children.
Prevention	P260 - Do not breathe dust/fume/gas/mist/vapours/spray.
	P264 - Wash hands and other contacted skin thoroughly after handling.
Precautionary Statement:	P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse
Response	skin with water/shower.
	P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Precautionary Statement:	P501 - Dispose of contents/container to an approved disposal site, in accordance with local
Disposal	regulations.
SUPPLEMENTAL HAZARD	Ingredients as required by Regulation (EC) No 648/2004:.
INFORMATION	3.8% Phosphates by weight, 5 - 15% Anionic Surfactants, Less than 5% Non-ionic surfactants,
	Sodium Metasilicate Pentahydrate.
	Contains - C9-11 Alcohol, ethoxylated, sodium (xylene and 4-ethylbenzene) sulfonate,

2.3. Other hazards			
Other hazards	This substance/mixture is not classified as PBT or vPvB according to current criteria. The substance/mixture does not contain substances with endocrine disrupting properties.		
Further information			
	RECOMMENDED SHELF LIFE 1 YEAR FROM DATE OF DELIVERY.		

Tetrapotassium pyrophosphate, 2-butoxyethanol, sodium metasilicate pentahydrate.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

EC 1272/2008

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification
C9-11 Alcohol, ethoxylated		68439-45-2			1 - 10%	Acute Tox. 4: H302; Eye Dam. 1: H318;
sodium (xylenes and 4-ethylbenzene) sulfonate			701-037-1	01-2119513350-56	1 - 10%	Eye Irrit. 2: H319;
Tetrapotassium pyrophosphate		7320-34-5	230-785-7	01-2119489369-18	1 - 10%	Eye Irrit. 2: H319;
2-butoxyethanol	603-014-00-0	111-76-2	203-905-0	01-2119475108-36	1 - 10%	Acute Tox. 4: H332; Acute Tox. 4: H312; Acute Tox. 4: H302; Eye Irrit. 2: H319; Skin Irrit. 2: H315;
Sodium Metasilicate Pentahydrate		10213-79-3	229-912-9	01-2119449811-37	1 - 10%	Met. Corr. 1: H290; Skin Corr. 1B: H314; STOT SE 3: H335;

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	Move the exposed person to fresh air.
Eye contact	Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Contact lenses should be removed.
Skin contact	Remove contaminated clothing. Wash off immediately with plenty of soap and water.
Ingestion	DO NOT INDUCE VOMITING. Rinse mouth thoroughly. Drink plenty of water to dilute ingested product.

Revision 11 Revision date 2022-11-17

	Revision date 2022-11-17	
4.2. Most important symptom	s and effects, both acute and delayed	
Inhalation	May cause irritation to respiratory system.	
Eye contact	Risk of serious damage to eyes. Causes serious eye damage.	
Skin contact	Causes severe burns.	
Ingestion	May cause irritation to mucous membranes.	
4.3. Indication of any immedia	ate medical attention and special treatment needed	
Inhalation	Move the exposed person to fresh air. In case of accident or if you feel unwell, seek medical	
	advice immediately (show the label where possible). Seek medical attention. Show this safety data	
	sheet to the doctor in attendance.	
Eye contact	Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Contact lenses	
	should be removed. Seek medical attention. Show this safety data sheet to the doctor in	
	attendance.	
Skin contact	Remove contaminated clothing immediately. Rinse immediately with plenty of water. Seek medical attention. Show this safety data sheet to the doctor in attendance.	
Ingestion	Drink 1 to 2 glasses of water. Seek medical attention. Show this safety data sheet to the doctor in	
ingoodon	attendance.	
General information		
	If you feel unwell, seek medical advice (show the label where possible). Treat symptomatically.	
SECTION 5: Firefighting n	neasures	
5.1. Extinguishing media		
	This product is not flammable. Use fire-extinguishing media appropriate for surrounding materials.	
5.2. Special hazards arising fi		
	Burning produces irritating, toxic and obnoxious fumes.	
5.3. Advice for firefighters	Burning produces irritating, toxic and obnoxious furnes.	
5.5. Advice for illeligities	F: 5 1 1 15 15 15 15 15 1	
	Fire fighters should wear self contained positive pressure breathing apparatus (SCBA) and full turnout gear.	
Further information		
	In the event of a fire and/or explosion do not breath fumes. Standard procedure for chemical fires.	
	Use extinguishing measures that are appropriate to local circumstances and the surrounding	
	environment.	
SECTION 6: Accidental re		
6.1. Personal precautions, pre	otective equipment and emergency procedures	
	Wear suitable protective equipment.	
6.2. Environmental precaution	ns	
	Advise local authorities if large spills cannot be contained.	
6.3. Methods and material for	containment and cleaning up	
	For large spills:. Absorb with inert, absorbent material. Sweep up. Transfer to suitable, labelled	
	containers for disposal. Clean spillage area thoroughly with plenty of water. For small spills:. Flush down the drain with plenty of water.	
6.4. Reference to other section	ons	
	See section 2, 7, 8, 13 for further information.	
SECTION 7: Handling and	I storage	
7.1. Precautions for safe hand		

Avoid contact with eyes and skin. Do not breathe vapours or spray mist. Adopt best Manual

Handling considerations when handling, carrying and dispensing.

Revision 11
Revision date 2022-11-17

respirable dust:

7.2. Conditions for safe storage	, including any incompatibilities		
	Store in a cool, dry area. Keep container tightly closed. Keep out of the reach of children. Store in original container.		
7.3. Specific end use(s)			
	Removes stubborn marks left be brake dust and road grime without damaging coatings, lacquers or tyres.		
Suitable packaging			
	Plastic containers.		
SECTION 8: Exposure contr	rols/personal protection		
8.1. Control parameters			
	Occupational exposure controls.		
8.1.1. Exposure Limit Values			
2-butoxyethanol	WEL 8-hr limit ppm: 25	WEL 8-hr limit mg/m3: 123	
	WEL 15 min limit ppm: 50	WEL 15 min limit mg/m3: 101.2	
	WEL 8-hr limit mg/m3 total -	WEL 15 min limit mg/m3 total -	
	inhalable dust:	inhalable dust:	
	WEL 8-hr limit mg/m3 total -	WEL 15 min limit mg/m3 total -	

respirable dust:

DNEL: Derived no-effect level.

Exposure Pattern - Workers

2-butoxyethanol	Acute inhalation - Systemic effects	1091 mg/m³	
	Acute inhalation - Local effects	246 mg/m³	Acute dermal - Systemic effects 89 mg/kg
	Long-term - inhalation - Systemic	98 mg/m³	Long-term - dermal - Systemic 125 mg/kg
	effects		effects
sodium (xylenes and	Long-term - inhalation - Systemic	26.9 mg/m³	
4-ethylbenzene) sulfonate	effects		
	Long-term - dermal - Systemic	136.25 mg/kg	
	effects		
Sodium Metasilicate	Long-term - inhalation - Systemic	6.22 mg/m³	
Pentahydrate	effects		
	Long-term - dermal - Systemic	1.49 mg/kg	
	effects		

Exposure Pattern - General population

Revision 11
Revision date 2022-11-17

Exposure Pattern - General population

2-butoxyethanol	Acute inhalation - Systemic effects	426 mg/m³	
	Acute dermal - Systemic effects	89 mg/kg	Acute oral - Systemic effects 26.7 mg/kg
	Long-term - inhalation - Systemic effects	59 mg/m³	Long-term - inhalation - Local 147 mg/m³ effects
	Long-term - dermal - Systemic effects	75 mg/kg	Long-term - oral - Systemic effects 6.3 mg/kg
sodium (xylenes and	Long-term - inhalation - Systemic	6.6 mg/m³	
4-ethylbenzene) sulfonate	effects		
	Long-term - dermal - Systemic	68.1 mg/kg	Long-term - dermal - Local effects 0.048 mg/cm ³
	effects		
	Long-term - oral - Systemic	3.8 mg/kg	
	effects		
Sodium Metasilicate	Long-term - inhalation - Systemic	1.55 mg/m³	
Pentahydrate	effects		
	Long-term - dermal - Systemic	0.74 mg/kg	Long-term - oral - Systemic effects 0.74 mg/kg
	effects		

8.2. Exposure controls







Adopt best Manual Handling considerations when handling, carrying and dispensing. Avoid contact with skin and eyes. Handle in accordance with good industrial hygiene and safety practice. Use appropriate personal protective equipment. Wear suitable protective clothing and eye/face protection.

8.2.1. Appropriate engineering controls

Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapours below there respective threshold limit value. Ensure eyewash stations and safety showers are close to the workstation location.

Eye / face protection Skin protection Handprotection

Avoid contact with eyes. If splashes are likely to occur, wear: safety glasses with side-shields.

Rubber gloves.

Skin protection - Other

Wear suitable protective clothing.

Respiratory protection

No personal respiratory protective equipment normally required. In case of insufficient ventilation wear suitable respiratory equipment.

8.2.3. Environmental exposure controls

Prevent further leakage or spillage if safe to do so.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Revision 11
Revision date 2022-11-17

9.1. Information on basic physical and chemical properties

Appearance Liquid Colour Clear Odour Characteristic Odour threshold No data available 13 pН **Melting point** No data available Initial boiling point No data available No data available **Evaporation rate** Flammability (solid, gas) No data available Vapour pressure No data available **Relative Vapour Density** No data available **Density / Relative Density** 1.068 - 1.075 g/cm3 Partition coefficient No data available No data available Autoignition temperature Viscosity < 50 centipoise **Explosive properties** No data available Oxidising properties No data available Solubility Soluble in water

9.2. Other information

Conductivity
Surface tension
Gas group
Benzene Content
Lead content
VOC (Volatile organic compounds)
No data available

9.2.1. Information with regard to physical hazard classes

No data is available on this product.

9.2.2. Other safety characteristics

No data is available on this product.

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under normal conditions.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Strong acids. Strong oxidising agents.

10.4. Conditions to avoid

Protect from frost.

10.5. Incompatible materials

No incompatible groups noted.

10.6. Hazardous decomposition products

No Hazardous decomposition products when stored and handled correctly.

SECTION 11: Toxicological information

Revision 11 Revision date 2022-11-17

11.1 Information on hazard classes

	This mixture has not been tested as a whole for health effects. The health effects have been calculated using the methods outlined in Regulation (EC) No 1272/2008 (CLP).
Acute toxicity	based on available data the classification criteria are not met.
	Oral ATE = >10,000 mg/kg.
	Dermal ATE = >10,000 mg/kg.
	Inhalation - Dust/Mist ATE = >20 mg/l.
Skin corrosion/irritation	Skin Corr. 1A: H314 - Causes severe skin burns and eye damage. Extreme pH - ≥ 11.5.
Serious eye damage/irritation	Causes serious eye damage.
Respiratory or skin	based on available data the classification criteria are not met.
sensitisation	
Germ cell mutagenicity	based on available data the classification criteria are not met.
Carcinogenicity	based on available data the classification criteria are not met.
Reproductive toxicity	based on available data the classification criteria are not met.
STOT-single exposure	based on available data the classification criteria are not met.
STOT-repeated exposure	based on available data the classification criteria are not met.
Aspiration hazard	based on available data the classification criteria are not met.
Repeated or prolonged	based on available data the classification criteria are not met.
exposure	
11.1.2. Mixtures	

No data available.

11.1.3. Hazard Information

No data available.

11.1.4. Toxicological Information

2-butoxyethanol	Dermal Rat LD50: 1100 mg/kg	Oral Rat LD50: 1300 mg/kg
	Inhalation Rat LC50/4 h: 11.0 mg/l	
C9-11 Alcohol, ethoxylated	Dermal Rat LD50: > 2000 mg/kg	Oral Rat LD50 = >300 - <= 2000
		mg/kg:
sodium (xylenes and	Oral Rat LD50: > 7200 mg/kg	Dermal Rabbit LD50: > 2000 mg/kg
4-ethylbenzene) sulfonate		
	Inhalation Rat LC50/4 h: >6.41 mg/l	
Sodium Metasilicate	Dermal Rat LD50: >5,000 mg/kg	
Pentahydrate		

11.2 Information on other hazards

No data is available on this product.

SECTION 12: Ecological information

12.1. Toxicity

2-butoxyethanol	Daphnia EC50/48h: 1550.0000 mg/l	Algae EC50/72h: 1840 mg/
	Rainbow trout LC50/96h: 1474 mg/l	
	EC50 for marine or freshwater >100.0000 mg/l	LC50 for marine or freshwater >100.0000 mg/l
	organisms	organisms
sodium (xylenes and	Daphnia EC50/48h: 1000.0000 mg/l	Green algae EC50/96h: 230 mg/l
4-ethylbenzene) sulfonate		
	Rainbow trout LC50/96h: >1000 mg/l	
Sodium Metasilicate	Daphnia EC50/48h: 1700.0000 mg/l	Algae EC50/72h: 207 mg/l
Pentahydrate		
	Brachydanio Rerio LC50/96h: 210 mg/l	

12.2. Persistence and degradability

Substance biodegrades at a moderate rate and inherently biodegradable according to the OECD

Revision 11
Revision date 2022-11-17

12.2. Persistence and degradability		
	guide lines.	
12.3. Bioaccumulative potential		
	The product is not bioaccumulating.	
Partition coefficient		
	Supagard Wheel Cleaner No data available 2-butoxyethanol 0.8 log P	
12.4. Mobility in soil		
12.4. Wobinty III Son	This product is coluble in water	
12.5. Results of PBT and vPvB	This product is soluble in water.	
12.5. Results of FBT and VFVB		
40.6 Fordersine dismunting proper	This substance/mixture is not classified as PBT or vPvB according to current criteria.	
12.6 Endocrine disrupting prope		
40.7.04	No data is available on this product.	
12.7. Other adverse effects		
	No data is available on this product.	
SECTION 13: Disposal cons	iderations	
13.1. Waste treatment methods		
	Dispose of waste and residues in accordance with local authority requirements.	
General information		
	Dispose of in compliance with all local and national requirements.	
Disposal of packaging		
	Do NOT reuse empty containers. Empty containers can be sent to landfill after cleaning, if in	
	compliance with local and national regulations.	
SECTION 14: Transport info	rmation	
Hazard pictograms		
	8	
14.1. UN number		
	UN1760	
14.2. UN proper shipping name		
	CORROSIVE LIQUID, N.O.S. (Contains Sodium Metasilicate Pentahydrate)	
14.3. Transport hazard class(es)		
ADR/RID	8	
Subsidiary risk	-	
IMDG	8	
Subsidiary risk		
IATA Subsidiary risk		
14.4. Packing group	l ⁻	
Packing group		

Revision 11
Revision date 2022-11-17

14.5. Environmental hazards	
Environmental hazards	No
Marine pollutant	No
14.6. Special precautions for user	
	No additional special precautions.
14.7 Maritime Transport in bulk according to IMO instruments	
	Not applicable.
ADR/RID	
Hazard ID	80
Tunnel Category	(E)
IMDG	
EmS Code	F-A S-B
IATA	
Packing Instruction (Cargo)	856
Maximum quantity	60 L
Packing Instruction	852
(Passenger)	
Maximum quantity	5L

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulations

REGULATION (EC) No 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.

COMMISSION REGULATION (EU) No 453/2010 of 20 May 2010 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.

COMMISSION REGULATION (EU) 2020/878 of 18 June 2020 amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).

15.2. Chemical safety assessment

No information available

SECTION 16: Other information

Other information

Revision This document differs from the previous version in the following areas:.

- 2 Other hazards.
- 2 Further information.
- 2 SUPPLEMENTAL HAZARD INFORMATION.
- 9 9.2.2. Other safety characteristics.
- 9 9.2.1. Information with regard to physical hazard classes.
- 10 10.2. Chemical stability.
- 10 10.1. Reactivity.

Revision 11
Revision date 2022-11-17

Other information		
	11 - Acute toxicity.	
	11 - Repeated or prolonged exposure.	
	11 - 11.2 Information on other hazards.	
	12 - 12.1. Toxicity.	
	12 - 12.6 Endocrine disrupting properties.	
	12 - 12.7. Other adverse effects.	
	15 - Regulations.	
Data sources	Classification and Procedure used to derive the classification for mixtures according to Regulation	
	(EC) No. 1272/2008, as retained and amended in UK law.	
	Skin Corr. 1A: H314 - Causes severe skin burns and eye damage Extreme pH - ≥ 11.5.	
Text of Hazard Statements in	Acute Tox. 4: H302 - Harmful if swallowed.	
Section 3	Eye Dam. 1: H318 - Causes serious eye damage.	
	Eye Irrit. 2: H319 - Causes serious eye irritation.	
	Acute Tox. 4: H302+H312+H332 - Harmful if swallowed, in contact with skin or if inhaled	
	Skin Irrit. 2: H315 - Causes skin irritation.	
	Met. Corr. 1: H290 - May be corrosive to metals.	
	Skin Corr. 1B: H314 - Causes severe skin burns and eye damage.	
	STOT SE 3: H335 - May cause respiratory irritation.	
Further information		
	The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.	