

# SAFETY DATA SHEET

PITSTOP OIL

Page: 1

Compilation date: 02.01.2024

Revision date: 02.01.2024

Revision No: 1

## Section 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

**Product name:** PITSTOP OIL

**Product code:** HC8020

**Synonyms:** HC8020

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Use of substance / mixture:** Aerosol lubricant.

### 1.3. Details of the supplier of the safety data sheet

**Company name:** SUPAGARD LIMITED

23 Gavinton Street

Muirend

Glasgow

Scotland

G44 3EF

**Tel:** 0141 633 5933

**Email:** james@supagard.co.uk

### 1.4. Emergency telephone number

**Emergency tel:** 0141 633 5933

(office hours only)

## Section 2: Hazards identification

### 2.1. Classification of the substance or mixture

**Classification under CLP:** STOT SE 3: H336; Aquatic Chronic 2: H411; Flam. Aerosol 1: H222; -: H229

**Most important adverse effects:** Extremely flammable aerosol. Pressurised container: May burst if heated. May cause drowsiness or dizziness. Toxic to aquatic life with long lasting effects.

### 2.2. Label elements

**Label elements:**

**Hazard statements:** H222: Extremely flammable aerosol.

H229: Pressurised container: May burst if heated.

H336: May cause drowsiness or dizziness.

H411: Toxic to aquatic life with long lasting effects.

**Hazard pictograms:** GHS02: Flame

GHS07: Exclamation mark

GHS09: Environmental

[cont...]

# SAFETY DATA SHEET

PITSTOP OIL

Page: 2



**Signal words:** Danger

**Precautionary statements:** P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P211: Do not spray on an open flame or other ignition source.  
P251: Do not pierce or burn, even after use.  
P410+P412: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.  
P102: Keep out of reach of children.  
P260: Do not breathe vapours.  
P262: Do not get in eyes, on skin, or on clothing.  
P280: Wear protective gloves/protective clothing/eye protection/face protection.  
P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

## 2.3. Other hazards

**Other hazards:** In use, may form flammable / explosive vapour-air mixture.

**PBT:** This product is not identified as a PBT/vPvB substance.

## Section 3: Composition/information on ingredients

### 3.2. Mixtures

#### Hazardous ingredients:

HYDROCARBONS C6-C7 ISOALKANES, CYCLICS, <5% N-HEXANE, <0.1% BENZENE - REACH registered number (s): 01-2119475514-35-XXXX

EINECS	CAS	PBT / WEL	CLP Classification	Percent
265-151-9	64742-49-0	-	Flam. Liq. 2: H225; STOT SE 3: H336; Asp. Tox. 1: H304; Aquatic Chronic 2: H411; Skin Irrit. 2: H315	30-50%

PROPANE, <0.1% 1,3 BUTADIENE - REACH registered number(s): 01-2119486944-21-XXXX

200-827-9	74-98-6	Substance with a Community workplace exposure limit.	Flam. Gas 1: H220; Press. Gas: H280	10-30%
-----------	---------	--	-------------------------------------	--------

[cont...]

# SAFETY DATA SHEET

PITSTOP OIL

Page: 3

BUTANE, <0.1% 1,3 BUTADIENE - REACH registered number(s): 01-2119474691-32-XXXX

203-448-7	106-97-8	Substance with a Community workplace exposure limit.	Flam. Gas 1: H220; Press. Gas: H280	10-30%
-----------	----------	--	-------------------------------------	--------

NAPHTHENIC PROCESS OIL, SOLVENT REFINED, NEUTRAL, <3% DMSO - REACH registered number(s): 01-2119467170-45-XXXX

-	64742-52-5	Substance with a Community workplace exposure limit.	-	1-10%
---	------------	--	---	-------

## Section 4: First aid measures

### 4.1. Description of first aid measures

**Skin contact:** Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water.

**Eye contact:** Bathe the eye with running water for 15 minutes. Consult a doctor.

**Ingestion:** Wash out mouth with water. Do not induce vomiting. If conscious, give half a litre of water to drink immediately. Consult a doctor.

**Inhalation:** Remove casualty from exposure ensuring one's own safety whilst doing so. Move to fresh air in case of accidental inhalation of vapours. Consult a doctor.

### 4.2. Most important symptoms and effects, both acute and delayed

**Skin contact:** There may be irritation and redness at the site of contact.

**Eye contact:** There may be irritation and redness. The eyes may water profusely.

**Ingestion:** There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur. There may be vomiting.

**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest.

**Delayed / immediate effects:** Immediate effects can be expected after short-term exposure.

### 4.3. Indication of any immediate medical attention and special treatment needed

**Immediate / special treatment:** Not applicable.

## Section 5: Fire-fighting measures

### 5.1. Extinguishing media

**Extinguishing media:** Alcohol or polymer foam. Carbon dioxide. Dry chemical powder. Use water spray to cool containers.

### 5.2. Special hazards arising from the substance or mixture

**Exposure hazards:** Highly flammable. In combustion emits toxic fumes. Forms explosive air-vapour mixture. Vapour may travel considerable distance to source of ignition and flash back. Aerosol cans may explode during a fire, giving a high speed projectile.

### 5.3. Advice for fire-fighters

**Advice for fire-fighters:** Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

[cont...]

# SAFETY DATA SHEET

PITSTOP OIL

Page: 4

## Section 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions:** Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Eliminate all sources of ignition. Cover leaking can until the discharge has stopped, before attempting cleanup operations. Spillage will create slippery surface.

### 6.2. Environmental precautions

**Environmental precautions:** Do not discharge into drains or rivers. Contain the spillage using bunding.

### 6.3. Methods and material for containment and cleaning up

**Clean-up procedures:** Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method. Do not use equipment in clean-up procedure which may produce sparks. Wash the ground with an appropriate self-emulsifying solvent.

### 6.4. Reference to other sections

**Reference to other sections:** Refer to section 8 of SDS.

## Section 7: Handling and storage

### 7.1. Precautions for safe handling

**Handling requirements:** Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of mists in the air. Smoking is forbidden. Use non-sparking tools.

### 7.2. Conditions for safe storage, including any incompatibilities

**Storage conditions:** Store in a cool, well ventilated area. Keep away from sources of ignition. Keep away from direct sunlight.

### 7.3. Specific end use(s)

**Specific end use(s):** No data available.

## Section 8: Exposure controls/personal protection

### 8.1. Control parameters

**Hazardous ingredients:**

**HYDROCARBONS C6-C7 ISOALKANES, CYCLICS, <5% N-HEXANE, <0.1% BENZENE**

[cont...]

# SAFETY DATA SHEET

PITSTOP OIL

Page: 5

## Workplace exposure limits:

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	1100 mg/m <sup>3</sup>	2200 mg/m <sup>3</sup>	-	-

## Respirable dust:

### PROPANE, <0.1% 1,3 BUTADIENE

UK	Asphyxiating	Asphyxiating	-	-
----	--------------	--------------	---	---

### BUTANE, <0.1% 1,3 BUTADIENE

UK	1450 mg/m <sup>3</sup>	1810 mg/m <sup>3</sup>	-	-
----	------------------------	------------------------	---	---

### NAPHTHENIC PROCESS OIL, SOLVENT REFINED, NEUTRAL, <3% DMSO

UK	5 mg/cm <sup>3</sup>	10 mg/cm <sup>3</sup>	-	-
----	----------------------	-----------------------	---	---

## DNEL/PNEC Values

DNEL / PNEC No data available.

## 8.2. Exposure controls

**Engineering measures:** Ensure there is sufficient ventilation of the area. Ensure lighting and electrical equipment are not a source of ignition.

**Respiratory protection:** Self-contained breathing apparatus must be available in case of emergency.

**Hand protection:** Impermeable gloves.

**Eye protection:** Safety glasses. Ensure eye bath is to hand.

**Skin protection:** Impermeable protective clothing.

## Section 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

**State:** Aerosol

**Colour:** Cream

**Odour:** Paraffinic

**Evaporation rate:** Fast

**Solubility in water:** Insoluble

**Viscosity:** Viscosity develops on drying.

**Boiling point/range°C:** Not applicable.

**Melting point/range°C:** Not applicable.

**Flammability limits %: lower:** 0.8

**upper:** 9.0

**Flash point°C:** -40

**Part.coeff. n-octanol/water:** Not applicable.

**Autoflammability°C:** >230

**Vapour pressure:** Not applicable.

**Relative density:** Not applicable.

**pH:** Not applicable.

**VOC g/l:** Not applicable.

### 9.2. Other information

**Other information:** No data available.

[cont...]

# SAFETY DATA SHEET

PITSTOP OIL

Page: 6

## Section 10: Stability and reactivity

### 10.1. Reactivity

**Reactivity:** Stable under recommended transport or storage conditions.

### 10.2. Chemical stability

**Chemical stability:** Stable under normal conditions. Stable at room temperature.

### 10.3. Possibility of hazardous reactions

**Hazardous reactions:** Hazardous reactions will not occur under normal transport or storage conditions.  
Decomposition may occur on exposure to conditions or materials listed below.

### 10.4. Conditions to avoid

**Conditions to avoid:** Heat. Hot surfaces. Sources of ignition. Flames. Direct sunlight.

### 10.5. Incompatible materials

**Materials to avoid:** Strong oxidising agents. Strong acids.

### 10.6. Hazardous decomposition products

**Haz. decomp. products:** In combustion emits toxic fumes.

## Section 11: Toxicological information

### 11.1. Information on toxicological effects

#### Hazardous ingredients:

#### HYDROCARBONS C6-C7 ISOALKANES, CYCLICS, <5% N-HEXANE, <0.1% BENZENE

DERMAL	RBT	LD50	3350	mg/kg
ORAL	RAT	LD50	16750	mg/kg
VAPOURS	RAT	4H LC50	259	g/l

#### Relevant hazards for product:

Hazard	Route	Basis
STOT-single exposure	-	Hazardous: calculated

### Symptoms / routes of exposure

**Skin contact:** There may be irritation and redness at the site of contact.

**Eye contact:** There may be irritation and redness. The eyes may water profusely.

**Ingestion:** There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur. There may be vomiting.

**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest.

**Delayed / immediate effects:** Immediate effects can be expected after short-term exposure.

[cont...]

# SAFETY DATA SHEET

PITSTOP OIL

Page: 7

## Section 12: Ecological information

### 12.1. Toxicity

**Hazardous ingredients:**

**HYDROCARBONS C6-C7 ISOALKANES, CYCLICS, <5% N-HEXANE, <0.1% BENZENE**

Daphnia magna	48H EC50	17.06	mg/l
RAINBOW TROUT (Oncorhynchus mykiss)	96H LC50	9.766	mg/l

### 12.2. Persistence and degradability

**Persistence and degradability:** The product is expected to be biodegradable

### 12.3. Bioaccumulative potential

**Bioaccumulative potential:** No bioaccumulation potential.

### 12.4. Mobility in soil

**Mobility:** Readily absorbed into soil. Volatile. Insoluble in water. Floats on water. Vapour is heavier than air.

### 12.5. Results of PBT and vPvB assessment

**PBT identification:** This product is not identified as a PBT/vPvB substance.

### 12.6. Other adverse effects

**Other adverse effects:** Toxic to aquatic organisms. Toxic to soil organisms.

## Section 13: Disposal considerations

### 13.1. Waste treatment methods

**Disposal operations:** Transfer to a suitable container and arrange for collection by specialised disposal company.

**Recovery operations:** Recycling/reclamation of metals and metal compounds.

**Waste code number:** 16 05 05

**Disposal of packaging:** Empty cans must not be burned because of explosion hazard. Recycle container where permitted. Disposal of waste containers must be done in accordance with local and / or national regulations.

**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

## Section 14: Transport information

### 14.1. UN number

**UN number:** UN1950

[cont...]

# SAFETY DATA SHEET

PITSTOP OIL

Page: 8

## 14.2. UN proper shipping name

Shipping name: AEROSOLS

## 14.3. Transport hazard class(es)

Transport class: 2

## 14.4. Packing group

## 14.5. Environmental hazards

Environmentally hazardous: Yes

Marine pollutant: No

## 14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: D

Transport category: 2

## Section 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

**Specific regulations:** This product is not, nor does it contain a persistent organic pollutant (POP) according to Regulation (EC) 2019/1021 and subsequent revisions. This product is not, nor does it contain any candidate on the REACH SVHC list according to Regulation (EC) 2006/1907 and subsequent revisions. This product is not, nor does it contain, any candidate on the Endocrine Disruptor list, and any subsequent revisions, classified for human health cat 2 or environmental cat 2, in accordance with EC1272/2008 (amended 2022)

### 15.2. Chemical Safety Assessment

**Chemical safety assessment:** A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

## Section 16: Other information

### Other information

**Other information:** This safety data sheet is prepared in accordance with Commission Regulation (EU) No 2015/830.

All substances in this preparation are registered within UK/EU/EFTA countries under the REACH (UK/EC) (amended) regulations, EC 1907/2006

IMPORTANT NOTE:

Risk phases in this section below relate to the INDIVIDUAL COMPONENTS in the formulation when used at their FULL CONCENTRATIONS, and not at the reduced levels in the mixed product.

See sections 2 and 3 for the calculated hazard and risk phrases for the blended product.

**Phrases used in s.2 and s.3:** H220: Extremely flammable gas.

H222: Extremely flammable aerosol.

[cont...]



## **SAFETY DATA SHEET**

PITSTOP OIL

**Page: 9**

H225: Highly flammable liquid and vapour.

H229: Pressurised container: May burst if heated.

H304: May be fatal if swallowed and enters airways.

H315: Causes skin irritation.

H336: May cause drowsiness or dizziness.

H411: Toxic to aquatic life with long lasting effects.

**Legal disclaimer:** The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product. For professional and industrial use only.