DIESEL FUEL ADDITIVE

Page: 1

Compilation date: 24/11/2021

Revision date: 14/05/2024

Revision No: 3

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: DIESEL FUEL ADDITIVE

Product code: HC1713 **Synonyms:** PD0418

HC1713 / SUP

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: PC13: Fuels.

1.3. Details of the supplier of the safety data sheet

Company name: SUPAGARD LIMITED

23 Gavinton Street

Muirend
Glasgow
Scotland
G44 3EF

Tel: 0141 633 5933

Email: james@supagard.co.uk

1.4. Emergency telephone number

Emergency tel: 0141 633 5933

(office hours only)

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Aquatic Chronic 3: H412; Skin Sens. 1B: H317; STOT SE 3: H336; Asp. Tox. 1: H304

Most important adverse effects: May be fatal if swallowed and enters airways. May cause an allergic skin reaction. May

cause drowsiness or dizziness. Harmful to aquatic life with long lasting effects.

2.2. Label elements

Label elements:

Hazard statements: H304: May be fatal if swallowed and enters airways.

H317: May cause an allergic skin reaction. H336: May cause drowsiness or dizziness.

H412: Harmful to aquatic life with long lasting effects.

Hazard pictograms: GHS07: Exclamation mark

GHS08: Health hazard

DIESEL FUEL ADDITIVE

Page: 2





Signal words: Danger

Precautionary statements: P102: Keep out of reach of children.

P280: Wear protective gloves/protective clothing/eye protection/face protection. P301+P310: IF SWALLOWED: Immediately call a POISON CENTER or doctor.

P331: Do NOT induce vomiting.

P302+P350: IF ON SKIN: Gently wash with plenty of soap and water.

P403+P233: Store in a well-ventilated place. Keep container tightly closed.

P501: Dispose of contents and container to a hazardous or special waste collection

point.

Haz. ingredients (label): HYDROCARBONS, C11-C14, ISOALKANES, LOW AROMATICS; HYDROCARBONS, C10,

AROMATICS, >1% NAPHTHALENE; 1H-BENZOTRIAZOLE-1-METHANAMINE (MIXED

REACTION MASS ISOMERS)

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

HYDROCARBONS, C11-C14, ISOALKANES, LOW AROMATICS - REACH registered number(s): 01-2119456620-43-XXXX

EINE	CS CAS	PBT / WEL	CLP Classification	Percent
926-141-	6 64742-47-8	-	Asp. Tox. 1: H304; -: EUH066	50-70%

HYDROCARBONS, C10, AROMATICS, >1% NAPHTHALENE - REACH registered number(s): 01-2119463588-24-XXXX

919-284-0	_	-	STOT SE 3: H336; Aquatic Chronic 2:	10-30%
			H411; Carc. 2: H351; Asp. Tox. 1: H304	

C7-9-ALKYL-3-(3,5-DI-TET-BUTYL-4-HYDOXYPHENYL)PROPIONATE - REACH registered number(s): 01-2119873226-29-XXXX

-	125643-61-	-	Aquatic Chronic 4: H413	1-10%
	10			

2-ETHYLHEXAN-1-OL - REACH registered number(s): 1-2119487289-20-XXXX

203-234-3	104-76-7	-	Skin Irrit. 2: H315; STOT SE 3: H335;	1-10%
			Acute Tox. 4: H332; Eye Irrit. 2: H319	

DIESEL FUEL ADDITIVE

Page: 3

1H-BENZOTRIAZOLE-1-METHANAMINE (MIXED REACTION MASS ISOMERS) - REACH registered number(s): 1-2119982395-25-XXXX

939-700-4	-	-	Skin Irrit. 2: H315; Skin Sens. 1B:	<1%
			H317; Aquatic Acute 1: H400; Aquatic	
			Chronic 2: H411	

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Wash immediately with plenty of soap and water. **Eye contact:** Bathe the eye with running water for 15 minutes.

Ingestion: Wash out mouth with water. Do not induce vomiting. If conscious, give half a litre of water

to drink immediately. Transfer to hospital as soon as possible.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Move to

fresh air in case of accidental inhalation of vapours. Consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be soreness and redness of the mouth and throat. There may be difficulty

swallowing. Nausea and stomach pain may occur. There may be vomiting.

Inhalation: Absorption through the lungs can occur causing symptoms similar to those of ingestion.

4.3. Indication of any immediate medical attention and special treatment needed

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray

to cool containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact

with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. Mark out the contaminated area

with signs and prevent access to unauthorised personnel. Turn leaking containers

leak-side up to prevent the escape of liquid.

DIESEL FUEL ADDITIVE

Page: 4

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for

disposal by an appropriate method. Wash the ground with an appropriate self-

emulsifying solvent.

6.4. Reference to other sections

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid the formation or spread of mists in the air. Avoid direct contact with the substance.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed.

7.3. Specific end use(s)

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

HYDROCARBONS, C11-C14, ISOALKANES, LOW AROMATICS

Workplace exposure limits:

Respirable dust:

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	1200 mg/cm3	-	-	-

HYDROCARBONS, C10, AROMATICS, >1% NAPHTHALENE

UK	Not established		
Ur	INUL ESTABLISHED	- 1	 <u>-</u>

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: Respiratory protection not required.

Hand protection: Protective gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing.

Section 9: Physical and chemical properties

DIESEL FUEL ADDITIVE

Page: 5

9.1. Information on basic physical and chemical properties

State: Liquid

Colour: Pale yellow

Odour: Paraffinic

Evaporation rate: Slow

Solubility in water: Insoluble

Viscosity: Non-viscous

Boiling point/range°C: >100 Melting point/range°C: No data available.

Flammability limits %: lower: 0.6 upper: 7.0

Flash point°C: 68 Part.coeff. n-octanol/water: No data available.

Autoflammability°C: No data available. Relative density: 0.810

pH: Not applicable. VOC g/I: No data available.

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

10.4. Conditions to avoid

Conditions to avoid: Heat.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

HYDROCARBONS, C11-C14, ISOALKANES, LOW AROMATICS

DERMAL	RBT	LD50	>5000	mg/kg	

DIESEL FUEL ADDITIVE

Page: 6

ORAL	RAT	LD50	>5000	mg/kg
VAPOURS	RAT	4H LC50	>5000	mg/kg

HYDROCARBONS, C10, AROMATICS, >1% NAPHTHALENE

DERMAL	HMN	LD50	Low acute	-
ORAL	HMN	LD50	Low acute	-
VAPOURS	HMN	LD50	Low acute	-

Relevant hazards for product:

Hazard	Route	Basis
Respiratory/skin sensitisation	-	Hazardous: calculated
STOT-single exposure	-	Hazardous: calculated
Aspiration hazard	-	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be soreness and redness of the mouth and throat. There may be difficulty

swallowing. Nausea and stomach pain may occur. There may be vomiting.

Inhalation: Absorption through the lungs can occur causing symptoms similar to those of ingestion.

Section 12: Ecological information

12.1. Toxicity

Hazardous ingredients:

HYDROCARBONS, C11-C14, ISOALKANES, LOW AROMATICS

Daphnia magna	48H EC50	>250	mg/l
RAINBOW TROUT (Oncorhynchus mykiss)	96H LC50	>1000	mg/l

HYDROCARBONS, C10, AROMATICS, >1% NAPHTHALENE

DAPHNIA	48H EC50	<10	mg/l
RAINBOW TROUT (Oncorhynchus mykiss)	96H LC50	<5	mg/l

12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil. Volatile. Insoluble in water. Floats on water. Vapour is heavier

than air.

DIESEL FUEL ADDITIVE

Page: 7

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Harmful to aquatic organisms.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal

company.

Recovery operations: Solvent reclamation/regeneration.

Waste code number: 20 01 13

Disposal of packaging: Dispose of as normal industrial waste. Clean with water.

NB: The user's attention is drawn to the possible existence of regional or national

regulations regarding disposal.

Section 14: Transport information

Transport class: This product does not require a classification for transport.

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture

by the supplier.

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No

2015/830.

IMPORTANT NOTE:

Risk phases in this section below relate to the INDIVIDUAL COMPONENTS in the

formulation when used at their FULL CONCENTRATIONS, and not at the reduced levels

in the mixed product.

See sections 2 and 3 for the calculated hazard and risk phrases for the blended product.

Phrases used in s.2 and s.3: EUH066: Repeated exposure may cause skin dryness or cracking.

H304: May be fatal if swallowed and enters airways.

H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H319: Causes serious eye irritation.

DIESEL FUEL ADDITIVE

Page: 8

H332: Harmful if inhaled.

H335: May cause respiratory irritation.

H336: May cause drowsiness or dizziness.

H351: Suspected of causing cancer (if inhaled).

H400: Very toxic to aquatic life.

H411: Toxic to aquatic life with long lasting effects.

H412: Harmful to aquatic life with long lasting effects.

H413: May cause long lasting harmful effects to aquatic life.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive

and shall be used only as a guide. This company shall not be held liable for any

damage resulting from handling or from contact with the above product.